



# Mounting Tape

## 03410

### Technical Data Sheet

3M Part No.(s)	3M Part Descriptor(s)
03410	3M™ Mounting Tape

**Product Description** 3M™ Mounting Tape is a double sided tape designed with pressure sensitive adhesive on both sides of an acrylic foam core. 3M™ Mounting Tape is suitable for attaching automotive exterior trim parts such as body side-moldings and cladding to automotive painted surfaces. It can also be used for mounting small items to interior surfaces, such as dashboards. This tapes medium density acrylic foam core provides a balance of strength and conformability allowing it to elongate and then relax under load.

Features, Advantages, Benefits	Features	Advantages	Benefits
	1. Acrylic foam core with unique viscoelastic properties	1. Will elongate and relax under load to minimize stress on the adhesive bond	1. For mounting to interior car surfaces
	2. Liner side adhesive bonds well to automotive painted surfaces	2. Medium foam density for a balance of conformability and strength	2. For the attachment of automotive trim parts such as body side moldings to automotive paint surfaces
	3. Non-liner side: bonds well to trim materials	3. Dual-sided adhesive each with unique adhesion properties	3. Can be used for interior and exterior automotive applications

### Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

<b>Dimensions</b>	1/2 in. x 75 in. - 24 rolls per case
<b>Thickness</b>	0.045 in. (1.14 mm)
<b>Density</b>	43 lb/ft <sup>2</sup> (688 kg/m <sup>3</sup> )
<b>Breakaway Peel after 72 hours at 72°F (22°C)</b>	25 lb/0.5 in.
<b>Continuing Peel after 72 hours at 72°F (22°C)</b>	9 lbs/0.5 in.

### Product Uses

3M™ Mounting Tape is used to mount small items to dashboards and other interior automotive surfaces. This tape will also bond well to automotive pain surfaces on the liner side and trim materials on the non-liner side.

# 3M™ Mounting Tape

03410

---

## Applications

Applications for this tape include, but may not be limited to, attachment of body side moldings, roof ditch moldings, appliques, and wheel flares to exterior vehicle surfaces and mounting small items to interior surfaces like dashboards.

---

## Shelf Life

This product should be stored at 72°F (22°C) and 50% relative humidity for up to one year from date of purchase.

---

## Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

---

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

## Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.