3M Automotive Aftermarket Division

Third Party Recommendations, Approvals, & Endorsements

Image: Note of the state o

| | | | al Service | 100 to 1 | 2014 | |
|---------|-------------------------------|--|--|--|---|-------------|
| | | | OORBOARD AREA | ACDEL 2014-01 | | |
| (Table) | ICE NOVISION | 1 150-40-408-404 | 11 Internation In Internation in Internation is had | dd fer Anlected Vehicles, u idoed and indicated by 4 | | |
| 100000 | | | | standers William | Second 1 | |
| Call | water may se wothom of the | ep into the beadline "A" of "O" plans into make the door a | and due to the following poe note respect, counting a two due to lowings at two the fourth and a start it has bosine adapt of the and a start within the front or the or too when the bost or the or too when the bost or the the full due and the built | or's waterproof tim, due tet doors | 20 Alle Conier | |
| | FFECTED | | | | | 111111 |
| A | 104 - on End | eavor | | | | 111111 |
| | | | | | | 111111 |
| | | not Rail some more | | The set dide | the covers off. The | 111111 |
| | A To P | ne cool raik. move the root rail mil converts will be dem | nationg upwers, release the space during removal and o pairwaters strong the runt re- mounting upwers. Replace | installiner table unter musit be replaced. Il body seattra on both si a the center covers. | des. | WHII. |
| | 2 HODAY ON | Sealard rais and its | | | | - 11111 5 1 |
| | 1 | 0 | Leakage at Door. 1. Remove the door. 2. Check for exclusion the webstycol fill 3. Dry the midd of a of website (dd) | give patter. Do not put on or of worker indicate is not in along the boltom and or tankeds under the tim. Andolf Water Mittom Sealer and get, allows 3 inches for | sites Apply a second bead criss?1 or reprivation() in the edge of the fam. | |
| | RUM | | tion to the door. Press to o use a heat gun to warm th | security set the Sim and b | ealard. | |
| | | each the waterproof | lien to the door. Physis to | ne door and film surfaces. | D Deber | |
| | NOTE | tenay be necessary to be time to the class. | Care a river your in the | | | |
| 1 | Contr | the film to the book | | Industriation Binder | (2117) | |
| 1 | PLAN | eta. | HEPAIR, in the Dealer Ser | | | |
| 1 | - | Chindle and a com | | | | |
| 1 | | | | | | |

Everyday, engineers and technicians around the world choose 3M products as the best solution for their manufacturing and repair needs. From Specifications and Endorsements to Service Bulletins and Recall Notices, 3M is proud to be a trusted partner of the Automotive Industry.

Here's just one example...



Reference Information

| D / | |
|---------------------------------------|---|
| Organization: | Mitsubishi Motors North America, Inc. |
| Document Type: Name: Number: | Technical Service Bulletin Water Leaking into Floorboard Area TSB-08-42B-005 |
| Issued: | September 2008 |
| Description Vehicles: Purpose: | 2004 - on Endeavor Water leakage may occur at the floorboard due to the following possible conditions. Water in the floorboard can eventually saturate the silencers under carpet, causing a musty smell. Water may seep into the headliner due to leakage at the roof rail body seam. It may run out at the bottom of the "A" or "D" pillars into the floorboard area. Water may seep inside the door at the lower edge of the door's waterproof film, due to the butyl tape coming loose. This could occur at either the front or rear doors. Condensation from the HVAC can flow onto the carpet due to either a blocked HVAC drain or a deteriorated grommet seal between the HVAC and the bulkhead at the drain. |
| Note: | Seal between the HVAC and the builthead at the drain. 3M provides this information for REFERENCE ONLY. ALWAYS refer to the original document or the OEM-provided model-specific collision damage repair manuals for complete instructions. |
| 3M Products: Included: | PN083703M™ MSP Seam SealerPN086213M™ Windo-Weld™ Round Ribbon Sealer |
| Note: | In some cases, 3M may offer an alternate part number (different size/color) with the same chemistry and/or performance as the included product. Please consult your 3M Representative for more information. |
| | Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. |

3M