

June, 2010

3M™ Preservation Sealing Tape 481

Product Description

3M™ Preservation Sealing Tape 481 has a unique rubber adhesive that provides excellent performance as an industrial and military preservation tape.

Product Features

- Conforms to many irregular surfaces and has excellent stain resistance.
- Effective for many outdoor applications in hot and cold weather over two years with quick, clean removal. Can be certified to Military Specification: SAE-AMS-T-22085 Type II.
- Polyethylene backing provides good conformability to many surfaces.
- Excellent stain resistance to a variety of surfaces.



3M™ Preservation Sealing Tape 481

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Black		
Total Tape Thickness	0.24 mm	9.5 mil	ASTM D3652
Backing Thickness	0.18 mm	7.5 mil	ASTM D3652
Backing	Polyethylene		
Adhesive	Rubber		
Water Vapor Transmission Rate	1.7 g/m ² /24 hr	0.11 g/100 in ² /24 hr	ASTM D3833

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	2.8 N/cm	25 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	26.3 N/cm	240 oz/in	ASTM D3759	
Elongation at Break	500 %		ASTM D3759	
Temperature Use Range	-7 to 77 °C	20 to 170 °F		

3M™ Preservation Sealing Tape 481

Available Sizes

Property	Values	
Standard Roll Length	33 m	36 yd

Handling/Application Information

Application Ideas

- Seals and protects various types of equipment to be stored by military and industry.
- Splicing and patching materials used by the construction industry.

Application Techniques

- Best results are attained when applied to a clean, dry surface at temperatures between 60° to 80°F (16° to 27°C).

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton. To obtain best performance, use this product within 24 months from date of manufacture.

Industry Specifications

Military Specification: SAE-AMS-T-22085 Type II

3M™ Preservation Sealing Tape 481

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.