

# 3M™ Power Tools for Body Repair

## 3M™ Pistol Grip Disc Sander

The 3M™ Pistol Grip Disc Sander is a light-weight tool with the power to grind welds and the size to access small and hard-to-reach areas. Perfect for grinding and sanding applications with our 3M™ Cubitron™ II Fibre Roloc™ Discs.

- Maximize cut speed with 3M™ Cubitron™ II Fibre Roloc™ Discs
- Suitable for both 2 inch and 3 inch discs
- Variable speed adjustment for optimal finish



## 3M™ Cut-Off Wheel Tools

The 3M™ Cut-Off Wheel Tools deliver the performance you need when working with tough automotive substrates. When paired with 3M™ Cubitron™ II Cut-Off Wheels, technicians can slice through even high-strength steel and aluminum with clean, straight lines and minimal effort.

- Power with a 3M™ Cubitron™ II Cut-Off Wheel for a cleaner cut that runs cooler
- Compact design with built-in safety features for easy handling
- Featuring a light-weight composite body for greater user comfort
- Available in 3 inch and 4 inch sizes



## 3M™ Mini File Belt Sander and File Belt Sander

The 3M™ File Belt Sanders allow technicians to access hard-to-reach areas and are great for spot weld removal, deburring, cleaning, and finishing.

- Remove spot welds cleanly and quickly with 3M™ Cubitron™ II File Belts — replacing the need for expensive drills and bits
- Adjustable arm for user comfort and multiple applications
- Available in 13 inch and 18 inch sizes



## 3M™ Pistol Grip Disc Sander

Part No.	Max RPM	Thread Size	Weight lb (kg)	Height in. (mm)	Length in. (mm)	Motor hp (W)
Use with 2 in. (50mm) and 3 in. (75mm) discs*						
<b>33577</b>	18,000	1/4 in. – 20	1.76 (0.8)	2.05 (52)	7.50 (189)	0.45 (336)

\*Tool includes a 2 in. (50mm) and 3 in. (75mm) 3M™ Roloc™ Disc Pad.



PN 33577

## 3M™ Cut-Off Wheel Tools

Part No.	Wheel Size in. (mm)	Max RPM	Thread Size	Weight lb (kg)	Height in. (mm)	Length in. (mm)	Motor hp (W)
ALWAYS USE WITH GUARD							
<b>33579</b>	3 (75)	20,000	1/4 in. – 28	1.91 (0.87)	3.14 (79.6)	7.73 (196)	0.70 (522)
<b>33581</b>	4 (100)	20,000	1/4 in. – 28	2.00 (0.91)	3.42 (86.9)	7.73 (196)	0.70 (522)



PN 33579

## 3M™ Mini File Belt Sander and File Belt Sander

Part No.	Belt Size in. (mm)	Max RPM	Weight lb (kg)	Height in. (mm)	Length in. (mm)	Motor hp (W)
Belt Speed: 4100 SFPM (1250 SMPM)						
<b>33573</b>	3/8 × 13 (10 × 330)	17,000	2.07 (0.94)	2.87 (73)	12.50 (320)	0.65 (485)
<b>33575</b>	1/2 × 18 (13 × 457)	17,000	2.16 (0.98)	2.87 (73)	15.15 (385)	0.65 (485)



PN 33573

Replacement Parts — in. (mm)	
<b>33583</b> Replacement Contact Wheel, 3/8 (10)	<b>33585</b> File Belt Replacement Arm, 3/8 × 13 (10 × 330)
<b>33584</b> Replacement Contact Wheel, 1/2 (13)	<b>33588</b> File Belt Replacement Arm, 1/2 × 18 (13 × 457)

