

3M Science.
Applied to Life.™

3M Respirator Selection Guide



Table of Contents

| | |
|---|------------------------|
| Respirator Selection Criteria | 1 |
| • Respirator Program Management | |
| • Respirator Fit | |
| • Assigned Protection Factors (APF) | |
| • Effects from Skin or Eye Contact | |
| • Human Factors | |
| • Location of Hazardous Areas | |
| • Respirator Characteristics, Capabilities, and Limitations | |
| • General Use Instructions | |
| • General Use Limitations | |
| Format Explanation..... | 4 |
| • Chemical Name | |
| • CAS # | |
| • Synonyms | |
| • IDLH Level | |
| • OEL | |
| • Respirator Recommendations | |
| • Comments | |
| Particulate Filter Definitions | 10 |
| • N-Series | |
| • R-Series | |
| • P-Series | |
| • HEPA | |
| How to Use This Guide | 11 |
| Chemical Compound Guide | 15 |
| Respirator Codes and Descriptions..... | end of document |



WARNING

These respirators help protect against certain airborne particles or gases and vapors only. No respirator is capable of preventing all airborne contaminants from entering the wearer's breathing zone. When respirators are used in conjunction with a respiratory protection program that meets the requirements in OSHA standard 29 CFR 1910.134, they can reduce airborne contaminant concentrations in the breathing zone to below the occupational exposure limit. Misuse of respirators may result in overexposure to the contaminant and cause sickness or death. For this reason, proper respirator selection, training, use, and maintenance are mandatory in order for the wearer to be properly protected.

Respirator Selection Criteria

The 3M™ Respirator Selection Guide includes a list of chemicals for which 3M respirators can be used. This information can be used to supplement general industrial hygiene knowledge. Once workplace contaminants and their concentrations have been identified, the guide can be used to help select an appropriate 3M™ Respirator for nearly 700 chemicals with Threshold Limit Values (TLVs®) or other recommended exposure limits. Because actual conditions vary from one worksite to another, this information is intended only as a guide. Selection of the most appropriate respirator will depend on the particular situation and should be made only by a person familiar with the working conditions and with the benefits and limitations of respiratory protection products. If you have any questions related to proper selection and use of 3M respirators, or the use of this guide.

Respirator Program Management

In the United States, where respirators are in use in the workplace, a formal respiratory protection program must be established covering the basic requirements outlined in the OSHA Respiratory Protection Standard (29 CFR 1910.134). Education and training must be properly emphasized and conducted periodically. Maintenance, cleaning, and storage programs must be established and routinely followed for respirators that are reused.

Respirator Fit

The OSHA Respiratory Protection Standard (29 CFR 1910.134) requires fit testing for all tight-fitting respirators. Whether you select a filtering facepiece (disposable) respirator or a reusable

respirator, the wearer must obtain a satisfactory fit as indicated by a qualitative or quantitative fit test. Worker comfort should also be considered. Removal of the respirator, even for short periods of time, dramatically reduces the protection afforded by the respirator.

Assigned Protection Factors (APF)

The respirator selected must have an assigned protection factor (APF) adequate for the particular workplace exposure. Divide the air contaminant concentration by the occupational exposure limit (OEL) to obtain a hazard ratio. Then select a respirator with an assigned protection factor greater than or equal to that hazard ratio.

Hazard Ratio

$$\text{Hazard Ratio} = \frac{\text{Airborne Contaminant Concentration}}{\text{OEL}}$$

Assigned protection factors* per OSHA 29 CFR 1910.134 are as follows:

Air Purifying Respirators

- Half facepiece (filtering facepiece-disposable and reusable) 10
- Full facepiece..... 50

Powered Air Purifying Respirators

- Loose-fitting facepiece..... 25
- Half facepiece..... 50
- Full facepiece, helmet, or hood 1000**

Supplied Air Respirators (airline)

- Continuous Flow
 - Loose-fitting facepiece..... 25
 - Half facepiece..... 50
 - Full facepiece, helmet, or hood 1000**
- Pressure demand with full facepiece..... 1000

Self-Contained Breathing Apparatus (SCBA)

Pressure demand airline with escape SCBA 10,000 unknown and IDLH atmospheres
 Pressure demand SCBA..... 10,000 unknown and IDLH atmospheres

Effects From Skin or Eye Contact

If a chemical can be absorbed through the skin, skin protection may be required in addition to respiratory protection. Eye protection may also be necessary if not provided by the respirator. Failure to provide adequate skin or eye protection can invalidate established exposure limits and make respirator use ineffective for protection against certain workplace contaminants.

*Assigned protection factors may vary for specific standards as promulgated by OSHA. Where assigned protection factors in local, state, or federal standards are lower than those listed here, they should be used instead. For additional limitations of 3M respiratory protection products, refer to 3M respirator packaging and User Instructions.

** Respirator manufacturer must provide data demonstrating performance of 1000 or greater, otherwise APF of 25.

Human Factors

Consider the entire package of safety equipment required for the job. The respirator selected must be compatible with hard hats, goggles, glasses, welding hoods, faceshields, etc. In addition, the worker must be able to communicate and perform required job duties without removing the respirator. If strenuous work is to be performed, or if the respirator is to be worn for an extended period of time, it may be desirable to select a lightweight respirator with low breathing resistance. If a respirator does not have good worker acceptance and does not stay on the worker's face, it will not provide the protection needed.

Location Of Hazardous Area

When specifying supplied air respirators, consider the distance the worker must travel to get to an uncontaminated work area, as well as obstacles or equipment present in the area. If ladders or scaffolds must be climbed, a supplied air respirator or a combination air purifying/supplied air respirator may not be appropriate.

Respirator Characteristics, Capabilities, and Limitations

A respirator may not be able to help protect against all of the contaminants present in a particular work environment. Specific limitations are stated on the approval labels and are included with User Instructions. These must be carefully reviewed for each respirator before use. General precautionary information is given below. Refer to respirator packaging or User Instructions for specific information.

General Use Instructions

- Failure to follow all instructions and limitations on the use of these respirators and/or failure to wear them during all times of exposure can reduce respirator effectiveness and may result in sickness or death.
- Many of the contaminants that can be dangerous to a person's health include the ones that are so small they cannot be seen or smelled at dangerous levels.
- Before use of any respirator, the wearer must first be trained by the employer in proper respirator use in accordance with applicable safety and health standards.
- The OSHA Respiratory Protection Standard [29 CFR 1910.134(f)(1)] requires that the wearer of any tight-fitting respirator be fit tested.
- Leave the contaminated area immediately if dizziness or other distress occurs, if the respirator becomes damaged or breathing becomes difficult, if contaminants can be smelled or tasted, or if irritation occurs.

General Use Limitations

- These respirators do not supply oxygen.
- Do not use when concentrations of contaminants are immediately dangerous to life or health, when concentrations are unknown, or in atmospheres containing less than 19.5% oxygen.
- Do not abuse or misuse any respirator.
- Do not use tight-fitting respirators or loose-fitting facepieces with beards or other facial hair or conditions that prevent direct contact between the face and the edge of the respirator.
- Do not use when concentrations exceed maximum use concentrations established by regulatory agencies.

Format Explanation

Chemical Name

Chemical names listed in this guide are generally those used in the Threshold Limit Values and Biological Exposure Indices for 2017 published by the American Conference of Governmental Industrial Hygienists (ACGIH). Pesticides and chemicals without established occupational exposure limits are not included. Call 3M Technical Service for assistance in selecting respirators for these chemicals.

CAS

Chemical abstract service registry numbers were established by the American Chemical Society to harmonize chemical identification regardless of the synonym used or differences in spelling.

Synonyms

Several common synonyms are listed in this column.

IDLH Level

This is the concentration considered Immediately Dangerous to Life or Health (IDLH), as published by the National Institute for Occupational Safety and Health (NIOSH) (DHHS [NIOSH] Publication No. 90-117). It specifically refers to the acute respiratory exposure that poses an immediate threat of loss of life, immediate or delayed irreversible adverse effects on health, or acute eye exposure that would prevent escape from a hazardous atmosphere.

The reasons NIOSH established an IDLH at a particular level for a specific chemical are described in Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs), NTIS Publication No. PB-94-195047, May 1994. The 1994 IDLH values established by NIOSH used interim criteria, and OSHA stated in a May 21, 1996 memorandum that OSHA will use the older IDLH values while NIOSH conducts further study regarding the 1994 values. The 1990 IDLH values are used in this guide since OSHA uses these values for enforcement.

For those substances with no IDLH listed, the manufacturer or supplier may have additional chemical information. The Chemical Referral Center operated by the Chemical Manufacturers Association can assist in providing telephone numbers for obtaining information from manufacturers. The lower explosive level (LEL) has been listed when an IDLH value was not located.

The concentration that would result in an oxygen deficient atmosphere should also be considered to be IDLH.

OEL

- The occupational exposure limits listed are 2017 ACGIH Threshold Limit Values (TLVs), unless otherwise stated. From ACGIH®, 2017 TLVs® and BEIs® Book. Copyright 2017. Reprinted with permission. The concentrations are expressed in ppm — parts per million (parts of contaminant per million parts of air) — unless specifically stated as mg/m³ (milligrams of contaminant per cubic meter of air) or some other unit.
- The OSHA Permissible Exposure Limit (PEL) is listed when it is more stringent than the current TLV.
- The 2010 Workplace Environmental Exposure Levels (WEEL) from the American Industrial Hygiene

Association is listed when it is the most stringent value or there is no TLV or PEL.

- Time Weighted Average (TWA) exposure limits are for a normal eight (8) hour workday and a forty (40) hour work-week.
- Short-Term Exposure Limit (STEL) is a 15-minute time weighted average exposure which should not be exceeded at any time during a workday.
- Ceiling (C) exposure limits refer to concentrations that should not be exceeded during any part of the working exposure.
- Exposure limits for particulates are as total dust unless otherwise noted (e.g., inhalable fraction, respirable fraction, respirable fibers, etc.)
- Skin notations indicate the substance can be absorbed through the skin. In these cases, appropriate measures must

be taken to prevent skin and eye contact to avoid invalidating the OEL.

- For a more detailed explanation of TLVs and their proper application, refer to the TLV booklet available for a nominal fee from ACGIH.

Odor Threshold

Odor thresholds have been removed from this version of the guide. While contaminant odor or irritation may serve as a secondary indicator of when to change cartridges, it cannot be used as the primary indicator for when to change.

For more information on odor thresholds, please see relevant publications such as “Odor Thresholds for Chemicals with Established Health Standards, Second Edition. AIHA (2013).”

Respirator Type

This column lists the suggested type of particulate, gas/vapor or supplied air respirator. The abbreviations used are explained at the end of this document.

All of these respirators have not been specifically tested against each compound listed. A review of chemical and physical properties of the materials, as well as adsorption or filtration characteristics of the respirators, forms the basis for the recommendations.

The recommendations are for single substances. When two or more substances are present, a combination respirator may be appropriate. For example, with a spray paint that contains organic solvents and titanium dioxide, a respirator consisting of an organic vapor cartridge and a particle filter may be appropriate. In cases where an air purifying respirator is not available for all of the substances of concern in a mixture, a supplied air respirator may be required.

In some cases, the respirator is preceded by an “(F)” designation. These contaminants have been identified as potential eye irritants. Full facepieces, hoods, helmets or loose fitting facepieces, or half facepieces with appropriate eye protection should be considered.

Do not exceed maximum use concentrations established by regulatory agencies. Follow the protection factor guidelines in specific OSHA standards, and refer to the instructions in the Respirator Selection Criteria and How To Use This Guide sections of this guide.

When a chemical cartridge respirator is recommended, it can only be used if a cartridge change schedule is established as described in 29 CFR 1910.134 (d)(3)(iii) (B) (2). If a change schedule is not established, a supplied air respirator must be used instead.

Comments

Other information may be listed in this column:

- A. Short service life means predicted cartridge life of less than 30 minutes at concentrations of ten times (10X) the OEL, or the contaminant's boiling point is less than 65C. Actual service life will vary considerably depending on concentration levels, temperature, humidity, work rate, etc. See the following literature references for specific details on the conditions and limitations of these estimates:
 1. 3M Company.
3M Service Life Software.
 2. Nelson, G.O. and C.A. Harder.
Respirator Cartridge Efficiency Studies: V. Effect of Solvent Vapor.

Sometimes, a supplied air respirator is recommended because the service life may be so short that the frequency required for changing the cartridges may not be practical.

References to **Ineffective sorbents** or **Unknown sorbent effectiveness** indicate 3M does not make chemical cartridge respirators appropriate for these substances at this time or it is not known how effective the sorbents would be for these materials.

- B. References to a **respirator not being specifically approved** refer to approvals for that particular substance only. All respirators listed in this guide are NIOSH approved for specific substances and/or conditions.

- C. {Comments regarding warning properties have been removed as OSHA allows air purifying respirators to be used against gases and vapors with poor or unknown warning properties. Instead cartridge change schedules based on objective information and data must be established.}
- D. These compounds have been identified as possibly existing in both particulate and vapor phase in the workplace. For these compounds, 3M recommends that a gas/vapor cartridge be used in addition to the traditionally accepted particulate filter. It is the user's responsibility to determine whether both forms coexist. Both chemical properties and use conditions/processes can affect the physical form in the workplace. Users should consider specific exposure data and workplace conditions before making their final selection.* If a chemical cartridge is used, a change schedule must be established to replace the cartridges before the end of their service life.
- E. These compounds have been identified as possibly existing in both vapor and particulate phase in the workplace. Even though these chemicals would be expected to be in the vapor phase, when other aerosols are present or there is high humidity, it is possible that the vapor may be adsorbed onto these coexisting particles or dissolved in available water droplets; therefore, 3M recommends a filter for the particulate phase be used in addition to the traditionally accepted chemical cartridge. It is the user's responsibility to determine whether both forms coexist.
- Both chemical properties and use conditions/processes can affect the physical form in the workplace. Users should consider specific exposure data and workplace conditions before making their final selection.*
- F. It is believed that an N-series filter is sufficient since these materials will not coat the filter fibers, but since this material may contain oil aerosols, an R- or P-series filter is recommended until further research or a regulatory agency takes a specific position.
- G. R- or P-series filters have been recommended pending more research as to how these materials affect the filter fibers.
- H. Listing of 3M **3510, 3530, 3550, or 3720** refers to a 3M™ Personal Air Monitor with Pre-Paid Analysis.

* See Perez, C. and S. C. Soderholm: Some Chemicals Requiring Special Consideration When Deciding Whether to Sample the Particle, Vapor, or Both Phases of an Atmosphere. *Appl. Occup. Hyg.* 6(10): 859-864 (1991).

Monitors may be used to measure the amount of specific contaminants in the air. 3M™ Monitors without pre-paid analysis may be used with analysis performed by a private laboratory.

You should check with the laboratory to determine what other chemicals can be measured with the monitors. An estimate of the airborne concentration is needed for making appropriate respirator selection and establishing a cartridge change schedule.

Particulate Filter Definitions

N-Series Filters: These filters are restricted to use in atmospheres free of oil aerosols. They may be used for any solid or liquid airborne particulate hazard that does not contain oil. Generally these filters should be used and reused subject only to considerations of hygiene, damage, and increased breathing resistance.

R-Series Filters: A filter intended for removal of any particle including oil-based liquid aerosol. They may be used for any solid or liquid airborne particulate hazard. If the atmosphere contains oil, the R-series filter should be used only for a single shift (or for 8 hours of continuous or intermittent use).

P-Series Filters: A filter intended for removal of any particle including oil-based liquid aerosols. They may be used for any solid or liquid particulate airborne hazard. NIOSH requires that respirator manufacturers establish time-use limitations for all P-series filters. 3M recommends that in atmospheres containing oil aerosols, P-series filters should be used and reused for no more than 40 hours of use or 30 days, whichever occurs first, unless the filter needs to be changed for hygiene reasons, is damaged, or becomes difficult to breathe through before the time limit is reached. When used in atmospheres containing non-oil aerosol, 3M P-series filters should be used and reused subject to conditions of hygiene, damage and increased breathing resistance.

Oil: Any of numerous mineral, vegetable and synthetic substances and animal and vegetable fats that are generally slippery, combustible, viscous, liquid or liquefiable at room temperatures soluble in various organic solvents such as ether but not in water.

95 Level Filter

At least 95% filtration efficiency per the NIOSH 42 CFR 84 test method.

100 Level Filter

At least 99.97% filtration efficiency per the NIOSH 42 CFR 84 test method.

HEPA Filter

At least 99.97% filtration efficiency per the NIOSH 42 CFR 84 test method. Filter class for powered air purifying respirators (PAPRs) only. Use instead of N, R, P type filters.

How to Use this Guide

If a respirator is being selected for a single compound listed in this guide with an air concentration not exceeding either the respirator APF times the OEL, or the IDLH, then the respirator identified in the **Respirator** column may be selected. Descriptions of the respirator codes may be found at the end of this guide.

If a particulate filter respirator is recommended (any respirator code with N95, N100, R95, P95 or P100 in it) and a mineral, vegetable or synthetic oil or other oily material is also present in the air, you must select a respirator that provides the same efficiency but is acceptable for oil aerosols (see Oil definition given previously). For example, if a respirator is being selected for beryllium dust at a concentration 2 times the exposure limit, the guide lists N95. If an oil mist is present (air concentration greater than 0.1 mg/m³, but less than the occupational exposure limit) either an R- or P-series filter must be selected, even though respiratory protection is not needed for the oil mist.

For PAPRs, use a HEPA filter instead of the N, R or P type particle filters listed in the guide.

If respiratory protection is required for an atmosphere with more than one chemical, you must follow the directions below for proper respirator selection. I

1. Identify the air contaminants present in the workplace. Include chemical name and form. Classify particulate contaminants as oil or non-oil material. If the chemical is listed in this guide, it is classified. For help, see definition of oil. The material safety data sheet (MSDS) can be helpful with this step. Consider particulate contaminants as oil if unknown or not sure. List the contaminants on the form contained in this guide or on your own form. Go to Step 2.
2. Determine the air concentration of the contaminant. Air sampling is highly recommended. Consideration should be given to TWA, short term and peak (ceiling) exposures, while keeping in mind seasonal and worker variability and the

specific process being used.

If air sampling data are not available and sampling is not practical, historical information from similar processes or analogous operations may be helpful for calculating maximum exposures and evaluating potential health effects. Record the airborne concentration(s) on the form provided or your own form. Go to Step 3.

3. Is the airborne concentration unknown?
 - a) If **yes**, go to Step 16.
 - b) If **no**, go to Step 4.
4. Is the oxygen concentration less than 19.5% or does the potential exist for the oxygen concentration to fall below 19.5%?
 - a) If **yes**, go to Step 16.
 - b) If **no**, go to Step 5.
5. Is the chemical listed in the guide?
 - a) If **yes**, go to Step 6.
 - b) If **no**, go to Step 15.

6. Record the IDLH value and the value from the OEL column on the form provided or on one you created. **Determine the hazard ratio (see page 1) and record.** Using this information, determine which condition describes your situation:
- Does the airborne concentration exceed the IDLH value? If **yes**, go to Step 16.
 - Does the hazard ratio exceed (>) 1000?
If **yes**, go to Step 16.
 - Does the hazard ratio exceed (>) 50? If **yes**, go to Step 7.
 - Does the hazard ratio exceed (>) 10?
If **yes**, go to Step 8.
 - Is the hazard ratio less than or equal to (\leq) 10? If **yes**, go to Step 9.
7. If the hazard ratio exceeds 50, but is less than 1000: Select one of the following respirators: (1) a full facepiece, helmet or hood supplied air respirator or (2) a full facepiece, helmet or hood powered air purifying respirator (PAPR) with the same cartridge type as listed in the guide under the Respirator column.

If a PAPR is selected, use a HEPA filter if an N, R, or P-series filter is listed. If the guide lists SA or SA(F), a PAPR **cannot** be used. If a gas or vapor respirator is selected, cartridge change schedules based on objective data must be established. Otherwise supplied air respirators must be used. The service life of gas or vapor cartridges should be considered to determine if supplied air respirators are a better selection given the high exposure concentrations. Record the respirator you selected in the last column of the form for that chemical. Go to Step 10.

8. If the hazard ratio exceeds 10 but is less than 50, select one of the following respirators:
- (1) If the guide lists SA or SA(F), a supplied air respirator must be used. Loose fitting facepieces may only be used if the hazard ratio is less than 25. (2) A powered air purifying respirator (PAPR) may be used with the cartridge and/or filter type listed under the Respirator column. Use a HEPA filter if an N, R, P-series filter is listed. Loose fitting facepiece may only be used if the hazard

ratio is less than 25. (3) A full facepiece respirator that has been quantitatively fit tested may be used with cartridges and/or filters listed under the Respirator column. If a gas or vapor respirator is selected, cartridge change schedules based on objective data must be established. Otherwise supplied air respirators must be used. Record the respirator you selected in the last column of the form for that chemical. Go to Step 10.

9. If the hazard ratio is less than or equal to 10: Select the respirator type listed in the Respirator column. If a gas or vapor respirator is selected, cartridge change schedules based on objective data must be established. Otherwise supplied air respirators must be used. Record the respirator you selected in the last column of the form for that chemical. Go to Step 10.
10. Are any other air contaminants present at the same time?
- If **yes**, go to Step 2 and repeat the procedure, recording the appropriate information for the next chemical. When two or more contaminants that act upon

the same organ system are present, consideration should be given to the combined effect rather than individual effects. Consult the current TLVs® and documentation published by the American Conference of Governmental Industrial Hygienists for more information and the appropriate formula. If combined effects are considered, calculate the hazard ratio for the mixture.

b) If **no**, go to Step 11.

11. Are any of the respirators listed in the last column a particulate filter respirator (i.e., does it have an N, R or P filter)?

a) If **yes**, go to Step 12.

b) If **no**, go to Step 14.

12. Are only N-series particulate filter respirator(s) listed?

a) If **yes**, go to Step 13.

b) If **no**, go to Step 14.

13. Is airborne oil mist present at a concentration greater than 0.1 mg/m³ but less than the value in the OEL column of the guide? (If a respirator is not being selected for oil, the presence of the oil

must still be considered when choosing the appropriate filter)

a) If **yes**, a respirator with either an R- or P-series or HEPA filter must be selected. R-series filters must be changed after 8 hours use or after the respirator is loaded with or exposed to 200 mg of aerosol. The manufacturer's service time recommendation must be followed for P-series filters. Record the respirator with the R- or P-series filter that is being selected. Go to Step 14.

b) If **no**, go to Step 14.

14. Was more than one respirator type required for the specific exposure situation (i.e., is there more than one respirator code included in the list made in the last column of the form)?

a) If **yes**, note all respirators recommended. If your list contains more than one respirator and all are air-purifying respirators, select the one with the highest assigned protection factor (see page 2) and one that removes all of the contaminants, if available.

If **SA** or **SA(F)** is one of the respirators listed, this respirator must be selected over all others. If any of the respirator codes contain the **(F)** designation, respirators with half facepieces cannot be used unless appropriate eye protection is also worn. If no air-purifying respirator will provide the protection required, select **SA** or **SA(F)**. Go to Step 17.

b) If **no**, record the respirator listed as the final respirator selected (bottom line). Go to Step 17.

15. If the chemical is not listed in the guide, either it is a pesticide or an occupational exposure limit was not located. If an acceptable exposure level is not known, a respirator cannot be recommended. If you have an exposure level for the material and would like help, go to Step 17. If no exposure limit is known, go to Step 16.

16. These conditions (unknown, <19.5% oxygen, airborne concentration >IDLH) are generally considered as IDLH or the hazard ratio exceeds 1000. Select either a positive pressure self-contained breathing

apparatus (SCBA) or combination respirator consisting of a positive pressure supplied air respirator with an auxiliary SCBA. The rated duration of the auxiliary SCBA should be sufficient to allow adequate time for escape. Record the respirator selected in the final row of the form. This is the minimum acceptable level of respiratory protection; the selection process is finished. If you need help, go to Step 17.

Respirator Selection Form

| Chemical Name | Air Concentration | IDLH | OEL | Hazard Ratio | Respirator Type |
|-----------------------------|-------------------|------|-----|--------------|-----------------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| Respirator Selected: | | | | | |

NOTE: For explanation of column headings and abbreviations, refer to Format Explanation starting on page 4.

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--------------------------------|--|-----------------------|--|--|--|
| Acetaldehyde 75-07-0 | Acetic aldehyde, Ethanal | 10000 | TWA=200 (OSHA) C=25 | (F)OV (F)MG | Multigas cartridge recommended for longer service life |
| Acetamide 60-35-5 | Ethanamide | | TWA=1 (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |
| Acetic acid 64-19-7 | Ethanoic acid, Glacial acetic acid, Methane carboxylic acid, Vinegar acid | 1000 | TWA=10 STEL=15 | (F)OV/AG | |
| Acetic anhydride 108-24-7 | Acetic acid anhydride, Acetyl oxide, Ethanoic anhydride | 1000 | TWA=1 STEL=3 | (F)OV | |
| Acetone 67-64-1 | 2-Propanone, Dimethyl ketone, Ketone propane | 20000 | TWA=250 STEL=500 | OV | Short service life. 3M 3530 Monitor |
| Acetone cyanohydrin 75-86-5 | 2-Cyano-2-propanol, 2-Hydroxy-2-methyl propanenitrile, 2-Methylactonile, 2-Propane cyanohydrin, a-Hydroxy isobutyronitrile | 22000 | TWA=2 (AIHA) STEL=5 (AIHA) C=5 mg/m ³ (as CN) -skin- | OV | |
| Acetonitrile 75-05-8 | Cyanomethane, Ethane nitrile, Ethyl nitrile, Methanecarbonitrile, Methyl cyanide | 4000 | TWA=20 -skin- | OV | 3M 3530 Monitor |

| | | | | | |
|---------------------------------|--|-------|--|--------|---|
| Acetophenone 98-86-2 | 1-Phenylethanone, Acetyl benzene, Benzoyl methide, Methyl phenyl ketone | | TWA=10 | OV | See comment E on page 8 |
| Acetylsalicylic acid 50-78-2 | Aspirin | | TWA=5 mg/m ³ | N95 | |
| Acrolein 107-02-8 | Acrylaldehyde, Acrylic aldehyde, Allylaldehyde, Propenal | 5 | TWA=0.1 (OSHA) C=0.1 -skin- | (F)OV | Short service life |
| Acrylamide 79-06-1 | Acrylamide monomer, Acrylic amide, Propenamamide | | TWA=0.03 mg/m ³ (inhalable fraction and vapor) -skin- | OV/N95 | See comment D on page 8 |
| Acrylic acid 79-10-7 | Acroleic acid, Propenoic acid | 24000 | TWA=2 -skin- | (F)OV | |
| Acrylonitrile 107-13-1 | AN, Propenenitrile, Vinyl cyanide | 500 | TWA=2 -skin- | OV | SA if cartridge not disposed of after shift, per 29 CFR 1910.1045. 3M 3510 monitor. |
| Adipic acid 124-04-9 | 1,4-Butanedicarboxylic acid, 1,6-Hexanedioic acid, Adipinic acid, Hexanedioic acid | | TWA=5 mg/m ³ | (F)N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|-------------------------------------|---|-----------------------|-------------------------------|--|-----------------------|
| Adiponitrile 111-69-3 | 1,4-Dicyanobutane, Addipic acid dinitrile, Hexanedinitrile, Tetramethylene cyanide | 17000 | TWA=2 -skin- | OV | |
| Allyl alcohol 107-18-6 | 2-Propen-1-ol, 2-Propenol, Vinyl carbinol | 150 | TWA=0.5 -skin- | (F)OV | 3M 3510 Monitor |
| Allyl Bromide 106-95-6 | 1-Bromo-2-propene; 1-Propene; 3-bromo-; 2-Propenyl bromide; 3-Bromo-1-propene; 3-Bromopropene; 3-Bromopropylene | 44000 | TWA=0.1 STEL=0.2 -skin- | (F)OV | |
| Allyl chloride 107-05-1 | 1-Chloro-2-propene, 3-Chloropropene | 300 | TWA=1 STEL=2 -skin- | OV | Short service life |
| Allyl glycidyl ether 106-92-3 | 1-Allyloxy-2,3-epoxy-propane, AGE | 270 | TWA=1 C=10 (OSHA) | (F)OV | |
| Allyl isothiocyanate 57-06-7 | AITC, Allyl isosulfocyanate, Allyl thiocarbanimide, Oil of mustard, 3-Isothiocyanate-1-propene | | STEL=1 (AIHA) -skin- | OV | SA if used with acids |
| Allyl propyl disulfide 2179-59-1 | 2-Propenyl propyl disulfide, Onion oil, Propyl allyl disulfide | | TWA=0.5 | (F)OV | |

| | | | | | |
|--|---|-----|--|--------|--|
| alpha-Alumina 1344-28-1 | | | TWA=15 mg/m ³ (OSHA) | N95 | |
| Aluminum metal and insoluble compounds 7429-90-5 | | | TWA=15 mg/m ³ (OSHA) TWA=1 mg/m ³ (respirable fraction) | N95 | |
| p-Aminobenzoic acid 150-13-0 | 4-Aminobenzoic acid, Aminobenzoic acid, PABA | | TWA=5 mg/m ³ (AIHA) | (F)N95 | |
| 2-Aminopyridine 504-29-0 | a-Aminopyridine | 5 | TWA=0.5 | OV | |
| Aminotri (methylenephosphonic acid) 6419-19-8 | ATMP, Briquest 301-32S, Briquest 302-500, Dequest 2000, Dequest 2001, Nitrilotrimethanephosphonic acid, NTF, NTMP, NTPA | | TWA=10 mg/m ³ (AIHA) | AG/N95 | If heated, AG cartridge may be needed |
| Ammonia 7664-41-7 | Anhydrous ammonia | 500 | TWA=25 STEL=35 | (F)AM | Irritation also provides warning |
| Ammonium chloride (liquids) 12125-02-9 | | | TWA=10 mg/m ³ STEL=20 mg/m ³ | AM/N95 | |
| Ammonium chloride (solids) 12125-02-9 | | | TWA=10 mg/m ³ STEL=20 mg/m ³ | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|--------------------------------------|--|----------------------------|
| Ammonium perfluorooctanoate 3825-26-1 | | | TWA=0.01 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| n-Amyl alcohol 71-41-0 | 1-Pentanol, Amyl alcohol, n-Butyl carbinol, n-Pentanol, Pentanol, Pentyl alcohol | | TWA=100 (AIHA) | (F)OV | |
| tert-Amyl methyl ether 994-05-8 | TAME | | TWA=20 | OV | |
| Aniline 62-53-3 | Aminobenzene, Aniline oil, Phenylamine | 100 | TWA=2 -skin- | OV | |
| o-Anisidine 90-04-0 29191-52-4 | 2-Methoxyaniline, o-Aminoanisole, o-Methoxyaniline (oil) | 50 mg/m ³ | TWA=0.5 mg/m ³ -skin- | OV/P95 | |
| p-Anisidine 104-94-9 29191-52-4 | 4-Methoxyaniline, p- Aminoanisole, p-Methoxyaniline (solid) | 50 mg/m ³ | TWA=0.5 mg/m ³ -skin- | OV/N95 | |
| Antimony and compounds (as Sb) 7440-36-0 | | 80 mg/m ³ | TWA=0.5 mg/m ³ | N95 | |

| | | | | | |
|---|--|-----------------------|--|---------|--|
| Arsenic, elemental 7440-38-2 | | 100 mg/m ³ | TWA=0.01 mg/m ³ | N100 | |
| Arsenic, inorganic compounds (except arsine) (as As) | | 100 mg/m ³ | TWA=0.01 mg/m ³ | MG/N100 | No half mask respirators for arsenic trichloride because of skin adsorption. N100 may be appropriate if vapor concentrations are below exposure limits |
| Arsenic, organic compounds (as As) | | | TWA=0.5 mg/m ³ (OSHA) | OV/N100 | MG/N100 may be required for certain organic arsenic compounds |
| Arsine 7784-42-1 | Arsenic hydride, Arsenic trihydride, Arseniuretted hydrogen, Arsenous hydride, Hydrogen arsenide | 6 | TWA=0.005 | (F)SA | Unknown sorbent effectiveness |
| Asbestos 1332-21-4 | Actinolite, Amosite, Anthophyllite, Chrysotile, Crocidolite, Tremolite | | TWA= 0.1 f/cc (respirable fibers) | N100 | Dual cartridge as per 29 CFR 1910.1001, 1915.1001 and 1926.1101 |
| Asphalt (petroleum; bitumen) fumes 8052-42-4 | Asphaltic bitumen, Asphaltum, Bitumen, Hot mix asphalt, Mineral pitch, Petroleum asphalt, Road asphalt, Road tar | | TWA=0.5 mg/m ³ (inhalable fraction as benzene-soluble aerosol) | OV/P95 | R or P95 alone may be suitable for some applications. See comment F on page 8 |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|---|------------------------|--|--|---|
| Barium and soluble compounds (as Ba) 7440-39-3 | | 1100 mg/m ³ | TWA=0.5 mg/m ³ | N95 | |
| Barium sulfate 7727-43-7 | | | TWA= 5 mg/m ³ (inhalable fraction) | N95 | |
| Benzaldehyde 100-52-7 | Benzenecarbonal, Benzoic aldehyde, Oil of bitter almond | | TWA=2 (AIHA) STEL=4 (AIHA) | (F)OV | |
| Benzene 71-43-2 | Benzol, Coal tar naptha | 3000 | TWA=0.5 STEL=2.5 -skin- | OV | SA if cartridges are not replaced at the start of each shift, per 20 CFR 1910.1028. 3M 3510 Monitor |
| Benzophenone 119-61-9 | Benzoyl benzene, Diphenyl ketone, Diphenyl methanone, Phenyl ketone | | TWA=0.5 mg/m ³ (AIHA) | OV/N95 | See comment D on page 8 |
| Benzotrichloride 98-07-7 | Benzenyl trichloride, Benzenylchloride, Benzoic trichloride, Benzyl trichloride, Phenyl chloroform, Toluene trichloride, Trichloromethylbenzene | | C=0.1 -skin- | (F)OV | |

| | | | | | |
|---|--|------------------------|--|-------------------|--|
| Benzoyl chloride 98-88-4 | a-Chlorobenzaldehyde, Benzene carbonyl chloride, Benzoic acid chloride | | C=0.5 | (F)OV/AG (F)MG | |
| Benzoyl peroxide 94-36-0 | Dibenzoyl peroxide | 7000 mg/m ³ | TWA=5 mg/m ³ | OV/N95 | See comment D on page 8 |
| Benzyl acetate 140-11-4 | Acetic acid benzyl ester, Acetic acid phenylmethyl ester, Phenylmethyl acetate | | TWA=10 | OV/N95 | |
| Benzyl alcohol 100-51-6 | a-Hydroxytoluene, Phenylcarbinol, Phenylmethanol | | TWA=10 (AIHA) | (F)OV | |
| Benzyl chloride 100-44-7 | a-Chlorotoluene | 10 | TWA=1 | (F)OV/AG | See comment E on page 8. 3M 3510 Monitor |
| Beryllium and compounds (as Be) 7440-41-7 | | 10 mg/m ³ | TWA=0.00005 mg/m ³ (inhalable fraction) STEL=0.002 mg/m ³ (OSHA) -skin- | N95 | See OSHA standard 1910.1024 regarding PAPRs requested by employee |
| Biphenyl 92-52-4 | Diphenyl, Phenylbenzene | 300 mg/m ³ | TWA=0.2 | OV/N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|---|-----------------------|---|--|-------------------------------------|
| Bismuth telluride (undoped) 1304-82-1 | Bismuth sesquitelluride | | TWA=10 mg/m ³ TWA=5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Bismuth telluride (Se-doped) (as Bi ₂ Te ₃) | | | TWA=5 mg/m ³ | N95 | |
| Boric acid 10043-35-3 | Borofax, Boron trihydroxide, Hydrogen orthoborate, Kill-off, Kjel-sorb Orthoboric acid, Three elephant, Trihydroxyborane | | TWA=2 mg/m ³ (inhalable fraction) STEL=6 mg/m ³ (inhalable fraction) | N95 | |
| Boron oxide 1303-86-2 | Anhydrous boric acid, Boric anhydride, Boric oxide | | TWA=10 mg/m ³ | N95 | |
| Boron tribromide 10294-33-4 | Boron bromide | | C=0.7 | (F)AG | |
| Boron trichloride 10294-34-5 | Trichloroboron | | C=0.7 | (F)AG | |
| Boron trifluoride 7637-07-2 | | 100 | STEL=0.1 C=0.7 | (F)AG | |
| Bromine 7726-95-6 | | 10 | TWA=0.1 STEL=0.2 | (F)AG | Irritation also provides warning |

| | | | | | |
|---|---|-------|-------------------------------|-------|---|
| Bromine pentafluoride 7789-30-2 | | | TWA=0.1 | AG | |
| Bromoform 75-25-2 | Tribromomethane | | TWA=0.5 | (F)OV | 3M 3510 Monitor |
| 1-Bromopropane 106-94-5 | n-Propylbromide, Propylbromide | | TWA=0.1 | OV | |
| 1,3-Butadiene 106-99-0 | Biethylene, Divinyl, Erythrene | 20000 | TWA=1 (OSHA) STEL=5 (OSHA) | OV | Cartridges must be replaced, per 29 CFR 1910.1051 |
| Butane 106-97-8 | n-Butane, Methylethyl methane | 16000 | STEL=1000 | SA | Short OV service life |
| 1-Butene 106-98-9 | 1-Butylene, a-Butene, a-Butylene, But-1-ene, Ethylethylene | | TWA=250 | OV | Short service life |
| 2-Butene (mixture of trans- and cis-) 107-01-7 | b-Butene, b-Butylene, Dimethylethylene, Pseudobutylene | | TWA=250 | OV | Short service life |
| cis-2-Butene 590-18-1 | b-cis-Butylene, cis-1,2- Dimethylethylene, cis-Butene, cis-Butene-2 | | TWA=250 | OV | Short service life |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--------------------------------------|---|-----------------------|----------------------|--|---|
| trans-2-Butene 624-64-6 | 2-Butene,(E)-; 2-trans-Butene, b-trans-Butylene, trans-1,2- Dimethylethylene, trans-Butene | | TWA=250 | OV | Short service life |
| 2-Butoxyethanol 111-76-2 | Butyl Cellosolve®, Ethylene glycol monobutylether | 700 | TWA=20 | (F)OV | See comment E on page 8 |
| 2-Butoxyethyl acetate 112-07-2 | Acetic acid, 2-butoxyethyl ester; 2-Butoxyethanol acetate; Butyl Cellusolve acetate; Butylglycol acetate; EGBA; Ektasolve EB acetate; Ethylene glycol monobutyl ether acetate; Glycol monobutyl ether acetate | 8800 | TWA=20 | OV | |
| n-Butyl acetate 123-86-4 | Acetic acid butyl ester, Butyl acetate, Butyl ethanoate | 10000 | TWA=50 STEL=150 | (F)OV | See comment E on page 8. 3M 3510 Monitor. |
| sec-Butyl acetate 105-46-4 | 1-Methylpropylacetate | 10000 | TWA=50 STEL=150 | (F)OV | See comment E on page 8. 3M 3510 Monitor. |
| tert-Butyl acetate 540-88-5 | Acetic acid tert-butyl ester | 10000 | TWA=50 STEL=150 | (F)OV | 3M 3510 Monitor |
| Butyl acrylate 141-32-2 | 2-Propenoic acid butyl ester, Butyl 2-propenoate | 15000 | TWA=2 | OV | 3M 3510 Monitor |

| | | | | | |
|---|---|----------------------|--|-----------|--|
| n-Butyl alcohol 71-36-3 | 1-Butanol, 1-Hydroxybutane, Butyl alcohol, Butyl hydroxide, Butyric alcohol, Methylolpropane, n-Butanol, n-Propyl carbinol, Propyl methanol | 8000 | TWA=20 | (F)OV | 3M 3510 Monitor |
| sec-Butyl alcohol 78-92-2 | 2-Butanol, Methyl ethyl carbinol | 10000 | TWA=100 | (F)OV | 3M 3510 Monitor |
| tert-Butyl alcohol 75-65-0 | 2-Methyl-2-propanol, TBA, Trimethyl carbinol | 8000 | TWA=100 | (F)OV | 3M 3510 Monitor |
| Butylamine 109-73-9 | 1-Aminobutane, n-Butylamine | 2000 | C=5 -skin- | AM | AM not specifically approved, but 3M recommended for longer service life |
| Butylated hydroxytoluene 128-37-0 | 2,6-bis(1,1-Dimethylethyl)-4-methylphenol; 2,6-Di-tert-butyl-p-cresol; BHT; DBPD | | TWA=2 mg/m ³ (inhalable fraction and vapor) | (F)OV/N95 | See comment D on page 8 |
| 4-tert-Butylcatechol 98-29-3 | 4-(1,1-Dimethylethyl)-1,2-benzenediol; 4-tert-Butyl pyrocatechol; 4-tert-Butyl-1,1,2-dihydroxy benzene; p-tert-Butylcatechol | | C= 2 mg/m ³ (AIHA) -skin- | (F)N95 | |
| tert-Butyl chromate (as CrO ₃) 1189-85-1 | Chromic acid di-tert-butyl ester | 30 mg/m ³ | TWA=0.005 mg/m ³ (OSHA) C=0.1 mg/m ³ -skin- | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|-------------------------------------|---|-----------------------|----------------------|--|--|
| Butylene oxide 106-88-7 | 1,2-Butene oxide; 1,2-Butylene oxide; 1,2-Epoxybutane; 1-Butene oxide; BO; Epoxy-butane | | TWA=2 (AIHA) | OV | Short service life |
| n-Butyl glycidyl ether 2426-08-6 | 1,2-Epoxy-3-butoxypropane, BGE | 3500 | TWA=3 -skin- | OV | 3M 3510 Monitor |
| n-Butyl lactate 138-22-7 | Lactic acid butylester | 11500 | TWA=5 | OV | Irritation also provides warning |
| Butyl mercaptan 109-79-5 | 1-Mercaptobutane, n-Butanethiol | 2500 | TWA=0.5 | OV | |
| o-sec-Butylphenol 89-72-5 | 2-sec-Butylphenol | | TWA=5 -skin- | OV/P95 | |
| p-tert-Butyltoluene 98-51-1 | 1-Methyl-4-tert-butylbenzene | 1000 | TWA=1 | OV | 3M 3510 Monitor |
| Butyraldehyde 123-72-8 | Butal, Butaldehyde, Butalyde, Butanal, Butanaldehyde, Butylaldehyde, Butyral butyric aldehyde | 19000 | TWA=25 (AIHA) | (F)Form | Formaldehyde cartridge not specifically approved, but 3M recommended for longer service life |

| | | | | |
|--|---|---|---|------|
| Cadmium and compounds (as Cd) 7440-43-9 | Cadmium oxide fume | 9 mg/m ³ (fume) 50 mg/m ³ | TWA=0.002 mg/m ³ (respirable fraction) TWA=0.005 mg/m ³ (OSHA) | N100 |
| Calcium arsenate (as As) 7778-44-1 | Cucumber dust, Tricalcium arsenate, Tricalcium o-arsenate | 100 mg/m ³ | TWA=0.01 mg/m ³ | N100 |
| Calcium carbonate 1317-65-3 | Limestone, Marble | | TWA=15 mg/m ³ (OSHA) TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 |
| Calcium chromate (as Cr) 13765-19-0 | Calcium chrome yellow | | TWA=0.001 mg/m ³ | N95 |
| Calcium cyanamide 156-62-7 | Calcium carbimide, Lime nitrogen | | TWA=0.5 mg/m ³ | N95 |
| Calcium fluoride (as F) 7789-75-5 | Fluorite, Fluorospar | | TWA= 2.5 mg/m ³ | N95 |
| Calcium hydroxide 1305-62-0 | Calcium hydrate, Caustic lime, Hydrated lime | | TWA=5 mg/m ³ | N95 |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|--|--|----------------------------|
| Calcium oxide 1305-78-8 | Pebble lime, Quicklime | | TWA=2 mg/m ³ | N95 | |
| Calcium silicate (containing no asbestos and <1% crystalline silica) 1344-95-2 | Calcium hydrosilicate, Wollastonite | | TWA=1 mg/m ³ | N95 | |
| Calcium sulfate 7778-18-9 | Gypsum, Plaster of Paris | | TWA=10 mg/m ³ (inhalable fraction) TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Camphor 76-22-2 | 2-Camphonone, Gum camphor, Laurel camphor, Synthetic camphor | 200 mg/m ³ | TWA=2 STEL=3 | (F)OV/N95 | 3M 3510 Monitor |
| Caprolactam 105-60-2 | 2-Oxohexamethylenimine, Aminocaproic lactam | 14000 | TWA=5 mg/m ³ (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |
| Captan 133-06-2 | N-(Trichloromethylthio)-4- cyclohexene-1,2-dicarboximide | | TWA=5 mg/m ³ (inhalable fraction) | N95 | |

| | | | | | |
|---------------------------------|--|-------|---|-------|----------------------|
| Carbon black 1333-86-4 | Acetylene black, Channel black, Furnace black, Lamp black, Thermal black | | TWA=3 mg/m ³ (inhalable fraction) | N95 | |
| Carbon dioxide 124-38-9 | Carbonic acid gas, Dry ice | 50000 | TWA=5000 STEL=30000 | SA | Ineffective sorbents |
| Carbon disulfide 75-15-0 | Carbon bisulfide, Carbon bisulfur, Carbon bisulphide, Carbon disulphide, Carbon sulfide, Dithiocarbonic anhydride, Sulphocarbonic anhydride, Weevitox | 500 | TWA=1 C=30 (OSHA) -skin- | OV | Short service life |
| Carbon monoxide 630-08-0 | Monoxide | 1500 | TWA=25 | SA | Ineffective sorbents |
| Carbon tetrabromide 558-13-4 | Tetrabromomethane | | TWA=0.1 STEL=0.3 | (F)OV | |
| Carbon tetrachloride 56-23-5 | Tetrachloromethane | 300 | TWA=5 STEL=10 C=25 (OSHA) -skin- | (F)OV | 3M 3510 Monitor |
| Carbonyl fluoride 353-50-4 | Carbon oxyfluoride, Fluoroformyl fluoride | | TWA=2 STEL=5 | (F)MG | |
| Carbonyl sulfide 463-58-1 | Carbon monoxide monosulfide, Carbon oxide sulfide, Carbon oxysulfide, Oxycarbon sulfide | | TWA=5 | SA | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|---|-----------------------|--|--|-------------------------------------|
| Catechol 120-80-9 | Pyrocatechol | 14000 | TWA=5 -skin- | OV/N95 | |
| Cellulose 9004-34-6 | Paper fiber | | TWA=10 mg/m ³ TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Cesium fluoride (as F) 13400-13-0 | | | TWA=2.5 mg/m ³ | N95 | |
| Cesium hydroxide 21351-79-1 | Cesium hydrate | | TWA=2 mg/m ³ | N95 | |
| Chloramphenicol 56-75-7 | [R-(R*,R*)]-2,2-dichloro-N- [2,hydroxy-1-(hydroxy methyl)-2- (4-nitrophenyl)ethyl] acetamide; Chloromycetin; Levomycetin | | TWA=0.5 mg/m ³ (AIHA) | N95 | |
| Chlorinated diphenyl oxide 31242-93-0 | Hexachlorodiphenyl oxide | | TWA=0.5 mg/m ³ | OV/P95 | |
| Chlorine 7782-50-5 | | 30 | TWA=0.5 STEL=1 C=1 (OSHA) | (F)AG | Irritation also provides warning |

| | | | | | |
|--|--|------|---------------------------------|----------|-----------------------|
| Chlorine dioxide 10049-04-4 | Chlorine oxide, Chlorine peroxide | 10 | TWA=0.1 STEL=0.3 | AG | |
| Chlorine trifluoride 7790-91-2 | Chlorine fluoride | 20 | C=0.1 | MG | |
| Chloroacetaldehyde 107-20-0 | 2-Chloroethanal, Chloroacetaldehyde (40% aqueous) | 100 | C=1 | (F)OV | |
| Chloroacetone 78-95-5 | Chloracetone, 1-Chloro-2- propanone, Monochloroacetone | | C=1 -skin- | (F)OV | |
| Chloroacetyl chloride 79-04-9 | Chloracetyl chloride | | TWA=0.05 STEL=0.15 -skin- | (F)OV/AG | |
| Chlorobenzene 108-90-7 | Chlorobenzol, MCB, Monochlorobenzene, Phenyl chloride | 2400 | TWA=10 | OV | 3M 3510 Monitor |
| Chlorobromomethane 74-97-5 | Bromochloromethane, CBM, Halon™ 1011, Methylene chlorobromide | 5000 | TWA=200 | OV | |
| 1-Chloro-1,1- difluoroethane 75-68-3 | a-Chloroethylidene fluoride, Chlorodifluoroethane, DymeI® 142b, Genetron™ 142b, HCFC-142b | | TWA=1000 (AIHA) | SA | Short OV service life |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|-------------------------------------|--|--|
| Chlorodifluoromethane 75-45-6 | Freon® 22 | | TWA=1000 | SA | Ineffective sorbents |
| Chlorodiphenyl (42% chlorine) 53469-21-9 | PCB, Polychlorinated biphenyl | 10 mg/m ³ | TWA=1 mg/m ³ -skin- | (F)OV/P95 | See comment D on page 8 |
| Chlorodiphenyl (54% chlorine) 11097-69-1 | PCB, Polychlorinated biphenyl | 5 mg/m ³ | TWA=0.5 mg/m ³ -skin- | (F)OV/P95 | See comment D on page 8 |
| Chloroform 67-66-3 | Trichloromethane | 1000 | TWA=10 C=50 (OSHA) | OV | Short service life. 3M 3510 Monitor |
| bis-(2-Chloroisopropyl) ether 39628-32-9 | BCIPE; bis-(1-methyl-2- chloroethyl) ether; bis-2- chloro-1-methylethyl ether; Dichloroisopropyl ether | | TWA=3 (AIHA) | (F)OV | |
| bis-Chloromethyl ether 542-88-1 | BCME, Chloro (chloromethoxy) methane, Chloromethyl ether, Dichloromethylether | | TWA=0.001 | (F)OV | OSHA requires SA with hood for certain applications; see 29 CFR 1910.1003 |

| | | | | | |
|------------------------------------|--|-----|-------------------|-------|----------------------------------|
| Chloropentafluoroethane 76-15-3 | FC-115, Monochloropentafluoroethane | | TWA=1000 | SA | Short OV service life |
| Chloropicrin 76-06-2 | Nitrochloroform, Nitrotrichloromethane, Trichloronitromethane | 4 | TWA=0.1 | (F)SA | Irritation also provides warning |
| b-Chloroprene 126-99-8 | 2-Chloro-1,3-butadiene, beta-Chloroprene, Chlorobutadiene | 400 | TWA=1 -skin- | (F)OV | Short service life |
| 2-Chloropropane 75-29-6 | 2-CP, 2-Propyl chloride, Isoprid, Isopropyl chloride | | TWA=50 (AIHA) | OV | Short service life |
| 1-Chloro-2-propanol 127-00-4 | 1-Chloro-2-hydroxypropane, 1-Chloroisopropyl alcohol, sec-Propylene chlorohydrin | | TWA=1 -skin- | OV | |
| 2-Chloro-1-propanol 78-89-7 | 1-Hydroxy-2-chloropropane, 2-Chloropropanol, 2-Chloropropyl alcohol, Propylene chlorohydrin | | TWA=1 -skin- | OV | |
| 2-Chloropropionic acid 598-78-7 | a-Chloropropionic acid | | TWA=0.1 -skin- | OV/AG | |
| o-Chlorostyrene 2039-87-4 | 1-Chloro-2-ethenylbenzene, 2-Chlorostyrene | | TWA=50 STEL=75 | OV | 3M 3510 Monitor |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|-------------------------------------|--|--|
| Chlorosulfonic acid 7790-94-5 | Chlorosulfuric acid, CSA | | C=0.1 mg/m ³ (AIHA) | (F)AG/N95 | HCl, SO ₂ hydrolysis products |
| 2-Chloro-1,1,1,2-tetrafluoroethane 2837-89-0 | Chlorotetrafluoroethane, Fluorocarbon 124, HCFC124, HFA124 | | TWA=1000 (AIHA) | SA | Short OV service life |
| o-Chlorotoluene 95-49-8 | 2-Chloro-1-methylbenzene | | TWA=50 | OV | 3M 3510 Monitor |
| Chlorotrifluoroethylene 79-38-9 | CFE, CTFE, Trifluorochloroethylene, Trifluorovinylchloride | | TWA=5 (AIHA) | SA | Short OV service life |
| Chromium II compounds (as Cr) 7440-47-3 | | | TWA=0.5 mg/m ³ (OSHA) | N95 | |
| Chromium metal and Cr III compounds (as Cr) 7440-47-3 | | | TWA=0.5 mg/m ³ | N95 | |
| Chromium compounds, insoluble Cr VI compounds (as Cr) 7440-47-3 | | | TWA=0.01 mg/m ³ | N95 | |

| | | | | | |
|---|---|-----------------------|---|------------|---|
| Chromium compounds, water soluble Cr VI compounds (not otherwise classified) (as Cr) 7440-47-3 | Chromic acid | 30 mg/m ³ | TWA=0.005 mg/m ³ (OSHA) | N95 | |
| Chromyl chloride 14977-61-8 | Chloro-chromic anhydride, Chromium oxychloride | | TWA=0.025 | AG | |
| Citral 5392-40-5 | 2,6-Octadienal-3,7-dimethyl; 3,7-Dimethyl-2,6-octadienal | | TWA=5 (inhalable fraction and vapor) -skin- | OV/P95 | See comment D on page 8 |
| Coal dust, Anthracite | | | TWA=0.4 mg/m ³ (respirable fraction) | N95 | May also contain crystalline silica (quartz) |
| Coal dust, Bituminous or Lignite | | | TWA=0.9 mg/m ³ (respirable fraction) | N95 | May also contain crystalline silica (quartz) |
| Coal tar pitch volatiles (as Benzene solubles) 65996-93-2 | Particulate polycyclic aromatic hydrocarbons, PPAH | 700 mg/m ³ | TWA=0.2 mg/m ³ | R95 P95 | Respirators with nuisance level organic vapor or acid gas relief specifically recommended |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|----------------|-----------------------|--------------------------------------|--|--|
| Cobalt, elemental and inorganic compounds (as Co) 7440-48-4 | | 20 mg/m ³ | TWA=0.02 mg/m ³ | N95 | |
| Cobalt carbonyl (as Co) 10210-68-1 | | | TWA=0.1 mg/m ³ | SA | Ineffective sorbents |
| Cobalt hydrocarbonyl (as Co) 16842-03-8 | | | TWA=0.1 mg/m ³ | SA | Ineffective sorbents |
| Coke oven emissions 65996-93-2 | | | TWA=0.15 mg/m ³ (OSHA) | R95 P95 | Respirators with nuisance level organic vapor or acid gas relief specifically recommended. |
| Copper dust and mist (as Cu) 7440-50-8 | | | TWA=1 mg/m ³ | N95 | |
| Copper fume (as Cu) 7440-50-8 | | | TWA=0.1 mg/m ³ (OSHA) | N95 | |

| | | | | | |
|-----------------------------------|--|-----------------------|--|--------|---|
| Cotton dust, raw | | | TWA=0.1 mg/m ³ (thoracic fraction) | N95 | 5X PEL maximum for disposables, per OSHA cotton dust standard. If oil aerosol present, use R or P95 |
| Cresol (all isomers) 1319-77-3 | Cresylic acid | 250 | TWA=20 mg/m ³ (inhalable fraction and vapor) -skin- | OV/P95 | See comment D on page 8 |
| Crotonaldehyde 4170-30-3 | b-Methylacrolein, Crotonic aldehyde, Propylene aldehyde | 400 | TWA=2 (OSHA) C=0.3 | (F)OV | |
| Cryolite (as F) 15096-52-3 | Greenland spar, Icetone | 500 mg/m ³ | TWA=2.5 mg/m ³ | N95 | |
| Cumene 98-82-8 | 2-Phenyl propane, Cumol, Isopropyl benzene | 8000 | TWA=50 | OV | 3M 3510 Monitor |
| Cumene hydroperoxide 80-15-9 | a,a'-Dimethylbenzyl hydroperoxide, CHP, Cumyl hydroperoxide, Isopropyl benzene hydroperoxide | | TWA=1 (AIHA) -skin- | (F)OV | |
| Cyanamide 420-04-2 | Carbodiimide, Cyanogenamide | | TWA=2 mg/m ³ | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--------------------------------|--|-----------------------|-----------------------------------|--|--|
| Cyanides (as CN) | | 50 mg/m ³ | TWA=5 mg/m ³ -skin- | SA | |
| Cyanogen 460-19-5 | Dicyan, Oxalonitrile | 66000 | C=5 | MG | |
| Cyanogen bromide 506-68-3 | Bromine cyanide | | C=0.3 | (F)SA | |
| Cyanogen chloride 506-77-4 | CNCl | | C=0.3 | (F)SA | Short OV service life |
| Cyclohexane 110-82-7 | Hexahydrobenzene, Hexamethylene | 10000 | TWA=100 | (F)OV | Irritation also provides warning. 3M 3510 Monitor. |
| Cyclohexanol 108-93-0 | Anol, Cyclohexyl alcohol, Hexahydrophenol, Hexalin, Hydralin, Hydroxycyclohexane | 3500 | TWA=50 -skin- | OV | See comment E on page 8. 3M 3510 Monitor. |
| Cyclohexanone 108-94-1 | Cyclohexyl ketone, Pimelic ketone | 5000 | TWA=20 STEL=50 -skin- | OV | 3M 3510 Monitor |

| | | | | | |
|---|--|-----------------------|-------------------------------------|-------|----------------------------------|
| Cyclohexene 110-83-8 | Benzene tetrahydride | 10000 | TWA=300 | OV | 3M 3510 Monitor |
| Cyclohexylamine 108-91-8 | Aminocyclohexane, Hexahydroaniline | 15000 | TWA=10 | (F)OV | |
| Cyclonite 121-82-4 | Hexahydro-1,3,5-trinitro-sym- triazine, RDX, sym-Trimethylene trinitramine | | TWA=0.5 mg/m ³ -skin- | N95 | |
| Cyclopentadiene 542-92-7 | 1,3-Cyclopentadiene | 2000 | TWA=75 | OV | Short service life |
| Cyclopentane 287-92-3 | Pentamethylene | 11000 | TWA=600 | SA | Short OV service life |
| Decaborane 17702-41-9 | | 100 mg/m ³ | TWA=0.05 STEL=0.15 -skin- | SA | Unknown sorbent effectiveness |
| Decabromodiphenyl oxide 1163-19-5 | bis-(Pentabromophenyl) ether, DBDPO, Decabromodiphenyl ether | | TWA=5 mg/m ³ (AIHA) | N95 | |
| 1-Decene 872-05-9 | a-Decene, Decylene | 5000 | TWA=100 (AIHA) | OV | |
| Dehydrolinalool 29171-20-8 | | | TWA=2 (AIHA) | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|-------------------------------------|--|--|
| Diacetone alcohol 123-42-2 | 2-Methyl-2-pentanol-4-one, 4-Hydroxy-4-methyl- 2-pentanone, Diacetone | 2100 | TWA=50 | (F)OV | 3M 3510 Monitor |
| Diacetyl 431-03-8 | Biacetyl, 2,3-Butanedione, Dimethylglyoxal, Dimethyl diketone, 2,3-Diketobutane | | TWA=0.01 STEL=0.02 | OV/P95 | |
| Diallylamine 124-02-7 | Di-2-propenylamine, N-2- propenyl-2-propen-1-amine | | TWA=1 (AIHA) -skin- | OV | |
| Diazomethane 334-88-3 | Azimethylene, Diazirine | 2 | TWA=0.2 | SA | Unknown sorbent effectiveness |
| Diborane 19287-45-7 | Boroethane | 40 | TWA=0.1 | SA | Unknown sorbent effectiveness |
| Dibromochloro- propane 96-12-8 | 1,2-Dibromo-3-chloropropane, 1-Chloro-2,3-dibromopropane, DBCP | | TWA=0.001 (OSHA) | (F)SA | OSHA requires (F)SA; no change schedule allowed |
| Dibromoneopenyl Glycol 3296-90-0 | Dibromopentaerythritol | | TWA=0.2 mg/m ³ (AIHA) | (F)R95/P95 | R95/P95 acceptable with appropriate eye/ face protection |

| | | | | | |
|---------------------------------------|---|------------------------|---|------------|---|
| Dibutylamine 111-92-2 | 1-Butanamine, n-butyl; Di-n-butylamine; DNBA | | C=5 (AIHA) -skin- | (F)OV | See comment E on page 8 |
| 2-N-Dibutylaminoethanol 102-81-8 | Dibutylaminoethanol, N,N-Dibutyl-N-(2-hydroxyethyl) amine | | TWA=0.5 -skin- | (F)OV | |
| Dibutyl phenyl phosphate 2528-36-1 | DBPP | | TWA=0.3 -skin- | R95 P95 | OV/P95 may be preferable if heat involved |
| Dibutyl phosphate 107-66-4 | Dibutyl acid-o-phosphate, Dibutyl phosphoric acid, Di-n-butyl hydrogen phosphate | 125 | TWA=5 mg/m ³ (inhalable fraction and vapor) -skin- | OV/P95 | See comment D on page 8 |
| Dibutyl phthalate 84-74-2 | 1,2-Benzene dicarboxylate, DBP, Dibutyl | 9300 mg/m ³ | TWA=5 mg/m ³ | OV/P95 | See comment D on page 8 |
| Dichloroacetic acid 79-43-6 | 2-2-Dichloroacetic acid; Acetic acid, dichloro; Dichloroethanoic acid; Urmer's liquid | | TWA=0.5 -skin- | (F)OV/AG | |
| Dichloroacetylene 7572-29-4 | Dichloroethyne | | C=0.1 | (F)SA | Short OV service life |
| o-Dichlorobenzene 95-50-1 | 1,2-Dichlorobenzene, o-Dichlorobenzol | 1000 | TWA=25 STEL=50 C=50 (OSHA) | (F)OV | See comment E on page 8. 3M 3510 Monitor |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|---|--|-----------------------|
| p-Dichlorobenzene 106-46-7 | 1,4-Dichlorobenzene, Dichloride, PDCB, | 1000 | TWA=10 | (F)OV/N95 | 3M 3510 Monitor |
| 1,4-Dichloro- 2-butene 764-41-0 | 1,4-DCB, 2-Butylenedichloride, DCB, dichlorobutene | | TWA=0.005 -skin- | (F)OV | |
| Dichlorodi- fluoromethane 75-71-8 | Freon® 12, Refrigerant 12 | 50000 | TWA=1000 | SA | Short OV service life |
| 1,3-Dichloro-5,5- dimethyl hydantoin 118-52-5 | Dactin, Halane | | TWA=0.2 mg/m ³ STEL=0.4 mg/m ³ | OV/N95 | |
| 1,1-Dichloroethane 75-34-3 | Ethylidene chloride | 4000 | TWA=100 | OV | Short service life |
| 1,2-Dichloroethylene 540-59-0 156-59-2 156-60-5 | Acetylene dichloride, Dioform | 4000 | TWA=200 | OV | Short service life |

| | | | | | |
|--|---|-------|---|-----------|---|
| Dichloroethyl ether 111-44-4 | 2,2'-Dichlorodiethyl ether; bis-(2-Chloroethyl) ether | 250 | TWA=5 STEL=10 C=15 (OSHA) -skin- | (F)OV | |
| 1,1-Dichloro-1-fluoroethane 1717-00-6 | Fluorocarbon 141b, HCFC 141b, HFA 141b | | TWA=500 (AIHA) STEL=3000 (AIHA, 5 minute) | SA | Short OV service life |
| Dichlorofluoromethane 75-43-4 | Dichloromonofluoromethane, Freon® 21, Refrigerant 21 | 50000 | TWA=10 | SA | Short OV service life |
| 1,1-Dichloro-1-nitroethane 594-72-9 | | 150 | TWA=2 C=10 (OSHA) | OV | |
| 2,4-Dichlorophenol 120-83-2 | 2,4-DCP, DCP | | TWA=1 (AIHA) -skin- | OV | R or P95 may also be needed if material is molten |
| 1,3-Dichloropropene 542-75-6 | 1,3-Dichloropropylene | 53000 | TWA=1 -skin- | (F)OV | |
| 2,2-Dichloropropionic acid 75-99-0 | Dalapon™ | | TWA=5 mg/m ³ (inhalable fraction) | (F)OV/N95 | |
| Dichlorotetrafluoroethane 76-14-2 | FC-114, Freon® 114, Halon™ 242, Refrigerant 114 | 50000 | TWA=1000 | SA | Short OV service life |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|---|--|----------------------------|
| Dicyclopentadiene 77-73-6 | | 8000 | TWA=5 | OV/N95 | |
| Dicyclopentadienyl iron (as Fe) 102-54-5 | bis-Cyclopentadienyl iron (as Fe) | | TWA=10 mg/m ³ TWA=5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Diesel fuel (as total hydrocarbons) 68334-30-5 68476-30-2 68476-31-3 68476-34-6 77650-28-3 | Astral oil, Coal oil, Fuel oil, Gas oil, Home heating oil, Marine diesel fuel | | TWA=100 (inhalable fraction and vapor) -skin- | OV/P95 | See comment E on page 8 |
| Diethanolamine 111-42-2 | 2,2'-Dihydroxydiethylamine, Butadiene Dioxide, DEA, Diolamine, N,N-Diethanolamine, di-(2-Hydroxyethyl)amine, 2,2'-Iminobisethanol | 16000 | TWA=1 mg/m ³ (inhalable fraction and vapor) -skin- | OV/N95 | See comment E on page 8 |

| | | | | | |
|---|---|-------|---------------------------------------|----------------|--|
| Diethylamine 109-89-7 | | 2000 | TWA=5 STEL=15 -skin- | (F)AM (F)OV | AM not specifically approved, but 3M recommended for longer service life |
| 2-Diethylaminoethanol 100-37-8 | 2-Diethylaminoethyl alcohol, N,N-Diethylethanolamine | 500 | TWA=2 -skin- | OV | |
| Diethylbenzenes, mixed 25340-17-4 | 1,2-Diethylbenzene, 1,3-Diethylbenzene, 1,4-Diethylbenzene, DEB, Dowtherm™ J | | TWA=5 (AIHA) | OV | |
| Diethylene glycol 111-46-6 | 2,2'-Dihydroxydiethyl ether, DEG, Diglycol | | TWA=10 mg/m ³ (AIHA) | R95 P95 | See comments D and G on page 8 |
| Diethylene glycol monobutyl ether 112-34-5 | Butoxy diethylene glycol, Butoxydiglycol, Butyl Carbitol® | | TWA=10 (inhalable fraction and vapor) | (F)OV/P95 | See comment D on page 8 |
| Diethylene glycol monoethyl ether 111-90-0 | 2-(2-Ethoxyethoxy) ethanol, Carbitol®, DiEGEE, Diethylene glycol ethyl ether, Dioxitol, Ethyl Carbitol®, Glycol ether DE | 12000 | TWA=25 (AIHA) | OV | |
| Diethylene triamine 111-40-0 | | 20000 | TWA=1 -skin- | (F)OV | |
| N,N-Diethylhydroxylamine 3710-84-7 | DEHA | | TWA=2 | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|--------------------------|--|----------------------|
| Diethyl ketone 96-22-0 | 3-Pentanone, Ethyl propionyl, Metacetone, Propione | 16000 | TWA=200 STEL=300 | OV | |
| Diethyl phthalate 84-66-2 | DEP, Ethylphthalate | 7000 | TWA=5 mg/m ³ | R95 P95 | |
| Difluorodibromo- methane 75-61-6 | DFBM, Dibromodifluoro- methane, Freon® 12B2 | 2500 | TWA=100 | OV | Short service life |
| 1,1-Difluoroethane 75-37-6 | Dymel® 152a, Ethylidene fluoride, Freon® 152a, Genetron™ 152a, HFC-152a | | TWA=1000 (AIHA) | SA | Ineffective sorbents |
| Difluoromethane 75-10-5 | Hydrofluorocarbon 32, R32, Refrigerant 32 | | TWA=1000 (AIHA) | SA | Ineffective sorbents |
| Diglycidyl ether 2238-07-5 | 2-Epoxypropyl ether, bis- (2,3-Epoxypropyl)-ether, DGE, Di-(epoxypropyl) ether, Diallyl ether dioxide | 25 | TWA=0.01 C=0.5 (OSHA) | (F)OV | |
| Diisobutylene (mixed isomers) 25167-70-8 | Diisobutene | | TWA=75 (AIHA) | OV | |

| | | | | | |
|--|--|------|---------------------------------|-------|---|
| a-Diisobutylene 107-39-1 | 2,4,4-Trimethyl-1-pentene, a-Diisobutene | | TWA=75 (AIHA) | OV | |
| b-Diisobutylene 107-40-4 | 2,4,4-Trimethyl-2-pentene, b-Diisobutene | | TWA=75 (AIHA) | OV | |
| Diisobutyl ketone 108-83-8 | 2,6-Dimethyl-4-heptanone, Isovalerone, sym- Diisopropylacetone, Valerone | 2000 | TWA=25 | (F)OV | See comment E on page 8. 3M 3510 Monitor. |
| Diisopropylamine 108-18-9 | | 1000 | TWA=5 -skin- | (F)OV | |
| Dimethyl acetamide 127-19-5 | DMAC, N,N-Dimethyl acetamide | 400 | TWA=10 -skin- | OV | |
| Dimethylamine 124-40-3 | Anhydrous dimethylamine | 2000 | TWA=5 STEL=15 | AM | AM not specifically approved, but 3M recommended for longer service life |
| bis-(2- Dimethylaminoethyl) ether 3033-62-3 | DMAEE; Ethylamine, 2,2"-Oxybis (N,N-dimethyl); Niax® Catalyst A-99 | | TWA=0.05 STEL=0.15 -skin- | (F)OV | |
| Dimethylaniline 121-69-7 | N,N-Dimethylaniline | 100 | TWA=5 STEL=10 -skin- | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|----------------------|--|-------------------------------|
| Dimethyl carbamoyl chloride 79-44-7 | Chloroformic acid dimethylamide, Dimethyl carbamic chloride, Dimethylcarbamyl chloride, DMCC | | TWA=0.005 -skin- | (F)MG | |
| Dimethyldichlorosilane 75-78-5 | Dichlorodimethylsilane | | C=2 (AIHA) | OV/AG | |
| Dimethyl disulfide 624-92-0 | 2,3-Dithiabutane, Dimethyldisulfide, Dimethyldisulphide, DMDS | | TWA=0.5 -skin- | OV/AG | |
| Dimethyl ether 115-10-6 | Methyl ether, Wood ether | 34000 | TWA=1000 (AIHA) | SA | Short OV service life |
| Dimethylethoxysilane 14857-34-2 | Ethoxydimethyl silane | | TWA=0.5 STEL=1.5 | (F)SA | Unknown sorbent effectiveness |
| Dimethyl formamide 68-12-2 | DMF, N,N-Dimethyl formamide | 3500 | TWA=10 -skin- | OV | |
| 1,1-Dimethylhydrazine 57-14-7 | UDMH, unsym-Dimethylhydrazine | 50 | TWA=0.01 -skin- | (F)AM | |

| | | | | | |
|---|---|------------------------|-----------------------------------|--------|---|
| Dimethylphthalate 131-11-3 | DMP | 9300 mg/m ³ | TWA=5 mg/m ³ | OV/P95 | See comment D on page 8 |
| Dimethyl sulfide 75-18-3 | DMS; Methane, thiobis; Thiobis (methane) | | TWA=10 | OV/AG | AG recommended since H2S may also be present |
| Dimethyl sulfoxide 67-68-5 | DMSO, Methylsulfoxide | | TWA=250 (AIHA) | OV | |
| Dimethylsulfate 77-78-1 | Methyl sulfate | 10 | TWA=0.1 -skin- | (F)OV | |
| Dimethyl terephthalate 120-61-6 | 1,4-Benzene dicarboxylic acid, dimethyl ester; Dimethyl para- phthalate; DMT | | TWA=5 mg/m ³ (AIHA) | OV/N95 | |
| N,N-Dimethyl-para- toluidine 99-97-8 | 4-Dimethylaminotoluene, DMPT, N,N,4-trimethylaniline, N,N,4-Trimethylbenzenamine | | TWA=0.5 (AIHA) | OV | |
| Dinitrobenzene 528-29-0 99-65-0 100-25-4 25154-54-5 | 1,2-Dinitrobenzene, 1,3-Dinitrobenzene, 1,4-Dinitrobenzene, m-Dinitrobenzene, o-Dinitrobenzene, p-Dinitrobenzene | 200 mg/m ³ | TWA=0.15 -skin- | OV/N95 | |
| 3,5-Dinitro-o- toluamide 148-01-6 | 2-Methyl-3,5-dinitrobenzamide, Coccidin, Dinitolmide, Salcostat, Zoalene | | TWA=1 mg/m ³ | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|-------------------------------------|--|---|
| Dinitrotoluene 25321-14-6 | DNT | 200 mg/m ³ | TWA=0.2 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| Di-sec-octyl phthalate 117-81-7 | bis(2-Ethylhexyl) phthalate, DEHP, Di-2-ethylhexyl phthalate, DOP | 3000 | TWA=5 mg/m ³ | R95 P95 | |
| 1,3-Dioxalane 646-06-0 | 1,3-Dioxacyclopentane; 1,3-Dioxalan; 1,3-Dioxole, dihydroethylene glycol formal; Dioxalane; Formal glycol; Glycol methylene ether; Glycolformal | | TWA=20 | OV | |
| Dioxane 123-91-1 | 1,4-Dioxane, Diethylene dioxide, Diethylene ether, p-Dioxane | 2000 | TWA=20 -skin- | OV | 3M 3510 Monitor |
| Diphenylamine 122-39-4 | DPA, N-Phenylaniline | | TWA=10 mg/m ³ | N95 | OV/N95 may be preferable when odor is a problem |
| Dipropylene glycol methyl ether 34590-94-8 | bis(2-Methoxypropyl) ether, Dipropylene glycol monomethyl ether, Dowanol™ 50B | 11000 | TWA=100 STEL=150 -skin- | OV | |

| | | | | | |
|-------------------------------|---|-------|--|--------|--|
| Dipropyl ketone 123-19-3 | 4-Heptanone, Butyrate | | TWA=50 | OV | |
| Divinyl benzene 1321-74-0 | DVB, Vinylstyrene | 11000 | TWA=10 | (F)OV | |
| Dodecyl mercaptan 112-55-0 | 1-Dodecanethiol, 1-Mercaptododecane, n-Dodecyl mercaptan, n-Lauryl mercaptan | | TWA=0.1 | OV | R or P filter may be needed with oily aerosols |
| Dowtherm™ Q | 1,1-Diphenylethane with ethylated benzenes | | TWA=1 (AIHA) | OV/P95 | |
| Emery 1302-74-5 | Corundum | | TWA=15 mg/m ³ (OSHA) TWA=1 mg/m ³ (respirable fraction) | N95 | |
| Enflurane 13838-16-9 | 2-Chloro-1,1,2-trifluoroethyl difluoromethyl ether; Ethrane | | TWA=75 | SA | Short OV service life. 3M 3510 monitor |
| Epichlorohydrin 106-89-8 | 1-Chloro,2,3-epoxypropane, 2-Chloropropylene oxide, gamma-Chloropropylene oxide | 250 | TWA=0.5 -skin- | (F)OV | 3M 3510 Monitor |
| Erythromycin 114-07-8 | Dotycin, E-Mycin™, Erycinum, Erycin, Pentadecanoic acid | | TWA=3 mg/m ³ (AIHA) | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--------------------------------------|---|-----------------------|----------------------------|--|---|
| Ethane 74-84-0 | Ethylhydride, Methyl methane | | | | Simple asphyxiant, oxygen displacing gas |
| Ethanolamine 141-43-5 | 2-Aminoethanol, 2-Hydroxyethylamine, β-Aminoethyl alcohol, Ethylolamine, Monoethanolamine | 1000 | TWA=3 STEL=6 | OV | |
| 2-Ethoxyethanol 110-80-5 | Cellosolve® solvent, Ethylene glycol monoethyl ether, Glycol monoethyl ether | 6000 | TWA=5 -skin- | OV | 3M 3510 Monitor |
| 2-Ethoxyethyl acetate 111-15-9 | Cellosolve® acetate, Ethylene glycol monoethyl ether acetate | 2500 | TWA=5 -skin- | OV | 3M 3510 Monitor |
| Ethyl acetate 141-78-6 | Acetic ester, Acetic ether, Ethyl ethanoate | 10000 | TWA=400 | (F)OV | 3M 3510 Monitor |
| Ethyl acrylate 140-88-5 | Acrylic acid ethyl ester | 2000 | TWA=5 STEL=15 -skin- | (F)OV | 3M 3510 Monitor |

| | | | | | |
|----------------------------------|--|-------|----------------------------|-------|--|
| Ethyl alcohol 64-17-5 | Ethanol | 15000 | STEL=1000 | OV | Short OV service life |
| Ethylamine 75-04-7 | Aminoethane, Anhydrous ethylamine, Monoethylamine | 4000 | TWA=5 STEL=15 -skin- | (F)AM | AM not specifically approved, but 3M recommended for longer service life |
| Ethyl amyl ketone 541-85-5 | 5-Methyl-3-heptanone, EAK | 3000 | TWA=10 | (F)OV | |
| Ethyl benzene 100-41-4 | Ethylbenzol, Phenylethane | 2000 | TWA=20 | OV | See comment E on page 8. 3M 3510 Monitor. |
| Ethyl bromide 74-96-4 | Bromoethane | 3500 | TWA=5 -skin- | SA | Short OV service life |
| Ethyl butyl ketone 106-35-4 | 3-Heptanone | 3000 | TWA=50 STEL=75 | OV | See comment E on page 8 |
| Ethyl chloride 75-00-3 | Chloroethane, Hydrochloric ether, Monochloroethane | 20000 | TWA=100 -skin- | SA | Short OV service life |
| Ethyl cyanoacrylate 7085-85-0 | 2-Cyano-2-propenoic acid, ethyl ester; 2-Cyanoacrylic acid, ethyl ester; ECA; Ethyl 2-cyano-2-propenoate; Ethyl 2-cyanoacrylate; Ethyl alpha-cyanoacrylate | | TWA=0.2 | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|------------------------------------|---|-----------------------|--|--|-----------------------------------|
| Ethyl tert-butyl ether 637-92-3 | 1,1-Dimethyl ethyl ether; 2-Ethoxy-2-methylpropane; ETBE; Ethyl 1,1-dimethylethyl ether; Ethyl tert-butyl oxide; tert-Butyl ethyl ether | | TWA=25 | OV | |
| Ethylene 74-85-1 | Acetene, Bicarburretted hydrogen, Elayl, Ethene, Olefiant gas | | TWA=200 | (F)SA | |
| Ethylene chlorohydrin 107-07-3 | 2-Chloroethanol, 2-Chloroethyl alcohol | 10 | C=1 -skin- | OV | 3M 3510 Monitor |
| Ethylenediamine 107-15-3 | 1,2-Diaminoethane, 1,2-Ethanediamine | 2000 | TWA=10 | (F)OV | |
| Ethylene dibromide 106-93-4 | 1,2-Dibromoethane | 400 | TWA=20 (OSHA) C=30 (OSHA) -skin- | (F)OV | |
| Ethylene dichloride 107-06-2 | 1,2-Dichloroethane, Ethylene chloride | 1000 | TWA=10 C=100 (OSHA) | OV | 3M 3510 Monitor |
| Ethylene glycol 107-21-1 | 1,2-Ethanediol | 32000 | TWA=25 (vapor fraction) STEL=50 (vapor fraction) STEL=10 mg/m ³ (inhalable particulate matter) | OV/P95 | See comments D and G on page 8 |

| | | | | | |
|---------------------------------------|--|-----------------------|---|--------|---|
| Ethylene glycol dinitrate 628-96-6 | Glycol dinitrate, Nitroglycol | 500 mg/m ³ | TWA=0.05 C=0.2 (OSHA) -skin- | OV | |
| Ethyleneimine 151-56-4 | Aminoethylene, Azirane, Aziridine, Dihydroazirine, Dimethylenimine, Ethyleimine | 100 | TWA=0.05 STEL=0.1 -skin- | (F)MG | OSHA requires SA with hood for certain applications; see 29 CFR 1910.1003 |
| Ethylene oxide 75-21-8 | 1,2-Epoxyethane, Dimethylene oxide, Oxirane | 800 | TWA=1 STEL=5 (OSHA) | (F)SA | OSHA requires (F)SA; no change schedule allowed. 3M 3550 Monitor. |
| Ethyl ether 60-29-7 | Diethyl ether, Ether, Ethyl oxide | 19000 | TWA=400 STEL=500 | OV | Short service life. 3M 3530 Monitor |
| Ethyl formate 109-94-4 | Ethyl methanoate, Formic acid ethyl ester | 8000 | STEL=100 | (F)OV | Short service life |
| 2-Ethylhexanoic acid 149-57-5 | 2-Butylbutanoic acid, 2-Ethylcaproic acid, 2-Ethylhexoic acid, Butylethylacetic acid, Ethylhexoic acid | | TWA=5 mg/m ³ (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |
| Ethylidene norbornene 16219-75-3 | ENB | | TWA=2 STEL=4 | (F)OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---------------------------------|--|-----------------------|---|--|--|
| Ethyl isocyanate 109-90-0 | Isocyanatoethene; Isocyanic acid, ethyl ester | | TWA= 0.02 ppm STEL= 0.06 ppm -skin- | OV | Short service life |
| Ethyl mercaptan 75-08-1 | Ethanethiol, Ethyl sulfhydrate | 2500 | TWA=0.5 C=10 (OSHA) | OV | Short service life |
| N-Ethylmorpholine 100-74-3 | 4-Ethylmorpholine | 2000 | TWA=5 -skin- | (F)OV | |
| Ethyl silicate 78-10-4 | Ethyl orthosilicate, Tetraethoxy-silane, Tetraethyl silicate | 1000 | TWA=10 | OV | |
| Ferrovandium dust 12604-58-9 | | | TWA=1 mg/m ³ STEL=3 mg/m ³ | N95 | |
| Flour dust | | | TWA=0.5 mg/m ³ (inhalable fraction) | N95 | |
| Fluorides (as F) | (Synonyms vary depending upon specific compound.) | 500 mg/m ³ | TWA=2.5 mg/m ³ | N95 | |
| Fluorine 7782-41-4 | | 25 | TWA=0.1 (OSHA) STEL=2 | (F)SA | Unknown reaction products with sorbent |

| | | | | | |
|-------------------------------------|---|-------|---|------------------|--|
| Formaldehyde 50-00-0 | Formalin, Methylene oxide | 30 | TWA=0.1 STEL=2 (OSHA) C=0.3 | (F)Form | Irritation also provides warning. 3M 3720 Monitor |
| Formamide 75-12-7 | Methanamide | | TWA=10 -skin- | OV | |
| Formic acid 64-18-6 | Hydrogencarboxylic acid, Methanoic acid | 30 | TWA=5 STEL=10 | (F)AG (F)Form | Low IDLH |
| Furfural 98-01-1 | 2-Furaldehyde, 2-Furancarboxaldehyde, Fural, Furfuraldehyde | 250 | TWA=0.2 -skin- | (F)OV | 3M 3510 Monitor |
| Furfuryl alcohol 98-00-0 | 2-Hydroxymethylfuran, 2-Furylmethanol | 250 | TWA=0.2 -skin- | (F)OV | See comment E on page 8 |
| Gallium arsenide 1303-00-0 | Gallium monoarsenide | | TWA=0.0003 mg/m ³ (respirable fraction) | N100 | |
| Gasoline 86290-81-5 | Petrol | 14000 | TWA=300 STEL=500 | (F)OV | |
| Germanium tetrahydride 7782-65-2 | Germane, Germanium hydride | | TWA=0.2 | (F)SA | Unknown sorbent effectiveness |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|-----------------------------------|---|-----------------------|---|--|---|
| Glutaraldehyde 111-30-8 | 1,5-Pentanedial | | C=0.05 | (F)OV | See comment E on page 8 |
| Glycerin mist 56-81-5 | Glycerol | | TWA= 5 mg/m ³ (OSHA, respirable fraction) | R95 P95 | |
| Glycidol 556-52-5 | 2,3-Epoxy-1-propanol; 2-Hydroxymethyloxiran; 3-Hydroxypropylene oxide; Epoxypropyl alcohol; Hydroxymethyl ethylene oxide | 500 | TWA=2 | OV | |
| Glycidyl methacrylate 106-91-2 | 1-Propanol, 2-3, epoxy-, ethacrylate; 2,3-Epoxypropyl methacrylate; 2-Methyl-2-propenoic acid, oxiranylmethyl ester; GMA; Methacrylic acid, 2,3-Epoxypropyl ester | | TWA=0.5 (AIHA) -skin- | OV | |
| Glyoxal 107-22-2 | 1,2-Ethanedione, Biformyl, Diformyl, Ethanedial, Glyoxalaldehyde, Oxalaldehyde | | TWA=0.1 mg/m ³ (inhalable fraction and vapor) | (F)OV/N95 | Short OV service life at 10X OEL. See comment E in Help document. |
| Grain dust (oat, wheat, barley) | | | TWA=4 mg/m ³ | N95 | |

| | | | | | |
|---|---|------|--|-------|--|
| Graphite (natural) 7782-42-5 | Black lead, Corbo minerals, Plumbago, Potelot, Silver lead | | TWA=2 mg/m ³ (respirable fraction) | N95 | |
| Graphite (synthetic) 7440-44-0 | | | TWA=15 mg/m ³ (OSHA) TWA=2 mg/m ³ (respirable fraction) | N95 | |
| Hafnium and compounds (as Hf) 7440-58-6 | | | TWA=0.5 mg/m ³ | N95 | |
| Halothane 151-67-7 | 2-Bromo-2-chloro-1,1,1- trifluoroethane | | TWA=50 | OV | Short service life. 3M 3510 Monitor |
| Hard metals containing cobalt and tungsten | | | TWA=0.005 mg/m ³ (thoracic fraction) | N95 | |
| Heptane (all isomers) 142-82-5 590-35-2 565-59-3 108-08-7 591-76-4 589-34-4 | n-Heptane, normal Heptane | 5000 | TWA=400 STEL=500 | OV | 3M 3510 Monitor |
| Hexachlorobenzene 118-74-1 | Perchlorobenzene | | TWA=0.002 mg/m ³ -skin- | N95 | |
| Hexachlorobutadiene 87-68-3 | Hexachloro-1,3-butadiene; Perchlorobutadiene | | TWA=0.02 -skin- | (F)OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|-------------------------------------|--|----------------------------|
| Hexachlorocyclo- pentadiene 77-47-4 | | | TWA=0.01 | (F)OV | |
| Hexachloroethane 67-72-1 | Perchloroethane | 300 | TWA=1 -skin- | OV/N95 | |
| Hexachloro- naphthalene 1335-87-1 | Halowax™ 1014 | 2 mg/m ³ | TWA=0.2 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| 1,4-Hexadiene 592-45-0 | 1-Allylpropene | | TWA=10 (AIHA) | OV | |
| Hexafluoroacetone 684-16-2 | 1,1,1,3,3,3-Hexafluoro-2- propanone | | TWA=0.1 -skin- | SA | Short OV service life |
| 1,1,1,3,3,3- Hexafluoropropane 690-39-1 | FC-236fa, FE-13, HFC-236fa, Hydrofluorocarbon 236fa | | TWA=1000 (AIHA) | SA | Ineffective sorbents |

| | | | | | |
|--|--|------|--|--------|----------------------------|
| Hexafluoropropylene 116-15-4 | 1,1,2,3,3,3-Hexafluoro- 1-propene; 1,1,2,3,3,3-Hexafluoropropylene; Fluorocarbon 1216; Hexafluoropropene; HFP; Perfluoro-1-propene; Perfluoropropene; Perfluoropropylene | | TWA=0.1 | SA | Short OV service life |
| Hexahydrophthalic anhydride (all isomers) 85-42-7 13149-00-3 14166-21-3 | 1,2-Cyclohexanedicarboxylic acid anhydride; 1,2-Cyclohexanedicarboxylic anhydride; 1,3-Isobenzofurandione, hexahydro; Cyclohexane-1,2- dicarboxylic anhydride, cis and trans mixture; Hexahydro- 1,3-isobenzofurandione; Hexahydrophthalic acid anhydride; HHPA; HHPAA | | C=0.005 mg/m ³ (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |
| Hexamethylene diisocyanate 822-06-0 | HDI | | TWA=0.005 | OV/N95 | |
| Hexane (n-hexane) 110-54-3 | Hexyl hydride, Normal hexane | 5000 | TWA=50 -skin- | OV | 3M 3510 Monitor |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|-------------------------------------|--|-----------------------|--|--|--|
| Hexane (other isomers) | | 12000 | TWA=500 STEL=1000 | OV | Short service life. 3M 3510 Monitor |
| 1,6-Hexanediamine 124-09-4 | 1,6-Diaminohexane, Hexamethylenediamine, HMD, HMDA | | TWA=0.5 | OV/N95 | |
| Hexanediol diacrylate 13048-33-4 | HDODA; Propenoic acid, 1,6-hexanediol ester | | TWA=1 mg/m ³ (AIHA) | OV/P95 | See comment D on page 8 |
| 1-Hexene 592-41-6 | Butyl ethylene, Hex-1-ene, Hexene, Hexene-n-1, Hexylene | | TWA=50 | OV | Short service life |
| sec-Hexyl acetate 108-84-9 | 1,3-Dimethylbutyl acetate, Methylamyl acetate, Methylisoamyl acetate, Methylisobutyl carbinol | 4000 | TWA=50 | (F)OV | See comment E on page 8 |
| Hexylene glycol 107-41-5 | 2-Methyl-2,4-pentanediol | 13000 | TWA=25 (vapor fraction) STEL=50 (vapor fraction) STEL=10mg/m ³ (inhalable particulate matter) | (F)OV/P95 | Irritation also provides warning |

| | | | | | |
|--|--|-----|--------------------------|------------|-----------------------------------|
| HFE-7100 163702-08-7 163702-07-6 | 60% of mixture is: 1-Methoxy-2-trifluoromethyl-1,1,2,3,3,3-hexafluoropropane; 1-Methoxyperfluoroisobutane 40% of mixture is 1-Methoxy-1,1,2,2,3,3,3,4,4,4-nonafluorobutane; 1-Methoxyperfluorobutane | | TWA=750 (AIHA) | OV | Short service life |
| Hydrazine 302-01-2 | Anhydrous hydrazine | 80 | TWA=0.01 -skin- | (F)AM | |
| Hydrogenated terphenyls 61788-32-7 | | | TWA=0.5 | R95 P95 | |
| Hydrogen bromide 10035-10-6 | HBr, Hydrobromic acid | 50 | C=2 | AG | Not specifically approved for HBr |
| Hydrogen chloride 7647-01-0 | HCl, Hydrochloric acid, Muriatic acid | 100 | C=2 | AG | Irritation also provides warning |
| Hydrogen cyanide 74-90-8 | Hydrocyanic acid, Prussic acid | 50 | C=4.7 -skin- | (F)SA | Low IDLH |
| Hydrogen fluoride 7664-39-3 | Anhydrofluoric acid, Etching acid, Fluoric acid, Fluorohydric acid, HF | 30 | TWA=0.5 C=2 -skin- | (F)HF | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|-----------------------------------|--|-------------------------------------|
| Hydrogen peroxide 7722-84-1 | Hydrogen dioxide, Peroxide | 75 | TWA=1 | (F)OV | See Technical Data Bulletin #185 |
| Hydrogen selenide (as Se) 7783-07-5 | Selenium hydride | 2 | TWA=0.05 | (F)MG | |
| Hydrogen sulfide 7783-06-4 | H ₂ S, Hepatic gas, Hydrosulfuric acid, Sulfuretted hydrogen | 300 | TWA=1 STEL=5 | AG | Poor warning (olfactory fatigue) |
| Hydroquinone 123-31-9 | 1,4-Benzenediol, Dihydroxybenzene, Quinol | | TWA=1 mg/m ³ | (F)OV/N95 | See comment D on page 8 |
| 4-Hydroxybenzoic acid 99-96-7 | | | TWA=5 mg/m ³ (AIHA) | (F)N95 | |
| 2-Hydroxypropyl acrylate 999-61-1 | HPA | 18000 | TWA=0.5 -skin- | OV | |
| Indene 95-13-6 | Indonaphthene | | TWA=5 | OV | |
| Indium and compounds (as In) 7440-74-6 | | | TWA=0.1 mg/m ³ | N95 | |

| | | | | | |
|---|--|----|---|-----------|-------------------------------|
| Iodides | | | TWA=0.01 (inhalable fraction and vapor) | (F)MG/N95 | See comment E on page 8 |
| Iodine 7553-56-2 | | 10 | TWA=0.01 (inhalable fraction and vapor) STEL=0.1 (vapor) | (F)MG/N95 | See comment E on page 8 |
| Iodoform 75-47-8 | Triiodomethane | | TWA=0.6 | (F)OV | |
| Iron oxide 1309-37-1 | Burnt sienna, Burnt umber, Ferric oxide, Hematite, Jeweler's rouge, Rouge | | TWA=5 mg/m ³ (respirable fraction) | N95 | |
| Iron oxide fume 1309-37-1 | Ferric oxide fume | | TWA=10 mg/m ³ (OSHA) TWA= 5 mg/m ³ (respirable fraction) | N95 | |
| Iron pentacarbonyl (as Fe) 13463-40-6 | Iron carbonyl | | TWA=0.1 STEL=0.2 | SA | Unknown sorbent effectiveness |
| Iron salts, soluble (as Fe) | Ferric chloride; Ferric nitrate; Ferric sulfate; Ferric/Ferrous salts, soluble; Ferrous chloride; Ferrous sulfate | | TWA=1 mg/m ³ | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--------------------------------|--|-----------------------|---------------------------------------|--|----------------------------|
| Isoamyl alcohol 123-51-3 | 3-Methyl-1-butanol, Fusel oil, Isobutyl carbinol, Isopentyl alcohol | 10000 | TWA=100 STEL=125 | (F)OV | See comment E on page 8 |
| Isobutane 75-28-5 | 2-Methyl propane, Methylpropane | 16000 | STEL=1000 | SA | Short OV service life |
| Isobutene 115-11-7 | 1,1-Dimethylethene, 1,1-Dimethylethylene, 2-Methylpropene, 2-Methylpropylene, Isobutylene | | TWA=250 | OV | Short service life |
| Isobutyl acetate 110-19-0 | 2-Methylpropyl acetate | 7500 | TWA=50 STEL=150 | (F)OV | |
| Isobutyl alcohol 78-83-1 | 2-Methyl-1-propanol, IBA, Isobutanol, Isopropylcarbinol | 8000 | TWA=50 | (F)OV | 3M 3510 Monitor |
| Isobutyl nitrite 542-56-3 | IBN; Nitrous acid, 2-methylpropyl ester; Nitrous acid, isobutyl ester | | C=1 (inhalable fraction and vapor) | OV/N95 | See comment E on page 8 |

| | | | | | |
|---|--|-------|---|--------|--|
| Isobutyraldehyde 78-84-2 | 2-Methyl-1-propanal, 2-Methylpropanal, 2-Methylpropionaldehyde, Isobutanal, Isobutyl aldehyde, Isobutyric aldehyde, Valine aldehyde | | TWA=25 (AIHA) | OV | Short service life |
| Isocyanuric acid 108-80-5 | Cyanuric acid; s-Triazine- 2,4,6(1H,3H,5H)-trione; s-Triazinetriol | | TWA=10 mg/m ³ (AIHA) TWA=5 mg/m ³ (AIHA, respirable fraction) | N95 | AM/N95 may be preferable if wet |
| Isooctyl alcohol 26952-21-6 | Isooctanol | 9000 | TWA=50 -skin- | OV | |
| Isophorone 78-59-1 | 3,5,5-Trimethyl-2-cyclohexene- 1-one | 800 | C=5 | OV | See comment E on page 8. 3M 3510 Monitor |
| Isophorone diisocyanate 4098-71-9 | IPDI | | TWA=0.005 | OV/N95 | |
| Isophthalic acid 121-91-5 | 1,3-Benzenedicarboxylic acid, IA, IPA, m-Phthalic acid | | TWA=10 mg/m ³ (AIHA) TWA=5 mg/m ³ (AIHA, respirable fraction) | N95 | |
| Isoprene 78-79-5 | 2-Methyl-1,3-butadiene | 15000 | TWA=2 (AIHA) | OV | Short service life |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---------------------------------------|--|-----------------------|----------------------|--|--|
| Isopropoxyethanol 109-59-1 | Ethylene glycol monoisopropyl ether, IPE, Isopropyl Cellosolve®, Isopropyl glycol | | TWA=25 -skin- | OV | |
| Isopropyl acetate 108-21-4 | Isopropyl ester of acetic acid, sec-Propyl acetate | 16000 | TWA=100 STEL=200 | (F)OV | 3M 3510 Monitor |
| Isopropylamine 75-31-0 | 2-Aminopropane, Monoisopropylamine | 4000 | TWA=5 STEL=10 | (F)AM (F)OV | AM not specifically approved, but 3M recommended for longer service life |
| N-Isopropylaniline 768-52-5 | o-Aminoisopropylbenzene, o-Isopropylaniline | | TWA=2 -skin- | OV | |
| Isopropyl ether 108-20-3 | Diisopropyl ether | 10000 | TWA=250 STEL=310 | OV | |
| Isopropyl glycidyl ether 4016-14-2 | 1,2-Epoxy-3-isopropoxypropane, IGE, Isopropoxymethyl-oxiran, Isopropyl epoxypropyl ether | 1000 | TWA=50 STEL=75 | (F)OV | |

| | | | | | |
|---|--|-----------------------|--|--------|--|
| Kaolin (particles with no asbestos and <1% crystalline silica) 1332-58-7 | Aluminium silicate, China clay | | TWA= 2 mg/m ³ (respirable fraction) | N95 | |
| Kerosene (applications with negligible aerosol) 8008-20-6 64712-81-0 64742-81-0 | Deobase, Diesel No.1, Fuel oil No.1, JP-4, JP-5, JP-8, Kerosine, | 7000 | TWA= 200 mg/m ³ (as total hydrocarbon vapor) -skin- | OV/P95 | When aerosols present, add a particulate prefilter |
| Ketene 463-51-4 | Carbomethene, Ethenone | | TWA=0.5 STEL=1.5 | (F)SA | Ineffective sorbents |
| Lead arsenate (as As) 3687-31-8 | | 100 mg/m ³ | TWA=0.01 mg/m ³ | N100 | |
| Lead chromate (as Cr) 7758-97-6 | Chromates of lead, Chrome orange, Red lead chromate | 30 mg/m ³ | TWA=0.012 mg/m ³ | N100 | |
| Lead, elemental and inorganic compounds (as Pb) 7439-92-1 | | 700 mg/m ³ | TWA=0.05 mg/m ³ | N100 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|--|--|---|
| d-Limonene 5989-27-5 | 1-Methyl-4(1-methylethenyl) cyclohexene, 4-Isopropyl-1- methcyclohexene, Cajeputene, Cinene, p-Mentha-1,8-diene | | TWA=30 (AIHA) | OV | |
| Lithium fluoride (as F) 7789-24-4 | | | TWA=2.5 mg/m ³ | N95 | |
| Lithium hydride 7580-67-8 | | 55 mg/m ³ | C=0.05 mg/m ³ (inhalable fraction) | N95 | |
| Lithium hydroxide 1310-65-2 | | | C=1 mg/m ³ (AIHA) | N95 | |
| Lithium hydroxide monohydrate 1310-66-3 | | | C=1.8 mg/m ³ (AIHA) | N95 | |
| Lithium oxide 12057-24-8 | Dilithium oxide, Lithium monoxide | | C=1 mg/m ³ (AIHA) | N95 | |
| LPG 68476-85-7 | Bottled gas, Liquefied petroleum gas | 19000 | TWA=1000 (OSHA) | SA | Mixture with compounds with short OV service life |

| | | | | | |
|---|---|-------|---|-----------|--------------------------------|
| Magnesite 546-93-0 | Magnesium carbonate | | TWA=15 mg/m ³ (OSHA) TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Magnesium oxide fume 1309-48-4 | Magnesia fume | | TWA=10 mg/m ³ (inhalable fraction) | N95 | |
| Maleic anhydride 108-31-6 | 2,5-Furandione, cis- Butenedioic anhydride, Maleic acid anhydride | 14000 | TWA=0.01 (Inhalable fraction and vapor) | (F)OV/N95 | See comment D on page 8 |
| Manganese cyclopentadienyl tricarbonyl 12079-65-1 | MCT | | TWA=0.1 mg/m ³ -skin- | SA | Properties of vapor unknown |
| Manganese, elemental and inorganic compounds (as Mn) 7439-96-5 | | | TWA=0.1 mg/m ³ (inhalable fraction) TWA=0.02 mg/m ³ (respirable fraction) C= 5 mg/m ³ (OSHA) | N95 | |
| Melamine 108-78-1 | 1,3,5-Triazine-2,4,6-triamine; 2,4,6-Triamino-1,3,5-triazine; Cyanuramide | | TWA=10 mg/m ³ (AIHA, inhalable fraction) TWA=5 mg/m ³ (AIHA, respirable fraction) | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|---|--|--|
| 2-Mercaptobenzo- thiazole 149-30-4 | 2-Benzothiazolethiol, 2-Benzothiazolylmercaptan, Benzothiazole-2-thione, Mercaptobenzothiazole | | TWA=5 mg/m ³ (AIHA) -skin- | N95 | |
| Mercaptoethanol 60-24-2 | 1-Hydroxy-2-mercaptoethane, 2-Hydroxy-1-ethanethiol, 2-Hydroxyethylmercaptan, 2ME, 2-Mercaptoethanol, 2-Thioethanol, Thioethyleneglycol, Thioglycol | | TWA=0.2 (AIHA) | OV | |
| Mercury, alkyl compounds (as Hg) | | 10 mg/m ³ | TWA=0.01 mg/m ³ -skin- | SA | |
| Mercury, aryl compounds (as Hg) | | 28 mg/m ³ | TWA=0.1 mg/m ³ -skin- | N95 | Dust with essentially no vapor pressure only |
| Mercury, inorganic compounds (as Hg) | | 28 mg/m ³ | TWA=0.025 mg/m ³ -skin- | N95 | Dust with essentially no vapor pressure only. Hg/N95 for volatile liquids |
| Mercury, metallic mercury vapor 7439-97-6 | Hg, Quicksilver | 28 mg/m ³ | TWA=0.025 mg/m ³ -skin- | Hg | |

| | | | | | |
|---------------------------------------|---|-------|--------------------------------|----------------|---|
| Mesityl oxide 141-79-7 | Isobutenyl methyl ketone, Isopropylidene acetone, Methyl isobutenyl ketone | 5000 | TWA=15 STEL=25 | (F)OV | 3M 3510 Monitor |
| Methacrylic acid 79-41-4 | a-Methacrylic acid | | TWA=20 | (F)OV | |
| Methane 74-82-8 | Biogas, Fire damp, Marsh gas, Methyl hydride, R 50 (refrigerant) | | | | Simple asphyxiant, oxygen displacing gas |
| 2-Methoxyethanol 109-86-4 | Ethylene glycol monomethyl ether, Methyl Cellosolve® | 2000 | TWA=0.1 -skin- | OV | 3M 3510 Monitor |
| 2-Methoxyethyl acetate 110-49-6 | Ethylene glycol methyl ether acetate, Ethylene glycol monomethyl ether acetate, Methyl Cellosolve® acetate | 4000 | TWA=0.1 -skin- | OV | 3M 3510 Monitor |
| 4-Methoxyphenol 150-76-5 | Hydroquinone monomethyl ether, p-Methoxyphenol | | TWA=5 mg/m ³ | N95 | |
| 3-Methoxypropyl amine 5332-73-0 | 1-Propanimine, 3-methoxy | | TWA=5 (AIHA) STEL=15 (AIHA) | (F)OV (F)AM | Irritation also provides warning. AM may be preferred, but not specifically approved |
| Methyl acetate 79-20-9 | Acetic acid methyl ester, Methyl acetic ester, Methyl ethanoate | 10000 | TWA=200 STEL=250 | OV | Short service life |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|-------------------------------|--|-----------------------|
| Methyl acetylene 74-99-7 | Allylene, Propyne | 15000 | TWA=1000 | SA | Short OV service life |
| Methyl acetylene propadiene mixture 59355-75-8 | MAPP gas, Methyl acetylene- allene mixture, Propyne-allene mixture | 15000 | TWA=1000 STEL=1250 | SA | Short OV service life |
| Methyl acrylate 96-33-3 | Methyl propenoate | 1000 | TWA=2 -skin- | (F)OV | 3M 3510 Monitor |
| Methylacrylonitrile 126-98-7 | 2-Methyl-2-propenenitrile, Isoprene cyanide | 20000 | TWA=1 -skin- | SA | |
| Methylal 109-87-5 | Dimethoxymethane, Dimethylacetal formaldehyde, Formal, Methyl formal | 15000 | TWA=1000 | SA | |
| Methyl alcohol 67-56-1 | Carbinol, Methanol, Wood alcohol | 25000 | TWA=200 STEL=250 -skin- | SA | Short OV service life |
| Methylamine 74-89-5 | Monomethylamine | 100 | TWA=5 STEL=15 | (F)AM | |

| | | | | | |
|--------------------------------------|---|-------|--------------------------------|-------|---|
| Methyl amyl alcohol 108-11-2 | Methyl isobutyl carbinol | 2000 | TWA=25 STEL=40 -skin- | OV | |
| Methyl n-amyl ketone 110-43-0 | 2-Heptanone, Amyl methyl ketone, Methyl amyl ketone, n-Amyl methyl ketone | 4000 | TWA=50 | OV | See comment E on page 8 |
| Methylaniline 100-61-8 | MA, Monomethyl aniline, N-Methyl aniline | 100 | TWA=0.5 -skin- | OV | |
| Methyl bromide 74-83-9 | Bromomethane | 2000 | TWA=1 C=20 (OSHA) -skin- | (F)SA | Short OV service life. Use of 60928 cartridge/ filter recommended by 3M, not specifically approved for methyl bromide |
| Methyl tert-butyl ether 1634-04-4 | 2,2-MMOP, 2-Methoxy-2-methyl-propane, MTBE, tert-Butyl methyl ether | 25000 | TWA=50 | OV | Short service life. 3M 3510 Monitor |
| Methyl n-butyl ketone 591-78-6 | 2-Hexanone, MBK | 5000 | TWA=5 STEL=10 -skin- | OV | 3M 3510 Monitor |
| Methyl chloride 74-87-3 | Chloromethane | 10000 | TWA=50 STEL=100 -skin- | SA | Short OV service life |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|-------------------------------------|--|-------------------------------------|
| Methyl chloroform 71-55-6 | 1,1,1-Trichloroethane | 1000 | TWA=350 STEL=450 | OV | 3M 3510 Monitor |
| Methyl 2-cyanoacrylate 137-05-3 | Mecrylate | | TWA=0.2 | (F)OV | |
| Methylcyclohexane 108-87-2 | Cyclohexylmethane, Hexahydrotoluene | 10000 | TWA=400 | OV | |
| Methylcyclohexanol 25639-42-3 | Hexahydrocresols | 10000 | TWA=50 | OV | |
| o-Methylcyclo- hexanone 583-60-8 | 2-Methylcyclohexanone | 2500 | TWA=50 STEL=75 -skin- | (F)OV | Irritation also provides warning |
| 2-Methylcyclo- pentadienyl manganese tricarbonyl (as Mn) 12108-13-3 | | | TWA=0.2 mg/m ³ -skin- | OV/N95 | SA preferable if heat involved |
| Methylene bisphenyl isocyanate 101-68-8 | 4,4-Diphenylmethane diisocyanate, MDI, Methylene- bis-(4-phenyl isocyanate) | 100 mg/m ³ | TWA=0.005 C=0.02 (OSHA) | OV/N95 | |

| | | | | | |
|--|--|------|--|--------|---|
| Methylene chloride 75-09-2 | Dichloromethane, Methylene dichloride | 5000 | TWA=25 (OSHA) STEL=125 (OSHA) | (F)SA | OSHA requires (F)SA; no change schedule allowed. Short OV service life. 3M 3530 Monitor |
| 4,4'-Methylene-bis-(2-chloroaniline) 101-14-4 | 4,4'-Methylene-bis-(2-chlorobenzamine), DACPM, MOCA | | TWA=0.01 -skin- | OV | |
| Methylene-bis(4-cyclohexylisocyanate) 5124-30-1 | | | TWA=0.005 | OV/N95 | |
| 4,4'-Methylene dianiline 101-77-9 | 4,4'-Diaminodiphenylmethane, MDA | | TWA=0.01 (OSHA) STEL=0.1 (OSHA) -skin- | N100 | Use OV/N100 if heat is involved. See 29 CFR 1910.1050. |
| Methyl ethyl ketone 78-93-3 | 2-Butanone, MEK | 3000 | TWA=200 STEL=300 | (F)OV | 3M 3510 Monitor |
| Methyl ethyl ketone peroxide 1338-23-4 | MEKP | | C=0.2 | (F)OV | |
| Methyl ethyl ketoxime 96-29-7 | 2-Butanone oxime, MEKO | | TWA=10 (AIHA) | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|-------------------------------------|---|-----------------------|------------------------------------|--|--|
| Methyl formate 107-31-3 | Formic acid methyl ester, Methyl methanoate | 5000 | TWA=50 STEL=100 | SA | Short OV service life |
| Methyl hydrazine 60-34-4 | Monomethyl hydrazine | 50 | TWA=0.01 C=0.2 (OSHA) -skin- | (F)AM | |
| Methyl iodide 74-88-4 | Iodomethane | 800 | TWA=2 -skin- | (F)SA | Short OV service life. Use of 60928 cartridge/filter recommended by 3M, not specifically approved for methyl iodide. |
| Methyl isoamyl ketone 110-12-3 | 2-Methyl-5-hexanone, 5-Methyl-2-hexanone, MIAK | 10000 | TWA=20 STEL=50 | (F)OV | |
| Methyl isobutyl ketone 108-10-1 | Hexone, MIBK | 3000 | TWA=20 STEL=75 | (F)OV | 3M 3510 Monitor |
| Methyl isocyanate 624-83-9 | Isocyanic acid,methyl ester | 20 | TWA=0.02 STEL=0.06 -skin- | SA | Unknown sorbent effectiveness |
| Methyl isopropyl ketone 563-80-4 | 3-Methyl-2-butanone, MIPK | | TWA=20 | (F)OV | |

| | | | | | |
|--|---|------|-------------------------|------------------|----------------------------|
| Methyl mercaptan 74-93-1 | Mercaptomethane, Methanethiol, Methyl sulfhydrate, Thiomethyl alcohol | 400 | TWA=0.5 C=10 (OSHA) | OV | Short service life |
| Methyl methacrylate 80-62-6 | 2-Methyl-2-propenoic acid methyl ester; Methacrylic acid,methyl ester; Methyl alpha- methyl-acrylate; Methyl-2- methyl-2-propenoate; Methyl-2- methylpropenoate; MMA | 4000 | TWA=50 STEL=100 | OV | 3M 3510 Monitor |
| 1-Methylnaphthalene 90-12-0 | a-Methyl naphthalene, a-Methylnaphthalene | | TWA=0.5 -skin- | OV/R95 OV/P95 | |
| 2-Methylnaphthalene 91-57-6 | b-Methyl naphthalene, b-Methylnaphthalene | | TWA=0.5 -skin- | OV/R95 OV/P95 | |
| Methyl propyl ketone 107-87-9 | 2-Pentanone, Ethyl acetone, MPK | 5000 | STEL=150 | (F)OV | 3M 3510 Monitor |
| n-Methyl-2- pyrrolidone 872-50-4 | 1-Methyl-2-pyrrolidone, m-Pyrol, n-Methyl Pyrrolidone, NMP | | TWA=10 (AIHA) -skin- | OV | |
| Methyl silicate 681-84-5 | Tetramethoxy silane | | TWA=1 | (F)OV | |
| a-Methyl styrene 98-83-9 | 1-Methyl-1-phenylethylene, AMS | 5000 | TWA=10 | OV | See comment E on page 8 |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|--|--|----------------------------------|
| Methyltrichlorosilane 75-79-6 | Trichloromethylsilane | | C=1 (AIHA) | (F)AG/N95 | Irritation also provides warning |
| Methyl vinyl ketone 78-94-4 | 3-Buten-2-one, 3-Butene-2-one, Acetyl ethylene, d(3)-2-Butenone, g-Oxo-a-Butylene, Methyl vinyl acetone, Methylene acetone | 21000 | C=0.2 -skin- | OV | |
| Mica (less than 1% quartz) 12001-26-2 | | | TWA=3 mg/m ³ (respirable fraction) | N95 | |
| Mineral oil (pure, highly and severely refined), excluding metal working fluids 8012-95-1 | Liquid petrolatum, Parrafin oil, USP mineral oil, White mineral oil | | TWA= 5 mg/m ³ (inhalable particulate matter) | R95 P95 | |
| Molybdenum and insoluble compounds (as Mo) 7439-98-7 | | | TWA=10 mg/m ³ (inhalable fraction) TWA=3 mg/m ³ (respirable fraction) | N95 | |

| | | | | | |
|--|--|-------|--|-----------|--|
| Molybdenum, soluble compounds (as Mo) 7439-98-7 | | | TWA=0.5 mg/m ³ (respirable fraction) | N95 | |
| Monochloroacetic acid 79-11-8 | Chloroethanoic acid, MCAA | | TWA=0.5 (inhalable fraction and vapor) -skin- | (F)OV/N95 | See comment D on page 8 |
| Morpholine 110-91-8 | Diethylenimide oxide, Tetrahyrdo-1,4-oxazine | 8000 | TWA=20 -skin- | (F)OV | |
| Naphtha (coal tar) 8030-30-6 | Crude solvent coal tar naphtha, High solvent naphtha, Rubber solvent | 10000 | TWA=100 (OSHA) | (F)OV | Odor variable. Irritation also provides warning. |
| Naphthalene 91-20-3 | Naphthalin, White tar | 500 | TWA=10 -skin- | OV | 3M 3510 Monitor. See comment E on page 8 |
| Natural gas 8006-14-2 | | | | | Simple asphyxiant, oxygen displacing gas. |
| Natural rubber latex 9006-04-6 | Caoutchouc, India rubber, Natural latex, Natural rubber, NRL, Polyisoprene, Rubber | | TWA=0.0001 mg/m ³ (inhalable fraction) -skin- | N95 | |
| Nickel carbonyl (as Ni) 13463-39-3 | Nickel tetracarbonyl | 7 | TWA=0.001 (OSHA) C=0.05 | (F)SA | Unknown sorbent effectiveness |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|--|--|----------------------------|
| Nickel, elemental/metal compounds (as Ni) 7440-02-0 | | | TWA=1 mg/m ³ (OSHA) TWA=1.5 mg/m ³ (inhalable fraction) | N95 | |
| Nickel, insoluble inorganic compounds (not otherwise specified) (as Ni) | | | TWA=0.2 mg/m ³ (inhalable fraction) | N95 | |
| Nickel, soluble inorganic compounds (not otherwise specified) (as Ni) | | | TWA=0.1 mg/m ³ (inhalable fraction) | N95 | |
| Nickel subsulfide (as Ni) 12035-72-2 | | | TWA=0.1 mg/m ³ (inhalable fraction) | N95 | |
| Nicotine 54-11-5 | 3-(1-Methyl-2-pyrrolidyl) pyridine | 35 mg/m ³ | TWA=0.5 mg/m ³ -skin- | OV/P95 | See comment D on page 8 |
| Nitric acid 7697-37-2 | Aqua fortis, Hydrogen nitrate, Red fuming nitric acid, RFNA, WFNA, White fuming nitric acid | 100 | TWA=2 STEL=4 | (F)SA | Ineffective sorbents |

| | | | | | |
|-----------------------------------|---|------------------------|------------------------------------|--------|----------------------------------|
| Nitric oxide 10102-43-9 | Nitrogen monoxide, NO | 100 | TWA=25 | SA | Ineffective sorbents |
| p-Nitroaniline 100-01-6 | 1-Amino-4-nitrobenzene, 4-Nitroaniline, Azoic diazo component 37, Fast Red GG base, p-Aminonitro-benzene, PNA | 300 mg/m ³ | TWA=3 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| Nitrobenzene 98-95-3 | Nitrobenzol, Oil of mirbane | 200 | TWA=1 -skin- | OV | |
| p-Nitrochlorobenzene 100-00-5 | 1-Chloro-4-nitrobenzene, 4-Chloronitrobenzene, PCNB, PNCB | 1000 mg/m ³ | TWA=0.1 -skin- | OV | |
| Nitroethane 79-24-3 | | 1000 | TWA=100 | (F)OV | |
| Nitrogen dioxide 10102-44-0 | Nitrogen peroxide | 50 | TWA=0.2 C=5 (OSHA) | SA | Ineffective sorbents |
| Nitrogen trifluoride 7783-54-2 | Nitrogen fluoride | 2000 | TWA=10 | SA | Unknown sorbent effectiveness |
| Nitroglycerin (NG) 55-63-0 | Glyceryl trinitrate, Trinitroglycerin | 500 mg/m ³ | TWA=0.05 C=0.2 (OSHA) -skin- | OV | |
| Nitromethane 75-52-5 | Nitrocarbol | 1000 | TWA=20 | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|---|-----------------------|---|--|----------------------------|
| 1-Nitropropane 108-03-2 | | 2300 | TWA=25 | OV | |
| 2-Nitropropane 79-46-9 | sec-Nitropropane | 2300 | TWA=10 | OV | |
| Nitrotoluene 88-72-2 99-08-1 99-99-0 | Nitrotoluol | 200 | TWA=2 -skin- | OV/N95 | See comment D on page 8 |
| 5-Nitro-o-toluidine 99-55-8 | 2-Methyl-5-nitrobenzenamine, 5-Nitro-2-toluidine, Azoic Diazo Compound 12 | | TWA=1 mg/m ³ (inhalable fraction) | OV/R95 OV/P95 | |
| Nitrous oxide 10024-97-2 | Dinitrogen monoxide | | TWA=50 | SA | Ineffective sorbents |
| Nonane 111-84-2 | n-Nonane | 8000 | TWA=200 | OV | |
| Octachloro- naphthalene 2234-13-1 | Halowax™ 1051 | | TWA=0.1 mg/m ³ STEL=0.3 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |

| | | | | | |
|---|---|-----------------------|---|--------|----------------------------------|
| Octane, all isomers 111-65-9 540-84-1 | n-Octane, Isooctane | 5000 | TWA=300 | OV | 3M 3510 Monitor |
| 1-Octanol 111-87-5 | 1-Hydroxyoctane, Alcohol C-8, Capryl alcohol, Heptyl carbinol, n-Octanol, n-Octyl alcohol | | TWA=50 (AIHA) | OV | |
| 1-Octene 111-66-0 | a-Octene, a-Octylene | 8000 | TWA=75 (AIHA) | OV | |
| Osmium tetroxide (as Os) 20816-12-0 | Osmic acid | 1 mg/m ³ | TWA=0.0002 STEL=0.0006 | (F)SA | Unknown sorbent effectiveness |
| Oxalic acid 144-62-7 6153-56-6 | Ethane dioic acid, Oxalic acid dihydrate | 500 mg/m ³ | TWA=1 mg/m ³ STEL=2 mg/m ³ | OV/N95 | See comment D on page 8 |
| p,p-Oxybis (benzenesulfonyl hydrazide) 80-51-3 | Benzenesulfonic acid, 4,4-Oxybis-dihydrazide; Celogen®; Diphenyl ether 4,4'-disulfohydrazide; OBSH | | TWA=0.1 mg/m ³ (inhalable fraction) | N95 | |
| Oxygen difluoride 7783-41-7 | Difluorine monoxide, Fluorine monoxide | 0.5 | C=0.05 | SA | Unknown sorbent effectiveness |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|--|--|---|
| Ozone 10028-15-6 | | 10 | TWA=0.1 (light work) TWA=0.08 (moderate work) TWA=0.05 (heavy work) | OZ | Respirators with nuisance level organic vapor relief recommended by 3M up to 10X OEL. Not NIOSH approved for ozone. |
| Paraffin wax fume 8002-74-2 | | | TWA=2 mg/m ³ | N95 | |
| Particulates Not Otherwise Regulated | Nuisance particulates | | TWA=15 mg/m ³ (total dust, OSHA) TWA=10 mg/m ³ (inhalable fraction) TWA=3 mg/m ³ (respirable fraction) | N95 | This category includes many materials. For oils, an R or P95 filter/respirator is recommended |
| Pentaborane 19624-22-7 | Pentaboron nonahydride, Stable pentaborane | 3 | TWA=0.005 STEL=0.015 | SA | Unknown sorbent effectiveness |
| Pentachloro- naphthalene 1321-64-8 | Halowax™ 1013 | | TWA=0.5 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |

| | | | | | |
|---|---|-------|--|--------|----------------------------|
| Pentaerythritol 115-77-5 | Tetramethylolmethane | | TWA=10 mg/m ³ TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Pentaerythritol triacylate 3524-68-3 | 2-Propenoic acid, 2-(hydroxymethyl)-2-[[[(1-oxo- 2-propenyl)oxy]methyl]-1,3- propanediyl-ester, PETA | | TWA=1 mg/m ³ (AIHA) | OV/P95 | See comment D on page 8 |
| 1,1,1,2,2- Pentafluoroethane 354-33-6 | Fluorocarbon 125, HFC-125, Pentafluoroethane | | TWA=1000 (AIHA) | SA | Ineffective sorbents |
| 1,1,1,3,3- Pentafluoropropane 460-73-1 | Genetron™ 245fa, HFC-245fa, R-245fa | | TWA=300 (AIHA) | SA | |
| Pentane, all isomers 109-66-0 78-78-4 463-82-1 | n-Pentane | 15000 | TWA=1000 | OV | Short service life |
| 2,4-Pentanedione 123-54-6 | Acetylacetone, Diacetylmethane | | TWA=25 -skin- | OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|---|--|---|
| Pentyl acetate, all isomers 628-63-7 626-38-0 620-11-1 625-16-1 123-92-2 624-41-9 | 2-Acetoxy pentane, 3-Amyl acetate, n-Amyl acetate, sec-Amyl acetate, tert-Amyl acetate, Banana oil, 1,1-Dimethylpropyl acetate, Isoamyl acetate, Isopentyl acetate, 3-Methyl-1-butanol acetate, 1-Methylbutyl acetate, 2-Methylbutyl acetate, 3-Methylbutyl acetate, 2-Methylbutyl ethanoate, 1-Pentanol acetate, 2-Pentanol acetate, 1-Pentyl acetate, 2-Pentyl acetate, 3-Pentyl acetate | 3000-9000 | TWA=50 STEL=100 | OV | See comment E on page 8. 3M 3510 Monitor |
| Peracetic acid 79-21-0 | Acetic peroxide, Peroxyacetic acid | | STEL= 0.4ppm (Inhalable fraction and vapor) | (F)OV/AG | See Technical Data Bulletin #185. See comment E on page 8 |
| Perchloroethylene 127-18-4 | Perk, Tetrachloroethylene | 500 | TWA=25 STEL=100 | (F)OV | |
| Perchloromethyl mercaptan 594-42-3 | PMM, Trichloromethyl sulfur chloride | 10 | TWA=0.1 | OV | |

| | | | | | |
|--|--|-------|---------------------------|--------|--|
| Perchloryl fluoride 7616-94-6 | Chlorine oxyfluoride | 385 | TWA=3 STEL=6 | SA | Unknown sorbent effectiveness |
| Perfluorobutyl ethylene 19430-93-4 | 1H,1H,2H-Perfluorohexene; 1-Hexane,3,3,4,4,5,5,6,6,6-nonafluoro; PFBE | | TWA=100 | OV | Short service life |
| Perfluoroisobutylene 382-21-8 | Octafluoroisobutylene, Octafluoro-sec-butene, PFIB | | C=0.01 | SA | Short OV service life |
| Persulfates, Ammonium 7727-54-0 | | | TWA=0.1 mg/m ³ | N95 | |
| Persulfates, Potassium 7727-21-1 | | | TWA=0.1 mg/m ³ | (F)N95 | |
| Persulfates, Sodium 7775-27-1 | | | TWA=0.1 mg/m ³ | (F)N95 | |
| Petroleum distillates 8002-05-9 | Aliphatic petroleum naphtha, Petroleum ether (boiling range 95-115 degrees C), Petroleum naphtha | 10000 | TWA=500 (OSHA) | OV | Odor variable. See also Gasoline, Stoddard solvent |
| Phenol 108-95-2 | Carbolic acid, Monohydroxy benzene | 250 | TWA=5 -skin- | OV/N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|---------------------------|--|---|
| m-Phenylenediamine 108-45-2 | 1,3-Benzenediamine, m-Diaminobenzene | | TWA=0.1 mg/m ³ | OV/N95 | SA preferable if heat involved |
| o-Phenylenediamine 95-54-5 | 1,2-Benzenediamine, o-Diaminobenzene, Orthamine | | TWA=0.1 mg/m ³ | OV/N95 | SA preferable if heat involved |
| p-Phenylenediamine 106-50-3 | 1,4-Diaminobenzene, p-Diaminobenzene | | TWA=0.1 mg/m ³ | OV/N95 | SA preferable if heat involved |
| Phenyl ether, vapor 101-84-8 | Diphenyl ether, Diphenyl oxide | 7000 | TWA=1 STEL=2 | OV | See comment E on page 8. 3M 3510 Monitor. |
| Phenyl ether-biphenyl mixture vapor 8004-13-5 | Diphenyl oxide-diphenyl mixture, Dowtherm™ A | | TWA=1 (OSHA) | OV | See comment E on page 8 |
| Phenyl glycidyl ether 122-60-1 | 1,2-Epoxy-3-phenoxy propane, Glycidyl phenyl ether, Oxirane, PGE, Phenoxyethyl, Phenoxypropoxide, Phenyl epoxypropyl ether | | TWA=0.1 -skin- | OV | |
| Phenylhydrazine 100-63-0 | Hydrazinobenzene | 295 | TWA=0.1 -skin- | (F)OV | |

| | | | | | |
|--|---|-------------------------|---|--------|--|
| Phenyl isocyanate 103-71-9 | Isocyanatobenzene, Carbamil Phenyl carbamide | | TWA=0.005 STEL=0.015 | OV | |
| Phenyl mercaptan 108-98-5 | Benzenethiol, Thiophenol | | TWA=0.1 | OV | |
| Phenylphosphine 638-21-1 | | | C=0.05 | OV | |
| Phosgene 75-44-5 | Carbon oxychloride, Carbonyl chloride, Chloroformyl chloride | 2 | TWA=0.1 | SA | |
| Phosphine 7803-51-2 | Hydrogen phosphide, Phosphorated hydrogen, Phosphorus hydride | 200 | TWA=0.3 STEL=1 | SA | Hg recommended for certain applications. See Technical Data Bulletin #212 |
| 2-Phosphono-1,2,4- butanetricarboxylic acid 37971-36-1 | PBTC | | TWA=10 (AIHA) | N95 | |
| Phosphoric acid 7664-38-2 | m-Phosphoric acid, o-Phosphoric acid, White phosphoric acid | 10000 mg/m ³ | TWA=1 mg/m ³ STEL=3 mg/m ³ | (F)N95 | N95 acceptable with appropriate eye/face protection |
| Phosphorus (yellow) 12185-10-3 | White phosphorus, WP | | TWA=0.1 mg/m ³ | SA | If no phosphorus vapor or phosphine gas present, N95 |
| Phosphorus oxychloride 10025-87-3 | Phosphoryl chloride | | TWA=0.1 | (F)AG | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|----------------------------|---|--|----------------------------|
| Phosphorus pentachloride 10026-13-8 | Phosphoric chloride | 200 mg/m ³ | TWA=0.1 | AG | |
| Phosphorus pentasulfide 1314-80-3 | Phosphoric sulfide | 750 mg/m ³ | TWA=1 mg/m ³ STEL=3 mg/m ³ | N95 | |
| Phosphorus trichloride 7719-12-2 | Phosphorus chloride | 50 | TWA=0.2 STEL=0.5 | (F)AG | |
| Phthalic anhydride 85-44-9 | 1,3-Isobenzofurandione, PAN | 10000 mg/m ³ | TWA=0.002 mg/m ³ (inhalable fraction and vapor) STEL=0.005 mg/m ³ (inhalable fraction and vapor) -skin- | OV/N95 | See comment D on page 8 |
| m-Phthalodinitrile 626-17-5 | IPN, Isophthalodinitrile, m-Dicyanobenzene | | TWA=5 mg/m ³ (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |
| o-Phthalodinitrile 91-15-6 | 1,2-Benzenedicarbonitrile, 1,2-dicyanobenzene, 1,2-Benzodinitrile, o-Benzenedinitrile, Phthalic acid dinitrile | | TWA=1 mg/m ³ (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |

| | | | | | |
|--|---|-----------------------|---|--------|----------------------------|
| 2-Picoline 109-06-8 | 2-Methyl-pyridine, a-Picoline | | TWA=2 (AIHA) STEL=5 (AIHA) -skin- | OV | |
| 3-Picoline 108-99-6 | 3-Methyl-pyridine, b-Picoline | | TWA=2 (AIHA) STEL=5 (AIHA) -skin- | OV | |
| 4-Picoline 108-89-4 | 4-Methyl-pyridine, g-Picoline | | TWA=2 (AIHA) STEL=5 (AIHA) -skin- | OV | |
| Picric acid 88-89-1 | 2,4,6-Trinitrophenol, Lyddite, Melinite, Pertite, Shimose | 100 mg/m ³ | TWA=0.1 mg/m ³ | N95 | |
| Piperazine and salts 110-85-0 | 1,4-Piperazine, 1,4-Diazacyclohexane, Diethylenediamine, Hexahydropyrazine, Piperazidine | | TWA=0.03 (inhalable fraction and vapor, as piperazine) | OV/N95 | See comment D on page 8 |
| Piperidine 110-89-4 | Hexahydropyridine | | TWA=1 (AIHA) -skin- | (F)OV | |
| Platinum metal (as Pt) 7440-06-4 | | | TWA=1 mg/m ³ | N95 | |
| Platinum soluble salts (as Pt) | | | TWA=0.002 mg/m ³ | (F)N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|--|--|----------------------------|
| Polyethylene glycols 25322-68-3 | PEG, PGE, Polyoxyethylene | | TWA=10 mg/m ³ (AIHA) | R95 P95 | See comment G on page 8 |
| Polypropylene glycols 25322-69-4 | PPG | | TWA=10 mg/m ³ (AIHA) | R95 P95 | See comment G on page 8 |
| Polyvinyl chloride 9002-86-2 | Cloroethene polymer, Cloroethylene homopolymer, Cloroethylene polymer, Polychloroethylene, PVC, Vinyl chloride homoploymer, Vinyl chloride polymer | | TWA=1 mg/m ³ (respirable fraction) | N95 | |
| Portland cement (containing no asbestos and <1% crystalline silica) 65997-15-1 | Cement, Hyraulic cement, Portland cement silicate | | TWA=1 mg/m ³ (respirable fraction) | N95 | |
| Potassium bromate 7758-01-2 | Bromic acid potassium salt | | TWA=0.1 mg/m ³ (AIHA) | N95 | |
| Potassium hydroxide 1310-58-3 | Caustic potash, Lye, Potassium hydrate | | C=2 mg/m ³ | N95 | |

| | | | | | |
|---|--|-------|--------------------------|-------|--|
| Propane 74-98-6 | Dimethyl methane, n-Propane | 20000 | TWA=1000 (OSHA) | SA | Ineffective sorbents |
| 2-Propanol 67-63-0 | IPA, Isopropanol, Isopropyl alcohol, sec-Propyl alcohol | 12000 | TWA=200 STEL=400 | (F)OV | Irritation also provides warning. 3M 3530 Monitor |
| n-Propanol 71-23-8 | 1-Propanol, Ethyl carbinol, n-Propyl alcohol, Propan-1-ol | 4000 | TWA=100 | (F)OV | See comment E on page 8 |
| Propargyl alcohol 107-19-7 | 2-Propyn-1-ol | | TWA=1 -skin- | OV | |
| Propargyl bromide 106-96-7 | 1-Bromo-2-propyne; 3-Bromopropyne; Bromopropyne; gama- Bromoallylene; Propyne, 3-bromo | | TWA=0.1 (AIHA) -skin- | OV | |
| 2-Propenoic acid, Isooctyl ester 29590-42-9 | IOA, Isoctyl acrylate | | TWA=5 (AIHA) | OV | |
| b-Propiolactone 57-57-8 | 3-Hydroxy beta-lactone; 3-Hydroxypropionic acid; beta- Propiolactone; BPL; Hydroacrylic acid, beta-lactone; Propiolactone | 29000 | TWA=0.5 | (F)OV | OSHA requires SA with hood for certain applications; see 29 CFR 1910.1003 |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|------------------------------------|--|----------------------------|
| Propionaldehyde 123-38-6 | 1-Propanal, Methylacetaldehyde, Propylaldehyde | | TWA=20 | SA | Short OV service life |
| Propionic acid 79-09-4 | Ethylformic acid, Methylacetic acid | 29000 | TWA=10 | (F)OV | |
| n-Propyl acetate 109-60-4 | Acetic acid n-propyl ester, Propyl acetate | 8000 | TWA=200 STEL=250 | (F)OV | 3M 3510 Monitor |
| Propylene 115-07-1 | 1-Propene, 1-Propylene, Methylethene, Methylethylene, Propene | | TWA=500 | SA | |
| Propylene dichloride 78-87-5 | 1,2-Dichloropropane | 2000 | TWA=10 | OV | 3M 3510 Monitor |
| Propylene glycol (aerosol only) 57-55-6 | 1,2-Dihydroxy propane, 1,2-Propanediol, Methyl glycol | | TWA=10 mg/m ³ (AIHA) | R95 P95 | See comment G on page 8 |
| Propylene glycol (vapor and aerosol) 57-55-6 | 1,2-Dihydroxy propane, 1,2-Propanediol, Methyl glycol | 24000 | TWA=10 mg/m ³ (AIHA) | OV/P95 | See comment G on page 8 |

| | | | | | |
|---|---|-------|-------------------------------|-------|--|
| Propylene glycol dinitrate 6423-43-4 | 1,2-Propanediol dinitrate, 1,2-Propylene glycol dinitrate | | TWA=0.05 -skin- | (F)OV | |
| Propylene glycol monomethyl ether 107-98-2 | 1-Methoxy-2-propanol | 16000 | TWA=50 STEL=100 | OV | 3M 3510 Monitor |
| Propylene glycol monomethyl ether acetate 108-65-6 | 1-Methoxy-2-acetoxypropane, 1-Methoxy-2-propanol acetate, 2-Methoxy-1-methylethyl acetate, Glycol ether PM acetate, PGMEA | 15000 | TWA=50 (AIHA) | OV | 3M 3510 Monitor |
| Propyleneimine 75-55-8 | 2-Methylaziridine | 500 | TWA=0.2 STEL=0.4 -skin- | (F)OV | |
| Propylene oxide 75-56-9 | 1,2-Epoxypropane, 1,2-Propylene oxide, 2,3-Epoxypropane, Methyloxirane, Propene oxide | 2000 | TWA=2 | OV | Short service life. 3M 3550 Monitor |
| n-Propyl nitrate 627-13-4 | Nitric acid n-propylester | 2000 | TWA=25 STEL=40 | OV | |
| Pyridine 110-86-1 | Azabenzene, Azine | 3600 | TWA=1 | OV | |
| Quinoline 91-22-5 | 1-Azabenzophthalene, 1-Benzazine, Chinoline, Lencol, Leukoline | | TWA=0.001 (AIHA) -skin- | (F)OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|--|--|---|
| Quinone 106-51-4 | Benzoquinone, p-Benzoquinone | 300 mg/m ³ | TWA=0.1 | (F)OV/N95 | |
| Resorcinol 108-46-3 | 1,3-Benzenediol, m-Dihydroxybenzene | 14000 | TWA=10 STEL=20 | N95 | OV/N95 may be preferable if heat is involved |
| Rhodium, metal and insoluble compounds 7440-16-6 | | | TWA=0.1 mg/m ³ (OSHA) | N95 | |
| Rhodium, soluble compounds (as Rh) | | | TWA=0.001 mg/ m ³ (OSHA) | N95 | |
| Selenium & compounds, (as Se) 7782-49-2 | | | TWA=0.2 mg/m ³ | N95 | |
| Selenium hexafluoride 7783-79-1 | | 5 | TWA=0.05 | SA | Unknown sorbent effectiveness |
| Silica, amorphous (diatomaceous earth) 61790-53-2 | Diatomite, Silicon dioxide | | TWA=0.8 mg/m ³ (OSHA) | N95 | Assuming 100% SiO ₂ (80 mg/m ³ divided by %SiO ₂) |

| | | | | |
|---|---|---|-----|--|
| Silica, crystalline 14808-60-7 1317-95-9 14464-46-1 | Crystallized silicon dioxide, Cristobalite, α -Quartz, Silica, Tripoli | TWA=0.025 mg/m ³ (respirable fraction) | N95 | |
| Silica, crystalline- tridymite 15468-32-3 | | TWA=0.05 mg/m ³ (OSHA, respirable fraction) | N95 | Assuming 100% SiO ₂ (5 mg/m ³ divided by %SiO ₂) |
| Silicon 7440-21-3 | | TWA=15 mg/m ³ (OSHA) TWA=5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Silicon carbide (fibrous) 409-21-2 | | TWA= 0.1 f/cc (respirable fibers) | N95 | |
| Silicon carbide (nonfibrous particles with no asbestos and <1% crystalline silica) 409-21-2 | | TWA= 10 mg/m ³ (inhalable fraction) TWA=3 mg/m ³ (respirable fraction) | N95 | |
| Silicon tetrahydride 7803-62-5 | Silane | TWA=5 | SA | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|---|--|--|
| Silver, metal and soluble compounds (as Ag) 7440-22-4 | | | TWA=0.01 mg/m ³ (OSHA) | N95 | |
| Soapstone (particles with no asbestos and <1% crystalline silica) | Massive talc, Soapstone silicate, Steatite | | TWA=2 mg/m ³ (respirable fraction) | N95 | |
| Sodium azide as hydrazoic acid vapor 26628-22-8 | Hydrazoic acid vapor | | C=0.11 | SA | Unknown sorbent effectiveness |
| Sodium azide as sodium azide 26628-22-8 | Hydrazoic acid (no vapor) | | C=0.29 mg/m ³ | N95 | |
| Sodium bisulfite 7631-90-5 | Sodium hydrogen sulfite | | TWA=5 mg/m ³ | AG/N95 | N95 alone may be suitable if irritation eliminated |
| Sodium borate, anhydrous 1330-43-4 | Borates, tetrasodium salts, anhydrous; Borax fused; Boric acid, disodium salt; Disodium tetraborate; Sodium tetraborate, anhydrous | | TWA=2 mg/m ³ (inhalable fraction) STEL=6 mg/m ³ (inhalable fraction) | N95 | |

| | | | | |
|---|---|-----------------------|---|-----|
| Sodium borate, decahydrate 1303-96-4 | Borascu; Borates, tetrasodium salts, decahydrate; Borax; Borocin; Disodium diborate decahydrate; Disodium tetraborate decahydrate; Sodium pyroborate decahydrate; Sodium tetraborate, decahydrate | | TWA=2 mg/m ³ (inhalable fraction) STEL=6 mg/m ³ (inhalable fraction) | N95 |
| Sodium borate, pentahydrate 12179-04-3 | Borates, tetrasodium salts, pentahydrate; Boric acid, pentahydrate; Boron sodium oxide, pentahydrate; Mule team borascu; Sodium tetraborate pentahydrate | | TWA=2 mg/m ³ (inhalable fraction) STEL=6 mg/m ³ (inhalable fraction) | N95 |
| Sodium chloroacetate 3926-62-3 | Chloroacetic acid, sodium salt; Monoxone; Sodium monochloroacetate | | TWA=2.5 mg/m ³ (AIHA) | N95 |
| Sodium fluoroacetate 62-74-8 | 1080, SFA, Sodium monofluoroacetate | 5 mg/m ³ | TWA=0.05 mg/m ³ -skin- | N95 |
| Sodium hydroxide 1310-73-2 | Caustic soda, Lye, Soda lye | 250 mg/m ³ | C=2 mg/m ³ | N95 |
| Sodium hypochlorite 7681-52-9 | Hypochlorous acid, sodium salt; Sodium oxychloride | | STEL= 2 mg/m ³ (AIHA) | N95 |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|----------------------------|--|--|--|
| Sodium metabisulfite 7681-57-4 | Sodium pyrosulfite | | TWA=5 mg/m ³ | AG/N95 | N95 alone may be suitable if irritation eliminated |
| Starch 9005-25-8 | Corn starch | | TWA=10 mg/m ³ TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Stearates 646-29-7; 557-05-1; 557-04-0; 57-11-4; 822-16-2 | Aluminium stearate, Calcium stearate, Glyceryl stearate, Lithium stearate, magnesium stearate, Potassium stearate, Sodium stearate, Stearic acid, Zinc stearate | | TWA=10 mg/m ³ (inhalable fraction) TWA=3 mg/m ³ (respirable fraction) | N95 | |
| Stibine 7803-52-3 | Antimony trihydride, Hydrogen antimonide | 40 | TWA=0.1 | SA | Unknown sorbent effectiveness |
| Stoddard solvent 8052-41-3 | Dry cleaning safety solvent, Mineral spirits | 29500 mg/m ³ | TWA=100 | OV | 3M 3510 Monitor |
| Strontium chromate (as Cr) 7789-06-2 | C.I. pigment yellow 32, Strontium yellow | | TWA=0.0005 mg/m ³ | N95 | |

| | | | | | |
|---------------------------------------|---|----------------------|--|--------|---|
| Strychnine 57-24-9 | | 3 mg/m ³ | TWA=0.15 mg/m ³ | N95 | |
| Styrene 100-42-5 | Cinnamene, Phenylethylene, Styrene, Styrene monomer, Vinyl benzene | 5000 | TWA=20 STEL=40 | OV | 3M 3510 Monitor |
| Subtilisins 1395-21-7 9014-01-1 | Proteolytic enzymes as 100% crystalline enzyme | | C=0.00006 mg/m ³ | SA | Difficult to measure 10X OEL. N95 acceptable with suitable air sampling data |
| Sucrose 57-50-1 | Saccharose, Table sugar | | TWA=10 mg/m ³ TWA= 5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Sulfur dioxide 7446-09-5 | SO ₂ | 100 | STEL=0.25 | AG | Irritation and taste also provides warning |
| Sulfur hexafluoride 2551-62-4 | SF ₆ | | TWA=1000 | SA | Unknown sorbent effectiveness |
| Sulfuric acid 7664-93-9 | Hydrogen sulfate, Matting acid, Oil of vitriol, Sulphuric acid, Vitriol brown oil | 80 mg/m ³ | TWA=0.2 mg/m ³ (thoracic fraction) | (F)N95 | N95 acceptable with appropriate eye/face protection |
| Sulfur monochloride 10025-67-9 | Sulfur chloride, Sulfur subchloride | 10 | C=1 | (F)AG | |
| Sulfur pentafluoride 5714-22-7 | Disulfur decafluoride | 1 | C=0.01 | AG | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|--|--|-------------------------------|
| Sulfur tetrafluoride 7783-60-0 | | | C=0.1 | AG | |
| Sulfuryl fluoride 2699-79-8 | | 1000 | TWA=5 STEL=10 | SA | Unknown sorbent effectiveness |
| Synthetic vitreous fibers - Continuous filament glass fibers | Fibrous glass, dust; Glass, fibrous or dust | | TWA=5 mg/m ³ (inhalable fraction) TWA=1 f/cc (respirable fibers) | N95 | |
| Synthetic vitreous fibers - glass wool fibers | | | TWA=1 f/cc (respirable fibers) | N95 | |
| Synthetic vitreous fibers - refractory ceramic fibers | | | TWA=0.2 f/cc (respirable fibers) | N95 | |
| Synthetic vitreous fibers - rock wool fibers | Mineral (rock), wool fiber | | TWA=1 f/cc (respirable fibers) | N95 | |
| Synthetic vitreous fibers - slag wool fibers | | | TWA=1 f/cc (respirable fibers) | N95 | |

| | | | | | |
|--|--|---|---|-----|--|
| Synthetic vitreous fibers - special purpose glass fibers | | | TWA=1 f/cc (respirable fibers) | N95 | |
| Talc (containing no asbestos and <1% crystalline silica) 14807-96-6 | Hydrous magnesium silicate, Non-asbestiform talc, Non-fibrous talc, Steatite talc | | TWA=2 mg/m ³ (respirable fraction) | N95 | |
| Tantalum, metal and oxide dusts (as Ta) 7440-25-7 | | | TWA=5 mg/m ³ (OSHA) | N95 | |
| Tellurium and compounds (as Te, excluding hydrogen telluride) 13494-80-9 | | | TWA=0.1 mg/m ³ | N95 | |
| Tellurium hexafluoride (as Te) 7783-80-4 | | 1 | TWA=0.02 | SA | Unknown sorbent effectiveness |
| Terephthalic acid 100-21-0 | 1,4 Benzenedicarboxylic acids, Benzene-p-dicarboxylic acid, p-Phthalic acid, Tephthol, TPA | | TWA=10 mg/m ³ | N95 | |
| Terphenyls 26140-60-3 | Diphenyl benzenes, Mixed terphenyls, m-Terphenyl, o-Terphenyl, p-Terphenyl | | C=5 mg/m ³ | N95 | OV/N95 may be preferable if heat is involved |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|-----------------------|---|--|----------------------------|
| 1,1,2- Tetrabromoethane 79-27-6 | Acetylene tetrabromide, Muthmann's liquid, Tetrabromoethane, Tetrabromoethylene | 10 | TWA=0.1 (inhalable fraction and vapor) | OV/N95 | See comment E on page 8 |
| 1,1,1,2- Tetrachloro-2,2- difluoroethane 76-11-9 | 2,2-Difluoro-1,1,1,2- tetrachloroethane; Freon® 112a; Halocarbon 112a; Refrigerant 112a | 15000 | TWA=100 | OV | |
| 1,1,2,2-Tetrachloro- 1,2-difluoroethane 76-12-0 | Freon® 112, Halocarbon 112, Refrigerant 112 | 15000 | TWA=50 | OV | |
| 1,1,2,2- Tetrachloroethane 79-34-5 | Acetylene tetrachloride | 150 | TWA=1 -skin- | OV | 3M 3510 Monitor |
| Tetrachloro- naphthalene 1335-88-2 | Halowax™, Nibren wax, Seekay wax | | TWA=2 mg/m ³ | OV/N95 | See comment D on page 8 |
| 2,3,5,6- Tetrachloropyridine 2402-79-1 | Pyridine 2,3,5,6-tetrachloro- | | TWA=5 mg/m ³ (AIHA) | OV/N95 | See comment D on page 8 |

| | | | | | |
|--|--|----------------------|---|--------|--|
| Tetrachlorosilane 10026-04-7 | Silicon chloride, Silicon tetrachloride | | C=1 (AIHA) | AG/N95 | Reacts rapidly with moisture yielding HCl and silica |
| Tetraethylene glycol diacrylate 17831-71-9 | 2-Propionic acid, oxy-bis (2,1- ethane-dioxy-2,1- ethanediol) ester; TTEGDA | | TWA=1 mg/m ³ (AIHA) -skin- | OV/P95 | See comment D on page 8 |
| Tetraethylene pentamine 112-57-2 | 1,2-Ethanediamine, N-(2-aminoethyl)-N'-(2- ((2-aminoethyl)amino) ethyl); DEH 26; TEPA; Tetraethyl pentamine; Tetren 1,4,7,10,13-Pentaazatridecane | | TWA=5 mg/m ³ (AIHA) -skin- | (F)OV | |
| Tetraethyl lead (as Pb) 78-00-2 | Lead tetraethyl, TEL | 40 mg/m ³ | TWA=0.075 mg/m ³ (OSHA) -skin- | OV | |
| 1,1,1,2- Tetrafluoroethane 811-97-2 | Fluorocarbon 134a, HFA 134a, HFC 134a, Tetrafluoroethane | | TWA=1000 (AIHA) | SA | Ineffective sorbents |
| Tetrafluoroethylene 116-14-3 | 1,1,2,2-Tetrafluoroethylene; Fluoroplast 4; Perfluoroethene; Perfluoroethylene; Tetrafluoroethene; TFE | | TWA=2 | SA | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|-----------------------|------------------------------|--|-----------------|
| 2,3,3,3- Tetrafluoropropene 754-12-1 | | | TWA=500 (AIHA) | SA | |
| Tetrahydrofuran 109-99-9 | Diethylene oxide, Tetramethylene oxide, THF | 20000 | TWA=50 STEL=100 -skin- | OV | 3M 3510 Monitor |
| Tetrahydrofurfuryl alcohol 97-99-4 | Tetrahydro-2-furancarbinol, Tetrahydro-2-furanmethanol, Tetrahydro-2-furylmethanol, THFA | | TWA=0.5 (AIHA) | OV | |
| Tetrakis (hydroxymethyl) phosphonium chloride 124-64-1 | Proban CC, Pyroset TKC, Retardol C, Tetrahydroxymethyl phosphonium chloride, THPC | | TWA=2 mg/m ³ | N95 | |
| Tetrakis (hydroxymethyl) phosphonium sulfate 55566-30-8 | bis tetrakis-(hydroxymethyl) phosphonium sulfate, Octakis (hydroxymethyl) phosphonium sulfate, Pyroset TKO, Retardol S, THPS | | TWA=2 mg/m ³ | N95 | |

| | | | | |
|--|--|----------------------|---|-----|
| Tetramethyl lead (as Pb) 75-74-1 | Lead tetramethyl, TML | 40 mg/m ³ | TWA=0.075 mg/m ³ (OSHA) -skin- | OV |
| Tetramethyl succinonitrile, vapor 3333-52-6 | TMSN | 5 | TWA=0.5 -skin- | OV |
| Tetranitromethane 509-14-8 | Tetan | 5 | TWA=0.005 | OV |
| Tetryl 479-45-8 | 2,4,6- Trinitrophenylmethylnitramine, Nitramine, N-Methyl-N- 2,4,6-tetranitroaniline, Tetralite | | TWA=1.5 mg/m ³ | N95 |
| Thallium, elemental and soluble compounds (as Tl) 7440-28-0 | Thallium acetate, Thallium carbonate, Thallium hydroxide | 20 mg/m ³ | TWA=0.02 mg/m ³ (inhalable fraction) -skin- | N95 |
| 4,4'-Thiobis(6-tert- butyl-m-cresol) 96-69-5 | 4,4'-Thiobis(3-methyl-6-tert- butyl phenol) | | TWA=15 mg/m ³ (OSHA) TWA=1 mg/m ³ (inhalable fraction) TWA=5 mg/m ³ (OSHA, respirable fraction) | N95 |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|------------------------|---|--|----------------------------|
| Thioglycolic acid 68-11-1 | Mercaptoacetic acid, Thioranic acid | 59000 | TWA=1 -skin- | (F)OV | |
| Thionyl chloride 7719-09-7 | Sulfur oxychloride, Sulfurous oxychloride | | C=0.2 | (F)AG | |
| Thiram 137-26-8 | Tetramethylthioram disulfide, TMT, TMTD, TMTDS | 1500 mg/m ³ | TWA=0.05 mg/m ³ (inhalable fraction and vapor) | OV/N95 | See comment D on page 8 |
| Tin, metal and inorganic compounds (except SnH ₄) (as Sn) 7440-31-5 | | 400 mg/m ³ | TWA=2 mg/m ³ | N95 | |
| Tin, organic compounds (as Sn) | | | TWA=0.1 mg/m ³ STEL=0.2 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| Titanium dioxide 13463-67-7 | Anatase, Brookite, Rutile | | TWA=10 mg/m ³ | N95 | |
| Titanium tetrachloride 7550-45-0 | Titanium chloride | | TWA=0.5 mg/m ³ (AIHA) | AG/N95 | |

| | | | | | |
|--|---|------|---|------------------|---|
| Toluene 108-88-3 | Aantisal 1a, Methacide, Methyl benzene, Methylbenzol, Monomethyl benzene, Phenyl methane, Tol, Toluol, Tolu-sol | 2000 | TWA=20 C=300 (OSHA) | OV | 3M 3510 Monitor |
| Toluene diamine 25376-45-8 95-80-7 | Diaminotoluene, TDA, Tolyenediamine | | TWA=0.005 (AIHA) -skin- | N95 | |
| Toluene-2,6- diisocyanate 91-08-7 | 2,6-TDI, 2,6-Toluene diisocyanate | 10 | TWA=0.001 (inhalable fraction and vapor) STEL=0.005 (inhalable fraction and vapor) -skin- | OV/N95 | See comment E on page 8 |
| Toluene-2,4- diisocyanate 584-84-9 | 2,4-TDI, 2,4-Toluene diisocyanate | | TWA=0.001 (inhalable fraction and vapor) STEL=0.005 (inhalable fraction and vapor) -skin- | OV/N95 | See comment E on page 8 |
| p-Toluenesulfonyl chloride 98-59-9 | 4-Methyl-benzenesulfonyl chloride, Tosyl chloride | | C=5 mg/m ³ (AIHA) | (F)OV/AG/ N95 | See comment D on page 8. HCl and p-toluene sulfuric acid produced by hydrolysis |
| m-Toluidine 108-44-1 | m-Aminotoluene | | TWA=2 -skin- | (F)OV | |
| o-Toluidine 95-53-4 | 1-Methyl-1,2-aminobenzene; 2-Methylaniline; o-Aminotoluene; o-Methylaniline | 100 | TWA=2 -skin- | (F)OV | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|------------------------------------|---|-----------------------|---|--|-------------------------------------|
| p-Toluidine 106-49-0 | p-Aminotoluene, | | TWA=2 -skin- | (F)OV | |
| Tributyl phosphate 126-73-8 | TBP, Tri-n-butyl phosphate | 125 | TWA=5 mg/ m ³ (Inhalable fraction and vapor) | OV/P95 | See comment E on page 8 |
| Trichloroacetic acid 76-03-9 | TCA | | TWA=0.5 | (F)OV/AG | Irritation also provides warning |
| 1,2,4-Trichlorobenzene 120-82-1 | | 25000 | C=5 | OV | |
| 1,1,2-Trichloroethane 79-00-5 | b-Trichloroethane, Vinyl trichloride | 500 | TWA=10 -skin- | (F)OV | 3M 3510 Monitor |
| Trichloroethylene 79-01-6 | 1,1,2-TCE, 1-Chloro-2,2- dichloroethylene, Ethylene trichloride, TCE, Triclene™ | 1000 | TWA=10 STEL=25 C=200 (OSHA) | OV | 3M 3510 Monitor |
| Trichlorofluoromethane 75-69-4 | CFC-11, Fluorotrichloromethane, Freon™ 11, Refrigerant 11, Trichloromonofluoromethane | 10000 | TWA=1000 (OSHA) C=1000 | SA | Short OV service life |

| | | | | | |
|--|--|------|-----------------------------------|--------|---|
| Trichloronaphthalene 1321-65-9 | Halowax™, Nibren wax, Seekay wax | | TWA=5 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| 1,2,3-Trichloropropane 96-18-4 | Allyl trichloride, Glycerin trichlorohydrin, Glycerol trichlorohydrin, Trichlorohydrin | 1000 | TWA=0.005 -skin- | (F)OV | |
| Trichlorosilane 10025-78-2 | Silicochloroform | | C=0.5 (AIHA) | (F)AG | |
| 1,1,2-Trichloro-1,2,2- trifluoroethane 76-13-1 | FC-113, Freon® 113, Halocarbon 113, Refrigerant 113, TTE | 4500 | TWA=1000 STEL=1250 | SA | Short OV service life. 3M 3530 Monitor |
| Triethanolamine 102-71-6 | 2,2,2-Nitrioltriethanol, Daltogen, Sterolamide, TEA, Trihydroxytriethylamine | | TWA=5 mg/m ³ | OV/P95 | See comment D on page 8 |
| Triethoxysilane 998-30-1 | Silane, triethoxy- | | TWA=0.05 (AIHA) | (F)SA | Unknown sorbent effectiveness |
| Triethylamine 121-44-8 | N,N-Diethylanamine, N-Triethylamine, TEA | 1000 | TWA=0.5 STEL=1 | (F)OV | AM not specifically approved, but 3M recommended for longer service life |
| Triethylene glycol diacrylate 1680-21-3 | 2-Propenoic acid, 2-ethanediybis-(oxy-2,1- ethanediy) ester; TREGDA | | TWA=1 mg/m ³ (AIHA) | OV/P95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|---|-----------------------|--------------------------------------|--|--|
| Triethylenetetramine 112-24-3 | 1,4,7,10-Tetraazadecane; 1,8-Diamino-3,6-diazaoctane; 3,6-Diazaoctane-1,8-diamine; N, N'-bis(2-aminoethyl)-1,2,ethane diamine; TECZA; TETA, Trientine | | TWA=1 (AIHA) -skin- | OV | See comment E on page 8. R or P filter, if filter required |
| Triethylphosphate 78-40-0 | Phosphoric acid triethyl ester | 17000 | TWA=7.45 mg/m ³ (AIHA) | OV/P95 | |
| Trifluorobromo- methane 75-63-8 | Bromotrifluoromethane, Freon® 13B1, Halocarbon 13B1, Halon™ 1301, Refrigerant 13B1 | 50000 | TWA=1000 | SA | Short OV service life |
| 1,1,1-Trifluoro-2,2- dichloroethane 306-83-2 | FC-123, HCFC-123, Hydrofluorocarbon 123 | | TWA=50 (AIHA) | SA | Short OV service life |
| 1,1,1-Trifluoroethane 420-46-2 | FC-143a, HFC-143a, Hydrofluorocarbon 143a | | TWA=1000 (AIHA) | SA | Ineffective sorbents |
| 2,2,2-Trifluoroethanol 75-89-8 | 2,2,2-Trifluoroethyl alcohol; Ethanol, 2,2,2,-Trifluoro; TFE | 55000 | TWA=0.3 (AIHA) | SA | Ineffective sorbents |
| 1,3,5-Triglycidyl-s- triazinetriene 2451-62-9 | 1,3,5-Triazine-2,4,6-(1H,3H,5H)- trione, Araldite PT-810, TEPIC | | TWA=0.05 mg/m ³ | N95 | |

| | | | | | |
|--|--|-------|--|----------|---|
| Trimellitic anhydride 552-30-7 | Anhydrotrimellitic acid, TMA, TMAN, Trimellitic acid anhydride | | TWA=0.0005 mg/m ³ (inhalable fraction and vapor) STEL=0.002 mg/m ³ (inhalable fraction and vapor) | OV/N95 | Chemical manufacturer's recommendation. See comment D on page 8 |
| Trimethoxysilane 2487-90-3 | | | TWA=0.05 (AIHA) | (F)OV | |
| Trimethylamine 75-50-3 | N,N-Dimethyl methanamine, N-Trimethylamine, TMA | 20000 | TWA=1 (AIHA) STEL=15 | (F)AM | AIHA WEEL is lower than TLV of 5 ppm. AM not specifically approved |
| Trimethyl benzene 25551-13-7 | Hemimellitene, Mesitylene, Pseudocumene | 8000 | TWA=25 | OV | 3M 3510 Monitor |
| Trimethylchlorosilane 75-77-4 | Chlorotrimethylsilane, Monochlorotrimethylsilicon, Trimethyl chlorosilane | | C=5 (AIHA) | (F)OV/AG | |
| Trimethyl phosphite 121-45-9 | Methyl phosphite, Phosphorus acid trimethylester | | TWA=2 | (F)OV | |
| Trimethylolpropane triacrylate 15625-89-5 | 2-Propenoic acid, 2-ethyl-2(((1- oxo-2-propenyl) oxy) methyl)- 1,3-propanediyl ester | | TWA=1 mg/m ³ (AIHA) | OV/P95 | |
| Trimethylolpropane trimethacrylate 3290-92-4 | Acrylic acid, triester w/2-ethyl 2 (hydroxymethyl) 1,3 propanediol | | TWA=1 mg/m ³ (AIHA) | OV/P95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|---|--|------------------------|---|--|---|
| 2,4,6-Trinitrotoluene (TNT) 118-96-7 | sym-Trinitrotoluene, TNT, Trinitrotoluene, Trinitrotoluol | 1000 mg/m ³ | TWA=0.1 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| Triorthocresyl phosphate 78-30-8 | o-Trityl phosphate, TCP, TOCP, Tricresylphosphate | 40 mg/m ³ | TWA=0.02 mg/m ³ (inhalable fraction and vapor) -skin- | R95 P95 | See comment D on page 8 |
| Triphenyl phosphate 115-86-6 | Phenyl phosphate, TPP | | TWA=3 mg/m ³ | N95 | OV/N95 may be preferable if heat is involved |
| Trisodium phosphate 7601-54-9 | Sodium o-phosphate, TSP | | STEL=5 mg/m ³ (AIHA) | (F)N95 | N95 acceptable with appropriate eye/face protection |
| Tungsten and compounds, the absence of cobalt 7440-33-7 | | | TWA=3 mg/m ³ (respirable particulate matter) | N95 | |

| | | | | | |
|---|---|----------------------|--|-------|--|
| Turpentine 8006-64-2 | Gum spirits, Gum turpentine, Turps, Wood turpentine | 1500 | TWA=20 | (F)OV | See comment E on page 8 |
| Uranium, insoluble compounds (as U) 7440-61-1 | | 30 mg/m ³ | TWA=0.2 mg/m ³ STEL=0.6 mg/m ³ | N95 | See 10 CFR 20 subpart H |
| Uranium, soluble compounds (as U) 7440-61-1 | | 20 mg/m ³ | TWA=0.05 mg/m ³ (OSHA) | N95 | AG/N95 if halides. See 10 CFR 20 subpart H |
| Urea 57-13-6 | Carbamide, Carbonyldiamide, Carbonyldiamine, Isourea | | TWA=10 mg/m ³ (AIHA) | N95 | AM/N95 may be preferable if heat is involved |
| n-Valeraldehyde 110-62-3 | Pentanal, Valeric aldehyde | | TWA=50 | (F)OV | |
| Vanadium pentoxide 1314-62-1 | Vanadic anhydride, Vanadium oxide | 70 mg/m ³ | TWA= 0.05 mg/m ³ (inhalable fraction) C=0.5 mg/m ³ (OSHA, respirable fraction) | N95 | |
| Vanadium pentoxide fume 1314-62-1 | | 70 mg/m ³ | TWA=0.05 mg/m ³ (inhalable fraction) C=0.1 mg/m ³ (OSHA) | N95 | |
| Vanillin 121-33-5 | Vanilla, Vanillaldehyde, Vanillic aldehyde | | TWA=10 mg/m ³ (AIHA) | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|---|-----------------------|--|--|---|
| Vegetable oil | | | TWA=15 mg/m ³ (OSHA) TWA= 5 mg/m ³ (OSHA, respirable fraction) | R95 P95 | |
| Vinyl acetate 108-05-4 | 1-Acetoxyethylene, Ethenyl acetate | 26000 | TWA=10 STEL=15 | (F)OV | 3M 3510 Monitor |
| Vinyl bromide 593-60-2 | Bromoethylene | | TWA=0.5 | (F)SA | Short OV service life |
| Vinyl Chloride 75-01-4 | Chloroethene, Chloroethylene, Monochloroethylene, VC, VCM, Vinyl chloride monomer | 36000 | TWA=1 STEL=5 (OSHA) | SA | OSHA allows OV for very short use periods. See 29 CFR 1910.1017 |
| 4-Vinylcyclohexene 100-40-3 | 1-Vinylcyclohexene-3, 4-Ethenyl-1-1-cyclohexene, 4-Vinyl-1-cyclohexene, 4-Vinylcyclohex-1-ene, 4-Vinylcyclohexene, 4-Vinylcyclohexene-1- butadiene dimer, VCH | | TWA=0.1 | OV | |
| Vinyl cyclohexene dioxide 106-87-6 | Vinylcyclohexane dioxide | | TWA=0.1 -skin- | (F)OV | |

| | | | | | |
|--|--|-------|---|-------|---|
| Vinyl fluoride 75-02-5 | Fluoroethene, Fluoroethylene, Monofluoroethylene | 26000 | TWA=1 | SA | Short OV service life |
| Vinylidene chloride 75-35-4 | 1,1-Dichloroethylene, VDC | 65000 | TWA=5 | OV | Short service life |
| Vinylidene fluoride 75-38-7 | 1,1-Difluoroethene; 1,1-Difluoroethylene; Ethene, 1,1-difluoro; Ethylene,1,1-difluoro; Halocarbon 1132A; VDF; Vinylidene difluoride | 55000 | TWA=500 | SA | Ineffective sorbents |
| N-Vinyl-2-pyrrolidone 88-12-0 | 1-Ethenyl-2-pyrrolidinone, 1-Vinylpyrrolidinone, N-Vinylpyrrolidinone, Vinylbutylactam, Vinylpyrrolidinone, Vinylpyrrolidone | | TWA=0.05 | OV | |
| Vinyl toluene 25013-15-4 | Methyl styrene, Tolyethylene | 5000 | TWA=50 STEL=100 | (F)OV | See comment E on page 8. 3M 3510 Monitor. |
| Vinyltrichlorosilane 75-94-5 | Silane trichloroethenyl, Silane trichlorovinyl, Trichlorovinyl silicane, Trichlorovinylsilane, Trichlorovinylsilicon, Vinylsilicon trichloride | | C=1 (AIHA) | OV/AG | |
| Wood dust (All varieties except western red cedar) | | | TWA=1 mg/m ³ (inhalable fraction) | N95 | |

| Chemical Name CAS # | Synonym | IDLH (ppm) | OEL (ppm) | Respirator (Exposures < both APF x OEL and IDLH) | Comments |
|--|--|------------------------|---|--|----------------------------|
| Wood dust (Western red cedar) | | | TWA=0.5 mg/m ³ (inhalable fraction) | N95 | |
| Xylene (o-, m-, p- isomers) 1330-20-7 95-47-6 108-38-3 106-42-3 | Dimethylbenzene (o-, m-, p-isomers), 1,2-Dimethylbenzene, 1,3-Dimethylbenzene, 1,4-Dimethylbenzene | 1000 | TWA=100 STEL=150 | OV | 3M 3510 Monitor |
| m-Xylene a,a'-diamine 1477-55-0 | MXDA | | C=0.1 mg/m ³ -skin- | OV/N95 | See comment D on page 8 |
| Xylidine 1300-73-8 | Aminodimethyl benzene, Aminoxylene dimethyl aniline, Dimethylaminobenzene | 150 | TWA=0.5 (inhalable fraction and vapor) -skin- | OV/N95 | See comment E on page 8 |
| Yttrium, metal and compounds (as Y) 7440-65-5 | | | TWA=1 mg/m ³ | N95 | |
| Zinc chloride fume 7646-85-7 | | 4800 mg/m ³ | TWA=1 mg/m ³ STEL=2 mg/m ³ | N95 | |

| | | | | |
|--|---|------------------------|--|-----|
| Zinc chromate (as Cr) 13530-65-9 11103-86-9 37300-23-5 | Basic zinc chromate, Chromates of zinc, Zinc potassium chromate, Zinc yellow | | TWA=0.01 mg/m ³ | N95 |
| Zinc oxide 1314-13-2 | Zinc white, Zincite | 2500 mg/m ³ | TWA=15 mg/m ³ (OSHA) TWA=2 mg/m ³ (respirable fraction) STEL=10 mg/m ³ (respirable fraction) | N95 |
| Zirconium and compounds (as Zr) 7440-67-7 | | 500 mg/m ³ | TWA=5 mg/m ³ STEL=10 mg/m ³ | N95 |

Respirator Codes and Descriptions

| | |
|------|--|
| (F) | Full Facepiece (with appropriate cartridges and filters) |
| AG | Acid Gas Respirator |
| AM | Ammonia/Methylamine Respirator |
| FORM | Formaldehyde Respirator |
| HF | Hydrogen Fluoride Respirator |
| Hg | Mercury Vapor Respirator |
| MG | Multi-gas/Vapor Respirator |
| N100 | N100 Particulate Respirator |
| N95 | N95 Particulate Respirator |
| OV | Organic Vapor Respirator |
| OZ | Ozone Respirator |

| | |
|-------|--|
| P100 | P100 Particulate Respirator |
| P95 | P95 Particulate Respirator |
| R95 | R95 Particulate Respirator |
| SA | Supplied Air Respirator |
| SA(F) | Supplied air respirator with full facepiece, helmet, hood or loose fitting facepiece, or half half facepiece with appropriate eye protection |

Note: Respirator abbreviations may be combined. For example, (F)OV/AG/P95 is a full facepiece respirator with an organic vapor/acid gas cartridge and a P95 particulate filter.

HEPA filters are used for PAPRs instead of N, R, P type particle filters.

3M™ Select and Service Life Software helps you select the most appropriate respirator or estimate service life of 3M gas/vapor cartridges.