



# **3M<sup>™</sup> Water Activated Tape Systems:**

# Simplicity. Security. Value.

Easy handling...

# **3M<sup>™</sup> Water Activated Tapes**

Simplify your packing operations with a proven solution. 3M™ Water Activated Tapes are an easy, economical answer to a wide variety of basic carton sealing challenges.

- Moistened adhesive interacts with porous surfaces to form a powerful, secure bond
- Tape forms a tamper-evident seal that shreds if an attempt is made to pull it off before delivery
- Paper construction is easy to handle, making it ideal for hand applications
- Boxes are sealed secure, yet easy to open without cutting tools
- Coreless rolls reduce waste and simplify roll changes

# **Key Product Features**

| Non-Reinforced |             | Fiberglass Reinforced |                    |
|----------------|-------------|-----------------------|--------------------|
| 6141           | Light Duty  | 6144                  | Up to 25 lb. Boxes |
| 6142           | Medium Duty | 6145                  | Up to 30 lb. Boxes |
| 6143           | Heavy Duty  | 6146                  | Up to 35 lb. Boxes |
|                |             | 6147                  | Up to 40 lb. Boxes |





# ...easy dispensing.

#### **3M<sup>™</sup> Water Activated Tape Dispensers**

With both electric and manual dispensers, you can choose the unit that best fits your carton sealing needs. Both dispensers have an extra large water bottle for fewer refills and greater productivity. Both can dispense tapes from 1 to 3 inches in width.

#### 3M<sup>™</sup> Electric Water Activated Dispenser W200

- Dispenses up to 45" of water activated tape at the push of a button
- Secondary shift push button extends the range up to 90" of tape
- Heated water reservoir speeds tape activation and improves adhesion in cooler packaging areas

#### 3M<sup>™</sup> Manual Water Activated Dispenser W100

- Manual lever dispenses tape up to 36" in length
- 12-gauge, all-metal base construction ensures long-term durability



Choose from either electric or manual dispensing systems.



### From 3M, a world leader in tape and adhesive technology

With 45 technology platforms and a culture of continuous innovation, 3M is known around the world for creating practical and ingenious solutions for almost every sphere of life.



#### February, 2011

# 3M™ Heavy Duty Water Activated Paper Tape 6143

#### **Product Description**

3M™ Heavy Duty Water Activated Paper Tape 6143 is used for box sealing and other packaging applications. This product has a paper backing and a gummed, high tack, water- activated, modified cornstarch based adhesive system.

#### **Product Features**

- Recommended for sealing medium weight corrugated boxes.
- Used for two C clips on cartons top and bottom.
- Works well on recycled cartons and non-unitized loads.
- Construction assures a reliable performance in a range of environments and applications.
- Tape available in kraft only.



# 3M<sup>™</sup> Heavy Duty Water Activated Paper Tape 6143

#### **Technical Information Note**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

#### **Typical Physical Properties**

| Property      | Values     |         | Method     | Test Condition    |
|---------------|------------|---------|------------|-------------------|
| Caliper       | 0.19 mm    | 7.5 mil | ASTM D645  |                   |
| Basis Weight  | 90 lb/ream |         | ASTM D646  |                   |
| Tear Strength | 200 g      |         | ASTM D1922 | Machine Direction |
| Tear Strength | 225 g      |         | ASTM D1922 | Cross Direction   |

# **Typical Performance Characteristics**

| Property         | Values       |          | Method     |
|------------------|--------------|----------|------------|
| Tensile Strength | 1016 N/100mm | 58 lb/in | ASTM D5803 |

#### **Available Sizes**

| Property             | Values            |        |
|----------------------|-------------------|--------|
| Standard Roll Length | 114.3 m           | 375 ft |
| Standard Width       | 76.2 mm           | 3.0 in |
| Packaging            | 10 rolls per case |        |

#### Handling/Application Information

#### **Application Techniques**

Semi-automatic application equipment is available. Application most easily accomplished at room temperature. Once applied, the tape performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

#### Storage and Shelf Life

To obtain best performance, use this product within 12 months from date of manufacture.

#### **Trademarks**

3M is a trademark of 3M Company.

#### **ISO Statement**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

#### **Technical Information**

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

#### **Product Selection and Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

#### Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

#### **Limitation of Liability**

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.