

#### June, 2010

# 3M<sup>™</sup> Preservation Sealing Tape 4811

#### **Product Description**

3M<sup>™</sup> Preservation Sealing Tape 4811 is a white polyethylene backing with a unique rubber adhesive that provides excellent performance as an industrial preservation tape.

#### **Product Features**

- Effective for many outdoor applications in hot and cold weather over one year with quick, clean removal.
- Can be applied from freezing to 120°F (49°C), removed at 0°F (-18°C).
- May be easily dispensed from a hand dispenser.
- White polyethylene backing provides good conformability for many irregular surfaces.
- Blends well with white film covering for a clean, professional and attractive appearance.



## **Technical Information Note**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

# **Typical Physical Properties**

| Property                         | Values         |         | Method     |
|----------------------------------|----------------|---------|------------|
| Color                            | White          |         |            |
| Total Tape Thickness             | 0.24 mm        | 9.5 mil | ASTM D3652 |
| Backing Thickness                | 0.18 mm        | 7.5 mil | ASTM D3652 |
| Backing                          | Polyethylene   |         |            |
| Adhesive                         | Rubber         |         |            |
| Water Vapor<br>Transmission Rate | 1.3 g/m²/24 hr |         | ASTM D3833 |

# **Typical Performance Characteristics**

| Property                 | Values      |              | Method     | Substrate       |
|--------------------------|-------------|--------------|------------|-----------------|
| Peel Adhesion            | 3.6 N/cm    | 30 oz/in     | ASTM D3330 | Stainless Steel |
| Tensile Strength         | 26.3 N/cm   | 240 oz/in    | ASTM D3759 |                 |
| Elongation at Break      | 490 %       |              | ASTM D3759 |                 |
| Temperature Use<br>Range | Up to 77 °C | Up to 170 °F |            |                 |

#### **Available Sizes**

| Property             | Values |       |
|----------------------|--------|-------|
| Standard Roll Length | 33 m   | 36 yd |

# Handling/Application Information

## **Application Ideas**

Seals and protects various types of industrial and military equipment in shipment and storage.

## Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton. To obtain best performance, use this product within 18 months from date of manufacture.

#### 3M<sup>™</sup> Preservation Sealing Tape 4811

#### Information

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.