

3M Science.
Applied to Life.™



Mil Spec MIL-STD-2041E
Compliant


Our best performing duct tape under the sun.

3M™ Performance Plus Duct Tape 8979/8979N




3M™ Performance Plus Duct Tape 8979/8979N takes high performance outdoors into the sun and cleanly off the surface.


- Removes cleanly for up to six months from most opaque surfaces even after exposure to sunlight and temperature extremes
- Stays on for up to one year without deterioration even outdoors
- Aggressive adhesive for quick and reliable attachment
- High tensile strength for demanding applications
- Strong water-resistant backing resists wear, abrasion, moisture and weathering
- Easy to tear straight across and down without curling for ease of application
- Saves time of removing sticky residue
- 8979N meets Military Compliance MIL-STD-2041E



Masking Access Holes



Outdoor Holding



Hanging Poly



3M™ Performance Plus Duct Tape 8979 holds up to weathering exposure and removes cleanly.



Product	3M UPC	Size	Color	Rolls/Cs
8979	048011-53922-5	24mm x 54.8m	● Slate Blue	48
	● 021200-56468-0	48mm x 54.8m		24
	021200-56469-7	72mm x 54.8m		12
	021200-56470-3	96mm x 54.8m		12
	048011-58183-5	144mm x 54.8m		6
	048011-58120-1	12" x 60 yds		2
	● 048011-53851-8	48mm x 22.8m	12	
	● 048011-53916-4	48mm x 54.8m	● Olive	24
● 048011-53918-8	48mm x 54.8m	● Black	24	
Nuclear Grade				
8979N	048011-58130-9	24mm x 54.8m	● Red	48
	048011-53914-0	48mm x 54.8m		24
	048011-53915-7	72mm x 54.8m		12
	021200-74327-6	48mm x 54.8m	● Slate Blue	24
	021200-74328-3	72mm x 54.8m		12
	048011-58185-9	144mm x 54.8m		6

● = Each roll is individually wrapped and marked with UPC Number.

Typical Physical Properties	
Adhesion to Steel	57 oz/in (6.2 N/cm)
Tensile Strength	36 lbs/in (63 N/cm)
Elongation at Break	17%
Tape Thickness	11.5 mil (0.29mm)
Temp Use Range	Up to 200°F (93°C)
Application Temperature	40–120°F (4–49°C)
Clean Removal Outdoors	Up to 6 months
Leachable Halogens (Cl, FL, Br)	8979N: <30 ppm total
Leachable Sulfur	8979N: <50 ppm
Backing	Polyethylene film over cloth scrim
Adhesive	Natural and synthetic rubber
References	8979: UL723/ASTM E84 8979N: ASME NQA-1, MIL-STD-2041E

Note: Data should be considered representative or typical only, and should not be used for specification purposes.

Looking for dependable tapes? Rely on 3M for quality and long-lasting products.