

Portable Mancoolers

Direct Drive Models 115V



4-IN-1 Fan

Features/Specifications:

- 2 year warranty
- Tilttable
- One fan, four mounting options
- All mountings in one box
- Easy to assemble
- Guards, Barrel, Mountings epoxy coated
- Pull Chain Switch



Performance:

Prop Dia.	Fan Style	CFM	RPM	F.L. Amps
30"	4-IN-1 All Mounts	5670 / 4590 / 3410	1110 / 810 / 600	2.9 / 2.1 / 1.93
36"	4-IN-1 All Mounts	11200 / 8090	830 / 600	4.6 / 3.5

Information:

EDP #	Catalog No.	Prop Dia.	Fan Style	HP	Ship Wt.
60470	DD3041	30"	4-IN-1 All Mounts	1/4	97
60471	DD3641	36"	4-IN-1 All Mounts	1/2	119

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

24" Mancooler

Features/Specifications:

- 2 year warranty
- Tilttable
- Ball bearing motor
- Two speed rocker switch
- Epoxy coated barrel
- Epoxy coated steel spiral resilient mounted guards
- Handle with cord wrap for 10' cord with three prong plug
- 1/4 HP, 1 Phase, Totally Enclosed Air Over



Information:

EDP #	Catalog No.	Prop Dia.	Fan Style	HP	CFM High Low	RPM High Low	Amps	Ship Wt.
70001	DDMC24C	24"	Portable Barrel	1/4	4000 / 2100	1100 / 800	3.5	75

Portable Mancoolers® - 115V

Direct Drive Models

4 - IN - 1® Fans



Vertical Mount



Hanging Mount



Portable Barrel



Wall Mount

2 Year Warranty - Affordable Versatility

Features

- 115V, 3 Speed, ¼ HP (30") & ½ HP (36") Totally Enclosed Air Over Motor
- A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions
- 36" 4-IN-1 Mancooler® is over sized, additional UPS Large Package Surcharges Apply
- Guards, Barrel, Mountings Epoxy Coated
- One Fan - Four Mounting Options
- All Mountings In One Box
- Easy to Assemble
- Pull Chain Switch
- Versatile
- Tilttable



EDP No.	Catalog No.	Prop Dia.	HP	CFM			RPM			F.L. Amps			Ship Wt.
				High	Med	Low	High	Med	Low	High	Med	Low	
60470	DD3041	30"	1/4	5670	4590	3410	1110	810	600	2.9	2.1	1.93	97
60471	DD3641	36"	1/2	11200	---	8090	830	---	600	4.6	---	3.5	119

24" Mancooler®



2 Year Warranty

Features

- 115V, 1/4 HP, 1 Phase, TEAO Ball Bearing Motor
- Handle with Cord Wrap for 10' Cord with Three Prong Plug
- Epoxy Coated Steel Spiral Resilient Mounted Guards
- Two Speed Rocker Switch
- Epoxy Coated Barrel
- Tilttable

EDP No.	Catalog No.	Prop Dia.	HP	CFM		RPM		Amps	Ship Wt.
				High	Low	High	Low		
70001	DDMC24C	24"	1/4	4000	2100	1100	800	3.5	75