



Model # 1832


**ONYX
1/2" NANO ANGLE
IMPACT WRENCH
- 415FT/LB**

EXTREME LOW PROFILE

**SINGLE OVERSIZED
HAMMER DESIGN**

**AS LONG AS A CREDIT
CARD AT 3.46" LONG**

**EXTENDED RIGHT
ANGLE GRIP**



3.46 in.



Model	Square Drive	Handle Type	Clutch type	Motor Housing	Air Exhaust
1832	1/2"	Straight right angle	Oversized Hammer	Aluminum w/ bed liner finish	360° Swivel Air Muffler
Air Inlet Thread	Switch	Max Torque	Working Torque	Weight	Length (from end to end)
1/4" NPT	3-speeds in both F and R	415 ft/lbs	300 ft/lbs	2.78 lbs	3.46"
Height (from end to end)	Free Speed	Noise Level (sound pressure)	Average Air Consumption	Min. Hose Size	
10.4"	9000 r.p.m.	85 dB	4.2 CFM	3/8"	

**INDUSTRY LEADING 415 FT/LBS. OF MAX TORQUE
ACCESS CONFINED BOLTS REMOTELY WITH
EXTENDED RIGHT ANGLE DESIGN**

**Astro Pneumatic
Tool Company**



AIR TOOLS

SHOP EQUIPMENT HAND TOOLS UNDERCAR KIT HYDRAULICS





Astro

MODEL NO. **1832**
1/2" NANO ANGLE
IMPACT WRENCH
- 415FT/LB



MODEL NO. **1838**
3/8" NANO ANGLE
IMPACT WRENCH
- 415FT/LB



- ✔ As long as a credit card at 3.46" long
- ✔ Industry leading 415 ft/lbs. of MAX torque
- ✔ Access confined bolts remotely with extended right angle design

SPECIFICATIONS

Air Inlet Thread: 1/4" NPT
 Weight: 2.78 lbs
 Max Torque: 415 ft/lbs
 Working Torque: 300 ft/lbs

Free Speed: 9000 r.p.m.
 Noise Level(sound pressure): 85 dB
 Average Air Consumption: 4.2 CFM
 Min. Hose Size: 3/8"

Length (from end to end): 3.46"
 Height (from end to end): 10.4"



Learn more about air impact wrenches we have.