

## Automotive Tools & Equipment for the Professional Technician



## Air Operated High-Pressure Grease Pump for 120 lbs. Drum



## Features:

- 50:1 heavy-duty double acting pump provides uniform high-pressure
- Upgraded pump seals provide 10-12 times longer life
- Will dispense 40 oz. of NLGI 0-2 grease per min. @ 150 psi
- Assures positive prime at lowest temperature
- All ATD Grease Pumps are factory tested for quality & reliability

## Includes:

- Roll-a-round base
- Follower plate (ATD-5325)
- · Air motor cover
- Lincoln-style air coupler
- Control valve (ATD-5218)
- Steel drum cover with screw downs

- 6 ft. high-pressure hose and pump muffler
- Grease strainer screen (ATD-5356)
- Barrel not included
- Package Dimensions: 39" x 19" x 8"
- Shipping Weight: 46 lbs.

Available Accessories & Replacement Parts:

ATD-5217-1 - 50:1 Double Acting Grease Replacement Pump for 120 lbs. Drum Systems

- Includes rapid disconnect air coupler, air nipple and muffler (fits all makes and models)
- Downtube Diameter: 1"
- Output: 80 cu.in/min. of NLGI #2 grease at 100 psi @ 70 degree(s)F ambient temperature (.35 cu. in.-cycle)
- Air Inlet: 1/8" NPT(f)
  Lube Outlet: 1/4" NPT(f)
  Shipping Weight: 17 lbs.

ATD-5324 - Piston Assembly

• Piston assembly for lower down tube on all air operated grease pumps

ATD-5325-2 - Rubber Follower Plate 120 lbs. Drum

- Molded Rubber for 120 lbs. drum pump
- Diameter opening for down tube 1"

ATD-5320 - Grease Pump Repair Kit

• Simple repair kit for grease pumps

ATD-5322 - Air Motor Repair Kit

• Complete repair kit for air motors

ATD-5323 - Downtube Repair Kit

Complete repair kit for downtubes