

Automotive Tools & Equipment for the Professional Technician



50:1 Grease Pump Assembly for 120 lbs. Drum



Features:

Will dispense 40 oz. of NLGI 0-2 grease per minute @ 150 psi. Hand truck provides convenient transportation for unit and has (2) semi-pneumatic disc wheels and a locking, screw-type clamp. DRUM NOT INCLUDED.

Includes:

- 50:1 double acting barrel pump
- 6 ft. high-pressure grease delivery hose
- Grease control valve
- Rapid disconnect air coupler
- Air nipple
- Muffler
- Follower plate (ATD-5325) with outer rubber wiping ring on the drum and inner rubber wiping ring on the pump tube
- Solid 1 piece hand truck and drum cover
- Output: 80 cu.in./min. of NLGI #2 grease at 100 psi @ 70 degree(s) F ambient temperature (.35 cu. in./cycle)

Air Inlet: 1/8" NPT(f)
Lube Outlet: 1/4" NPT(f)
Shipping Weight: 55 lbs.

Available Accessories & Replacement Parts
ATD-5217-1 - 50:1 Double Acting Grease Replacement Pump for 120 lbs. Drum
Systems

- Rapid disconnect air coupler, air nipple and muffler (fits all makes and models)
- Downtube Diameter: 1"
- Output: 80 cu.in/min. of NLGI #2 grease at 100 psi @ 70 degree(s)F ambient temperature (.35 cu. in./cycle)

Air Inlet: 1/8" NPT(f)Lube Outlet: 1/4" NPT(f)

ATD-5324 - Piston Assembly

• Piston assembly for lower downtube on all air operated grease pumps