



Automotive Tools & Equipment for the Professional Technician

Air Operated High-Pressure Grease Pump for 25-50 lbs. Pails



Features:

- 50:1 heavy-duty double acting pump
- Upgraded pump seals provide 10-12 times longer life
- 6 ft. high-pressure hose, pump muffler and Lincoln-style air coupler
- All ATD Grease Pumps are factory tested for quality & reliability

Includes:

- Follower plate with rubber wiping rings to fit CONICAL pails
- Grease Control Valve
- Rapid disconnect air coupler
- Muffler and drum cover
- Grease strainer screen (ATD-5356)
- Output: 80 cu.in/min. of NLGI #2 grease at 100 psi @ 70 degree(s)F ambient temperature (.35 cu. in.-cycle)

• Air Inlet: 1/8" NPT(f)

• Lube Outlet: 1/4" NPT(f)

• Weight: 28 lbs.

Available Accessories & Replacement Parts

ATD-5289-1 - Replacement Pump for 25-50 lbs. Pail Systems

• Includes rapid disconnect air coupler, 1/8" air nipple and muffler (fits all makes and models)

• Output: 80 cu-in/minute of NLGI#2 at 70 degree(s) ambient temperature

• Weight: 13 lbs.

ATD-5324 - Piston Assembly

 Piston assembly for lower down tube on all air operated grease pumps

ATD-5320 - Grease Pump Repair Kit

• Simple repair kit for grease pumps

ATD-5322 - Air Motor Repair Kit

• Complete repair kit for air motors

ATD-5323 - Down Tube Repair Kit

• Complete repair kit for down tubes