

LI-ION RECHARGEABLE

DUTY/PERSONAL-SIZE FLASHLIGHT

NSR-9940XL

NIGHTSTICK[®]
Life Depends on Light[™]

**DUAL
LIGHT[™]
TECHNOLOGY**

DOWNWARD FACING FLOODLIGHT



AVAILABLE IN MULTIPLE COLORS



Downward facing floodlight provides soft, unfocused light for reading or walking, or added safety in Dual-Light[™] mode.



Powerful integrated **Tail cap magnet** for hands-free use.



Light includes **drop-in charger designed to be mounted to wall or dashboard** with included AC/DC adapters.



Constructed of 6061-T6 **anodized aluminum with aggressive knurling** for positive grip.



650 LUMENS

DUTY/PERSONAL FLASHLIGHT

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

- NSR-9940XL, UPC 0 17398 80411 0
- NSR-9940XL-BL, UPC 0 17398 80745 6
- NSR-9940XL-R, UPC 0 17398 80744 9
- NSR-9940XL-G, UPC 0 17398 80746 3

MARKET APPLICATIONS

- Law enforcement, security, sporting goods, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, CEC, BIS,
- US Patent: 9,713,217

CASE MATERIAL

- Aircraft-grade 6061-T6 Aluminum w/Type III Hard Anodized Finish

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 650L, 4.25 hrs. runtime
- MEDIUM: 300L, 9.5 hrs. runtime
- LOW: 150L, 18.75 hrs. runtime

FLOODLIGHT

- HIGH: 200L, 7.25 hrs. runtime

DUAL-LIGHT

- 400L, 7 hrs. runtime

STROBE RUNTIME

- 6 hrs. runtime

CANDELA

- HIGH: 23,142
- MEDIUM: 11,302
- LOW: 6,028

BEAM DISTANCE

- HIGH: 304m
- MEDIUM: 212m
- LOW: 115m

WATER RATING

- IP-X7 Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 9.5 in (241 mm)
- HANDLE DIAMETER: 1.2 in (30 mm)
- HEAD DIAMETER: 1.6 in (41 mm)
- WEIGHT: 13.2 oz (374 g)

BATTERY







- Rechargeable Lithium-ion

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Flashlight
- Anti-roll Ring
- Rechargeable Lithium-ion Battery
- AC Power Supply
- DC Power Supply and Charger
- Instruction manual

FL1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	650 LUMENS	200 LUMENS	400 LUMENS
	4h 15min	7h 15min	7h
	304m		
	23142cd		
	2m		
	1m		
CERTIFIED			
