

USB RECHARGEABLE

TACTICAL FLASHLIGHT

USB-558XL-SERIES

BAYCO
PRODUCTS INC.

NIGHTSTICK[®]
Life Depends on Light™



PERFECT
EVERYDAY USE



5.9"

5 oz



PERFECT
EVERYDAY USE



Sliding collar hides
USB port when not in use



Red **charging indicator light**
turns green when fully charged



Use the included li-ion battery for
day-to-day use or **included back-up
CR123 carrier** when away from a
rechargeable battery source (CR123
batteries not included)



Press and hold down single switch
to **cycle between high, medium
and low modes**. Press twice to
activate **strobe** mode



AVAILABLE
IN MULTIPLE
COLORS.
COLOR MODELS
INCLUDE A
CORDERA
BELT HOLSTER.



CERTIFIED
CE

FLY STANDARD	HIGH	MEDIUM	LOW
	900 LUMENS	350 LUMENS	100 LUMENS
	2h	4h 15min	16h
	215m	129m	56m
	11524cd	4133cd	1040cd
	2m		
	1m		

900 LUMENS

TACTICAL FLASHLIGHT

LI-ION BATTERY (INCLUDED)

ITEM NUMBER/UPC

- USB-558XL, UPC 017398806022
- USB-558XL-BL, UPC 017398807456
- USB-558XL-R, UPC 017398807470
- USB-558XL-G, UPC 017398807463

MARKET APPLICATIONS

- Automotive, law enforcement, security, sporting goods, fire, rescue and industrial

CERTIFICATIONS

- CE, NFPA-1971-8.6 (2013)

CASE MATERIAL

- Aircraft grade 6061-T6 aluminum with type II anodized finish

LUMENS/RUNTIME

- HIGH: 900L, 2 hrs. runtime
- MEDIUM: 350L, 4.25 hrs. runtime
- LOW: 100L, 16.75 hrs. runtime

CANDELA

- HIGH: 11,524
- MEDIUM: 4,133
- LOW: 1,040

BEAM DISTANCE

- HIGH: 215 m
- MEDIUM: 129 m
- LOW: 56 m

WATER RATING

- IP-X7 Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 5.9 in (150 mm)
- BARREL DIAMETER: 1 in (25 mm)
- BEZEL DIAMETER: 1.2 in (30 mm)
- WEIGHT: 5.7 oz (162 g) (with batteries)

BATTERY

- Li-ion rechargeable battery, or 2 CR123 (not included) using CR123 battery carrier (included)


WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Flashlight
- Li-ion rechargeable battery
- CR123 battery carrier
- USB charging cord (2')
- Instruction manual

*Colored models include cordera belt holster

FL1 STANDARD	HIGH	MEDIUM	LOW
	900 LUMENS	350 LUMENS	100 LUMENS
	2h	4h 15min	16h
	215m	129m	56m
	11524cd	4133cd	1040cd
			

CERTIFIED



Patent #9,713,217 and #10,088,138