

Safe Multi-Function

Lumens Dual-Light™ Lumens Spotlight Lumens Floodlight

Spot High Spot Low



Flood High Flood Low







This multi-function Dual-Light™ headlamp is cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The dual top mounted switches provide user-selectable high or low-brightness spotlight, high or low-brightness floodlight operation and our exclusive Dual-Light design...the ability to turn on both the spotlight and the floodlight at the same time for maximum user safety and lighting versatility.

INTRINSICALLY SAFE

















- cetlus, atex, iecex and inmetro listed **Intrinsically Safe**
- Beam distance rated at 94 meters
- Dual brightness spotlight & floodlight plus Dual-Light™
- Engineered polymer housing







Intrinsically Safe Multi-Function Dual-Light" Headlamp



FEATURES

- CREE® LED technology 50,000 + hours LED life
- High/low-brightness spotlight, high/low-brightness floodlight & Dual-Light™
- Focused spotlight beam for distance illumination
- Wide unfocused floodlight beam for close-up illumination
- Engineered polymer housing
- Dual switches located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Heavy-duty rubber strap for hard hat applications
- Dustproof / Waterproof
- Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)
- Limited Lifetime Warranty

SAFETY RATING

cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe

Patent 7,738,229

Model	UPC 0 17398	
XPP-5454G	80427 1	

SPECIFICATIONS

- Lumens: high spotlight-115, low spotlight-60, high floodlight-120, low floodlight-60, dual-light-160
- Run-time: high spotlight-5 hrs, low spotlight-16.25 hrs, high floodlight-5.25 hrs, low floodlight-16.75 hrs, dual-light-3.5 hrs
- Beam distance: 94 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Width: 2.6in, height: 2.1in, depth: 1.8in, weight: 3.3oz

FL1 STANDARD	DUAL-LIGHT	HIGH	LOW
314	160 LUMENS	115 LUMENS	60 LUMENS
0	3h 30min	5h	16h
	94m	82m	60m
	1711cd	1668cd	882cd
2m	CE		

INCLUDED

- Headlamp
- 3 Premium alkaline AAA batteries
- Elastic non-slip head strap
- Heavy-duty rubber hard hat strap



XPP-5454G

Intrinsically Safe Multi-Function Dual-Light™ Headlamp

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION

This multi-function Dual-Light™ headlamp is cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The dual top mounted switches provide user-selectable high or low-brightness spotlight, high or low-brightness floodlight operation and our exclusive Dual-Light design…the ability to turn on both the spotlight and the floodlight at the same time for maximum user safety and lighting versatility. Power comes from 3 AAA premium batteries (included).

CASE MATERIAL Engineered Polymer - Green

DIMENSIONS Width: 2.6 inches (66 mm) • Height: 2.1 inches (53 mm) • Depth: 1.8 inches (46 mm)

WEIGHT Weight: 3.3 oz. (94 g) with batteries installed

LIGHT SOURCE

Unbreakable polycarbonate with scratch resistant coating
CREE® LED Impervious to shock with a 50,000 hour lifetime

LIGHT OUTPUT High-Brightness Spotlight: 115 lumens • Low-Brightness Spotlight: 60 lumens • High-Brightness Floodlight: 120 lumens

• Low-Brightness Floodlight: 60 lumens • Dual-Light: 160 lumens

ON/OFF Dual Switches. High/Low Spotlight, High/Low Floodlight, Dual-Light

RUN-TIME High-Brightness Spotlight: 5 hours • Low-Brightness Spotlight: 16.25 hours • High-Brightness Floodlight: 4.25 hours •

Low-Brightness Floodlight: 13.75 hours • Dual-Light: 3.5 hours

BATTERY 3 Alkaline AAA batteries (included)

• cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe

• CREE® LED technology - 50,000 + hours LED life

High/low-brightness spotlight, high/low-brightness floodlight
 & Dual-Light™


- · Focused spotlight beam for distance illumination
- · Wide unfocused floodlight beam for close-up illumination
- · Engineered polymer housing
- Dual switches located on top of light
- · Adjustable ratchet tilt head
- Non-slip elastic head strap
- · Heavy-duty rubber strap for hard hat applications
- Dustproof / Waterproof
- Impact & chemical resistant
- 3 AAA batteries (included)

FL1 STANDARD	DUAL-LIGHT	HIGH	LOW
31/K	160 LUMENS	115 LUMENS	60 LUMENS
0	3h 30min	5h	16h
M	94m	82m	60m
	1711cd	1668cd	882cd
2m			
1m			

WARRANTY Limited Lifetime Warranty

APPROVALS





Bayco Products, Inc. XPP-5454G 640 S. Sanden Blvd., Wylie, TX 75098



ID 4008947 INTRINSICALLY SAFE SECURITE INTRINSEQUE



Intertek

CLASS I DIV 1 GRPS A-D T3 CLASS II & III GRPS E-G T135°C CLASS I ZONE 0 AEx ia IIC T3 Ga Ex ia IIC T3 Ga ⑤ II 1 G Ex ia op is IIC T3 Ga Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27928X IECEx ITS 18.0030X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell E92 or EN92

Conforms to:

ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11

Certified to: CAN/CSA STD C22.2 No 157 CAN/CSA STD C22.2 No 60079-0 CAN/CSA STD C22.2 No 60079-11 CSA STD C22.2 No 25