

Car repair



		art.
	059040197	5904 VG/1M

- n. 16 **42:** combination wrenches 6÷21 mm
- n. 5 **42:** combination wrenches 22 - 24 - 27 - 30 - 32 mm
- n. 1 **1084:** heavy duty diagonal cutting nippers □ 160 mm
- n. 1 **1150:** half-round needle nose pliers = 180 mm
- n. 1 **1166:** screwdrivers for slotted head screws ● 160 mm
- n. 8 **96T:** offset hexagon key wrenches ○ 2-2,5-3-4-5-6-7-8 mm
- n. 6 **97TTX:** drivers for Torx® head screws, with handles ⊙ T10-T15-T20-T25-T27-T30
- n. 4 **1201:** screwdrivers for cross head Phillips® screws ● 3x75 - 4x100 - 5,5x150 - 6,5x150 mm
- n. 3 **1202:** screwdrivers for cross head Phillips® screws ⊕ PH0x60 - PH1x80 - PH2x100 mm
- n. 1 **920AN/125:** 1/2" wobble extension bar 125 mm
- n. 1 **920AN/250:** 1/2" wobble extension bar 250 mm
- n. 1 **920/25:** 1/2" drive universal joint
- n. 1 **920/42:** 1/2" drive sliding T-handle
- n. 1 **920/55:** 1/2" drive reversible ratchet ⊗
- n. 19 **920A:** 1/2" square drive hexagon sockets ○ 10÷24 - 26 - 27 - 30 - 32 mm
- n. 1 **1032:** circlip pliers straight, internal ⊙ 180 mm
- n. 1 **1034:** circlip pliers bent, internal ⊙ 170 mm
- n. 1 **1036:** circlip pliers straight, external ● 175 mm
- n. 1 **1038:** circlip pliers bent, external ● 175 mm
- n. 2 **35:** flat chisels, ribbed type 100 - 200 mm
- n. 1 **1370:** engineer's hammer 300 g
- n. 1 **1390:** soft face hammer Ø 35 mm