

Car repairs



art.	art.	
059040196	5904 VG/5T	
024002454	2400SAXL-O/V	(C24SA-XL/7O +5904VG/5T)
024002455	2400SAXL-G/V	(C24SA-XL/7G +5904VG/5T)
024002456	2400SAXL-R/V	(C24SA-XL/7R +5904VG/5T)

- n. 5 **920ME**: 1/2" drive, socket drivers for hexagon screws O 5 - 6 - 8 - 10 - 12 mm
- n. 1 **920/21**: 1/2" drive extension bar 125 mm
- n. 1 **920/22**: 1/2" drive extension bar 255 mm
- n. 1 **920/25**: 1/2" drive universal joint
- n. 1 **920/42**: 1/2" drive sliding T-handle
- n. 1 **920/55**: 1/2" drive reversible ratchet ⊗
- n. 19 **920A**: 1/2" square drive hexagon sockets O 10÷24 - 26 - 27 - 30 - 32 mm
- n. 16 **42**: combination wrenches 6÷21 mm
- n. 5 **42**: combination wrenches 22 - 24 - 27 - 30 - 32 mm
- n. 8 **952**: T - handle wrenches with swivelling socket O 7 - 8 - 10 - 12 - 13 - 14 - 17 - 19 mm
- n. **VP6**: empty thermoformed tray
- n. 1 **1032**: circlip pliers straight, internal ⊗ 180 mm
- n. 1 **1034**: circlip pliers bent, internal ⊗ 170 mm
- n. 1 **1036**: circlip pliers straight, external ⊗ 175 mm
- n. 1 **1038**: circlip pliers bent, external ⊗ 175 mm
- n. 7 **1290**: screwdrivers for cross head Phillips® screws ⬮ 2,5x50 - 3x75 - 3,5x100 - 4x125 - 5,5x100 - 5,5x150 - 6,5x150 mm
- n. 5 **1297TX**: drivers for Torx® head screws, with handles ⊗ T25 - T27 - T30 - T40 - T45
- n. 6 **96T**: offset hexagon key wrenches O 2 - 2,5 - 3 - 4 - 5 - 6 mm
- n. 8 **55**: double open end wrenches 6x7 - 8x9 - 10x11 - 12x13 - 14x15 - 16x17
18x19 - 20x22 mm
- n. 9 **96N/SC9**: offset hexagon key wrenches O 1,5 - 2 - 2,5 - 3 - 4 - 5 - 6 - 8 - 10 mm
- n. 3 **1290**: screwdrivers for cross head Phillips® screws ⬮ 8x150 - 8x200 - 10x200 mm
- n. 2 **1290N**: screwdriver for slotted head screws, extra-short series ⬮ 4x30 - 6,5x30 mm
- n. 6 **1292**: screwdrivers for cross head Phillips® screws ⊕ PH0x60 - PH0x100 - PH1x80 - PH1x120 - PH2x100 - PH2x150 mm
- n. 2 **1292**: screwdrivers for cross head Phillips® screws ⊕ PH3x150 - PH4x200 mm
- n. 2 **1292N**: screwdriver for cross head Phillips® screws, extra-short series ⊕ PH1x30 - PH2x30 mm
- n. 2 **35**: flat chisels, ribbed type 100 - 200 mm
- n. 1 **1370**: engineer's hammer 300 g
- n. 1 **1390**: soft face hammer Ø 35 mm
- n. 1 **1150BM**: half-round needle nose pliers = 180 mm
- n. 1 **1166BM**: extra long needle knurled nose pliers, bi-material handles ⬮ 160 mm
- n. 1 **1084BM**: heavy duty diagonal cutting nippers □ 160 mm
- n. 8 **861TX**: bits for Torx® head screws ⊗ T6÷T15
- n. 8 **866TX**: bits for Torx® head screws ⊗ T20÷T55
- n. 1 **895/1**: socket holder
- n. 1 **895/6**: socket holder
- n. 1 **900FTX**: 1/4" sockets for Torx® head screws ⊗ E4÷E10
- n. 1 **920FTX**: 1/2" sockets for Torx® head screws ⊗ E12÷E24
- n. 1 **920TX**: 1/2" drive, socket drivers for Torx® head screws ⊗ T55L - T60 - T70L