

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 01/04/2016 Revision date: 01/04/2016 Version: 1 0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : SET Small Engine Tune-up

Product code : 16-SET

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Air Intake Cleaner

1.3. Details of the supplier of the safety data sheet

The Blaster Corporation

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Aerosol 2 Gases Under Pressure - DissolvedGas Acute Toxicity 4 (Inhalation) Skin Sensitization 1 Aspiration Hazard 1

2.2. Label elements

GHS-US labelling

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard pictograms (GHS-US)



: Danger







Hazard statements (GHS-US) : Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled.

May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) : Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid brea hing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ven ilated area.

Contaminated work clo hing must not be allowed out of the workplace. Wear protective gloves. Ifswallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Wash contaminated clo hing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents and container in accordance with all local, regional, na ional and international regulations.

2.3. Other hazards

Signal word (GHS-US)

No additional information available

2.4. Unknown acute toxicity (GHS-US)

3 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information oningredients

3.1. Substance

Not applicable

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates, petroleum, solvent-dewaxed heavyparaffinic	(CAS No)64742-65-0	40 - 70	Asp. Tox. 1
Petroleum distillates, hydrotreated light	(CAS No)64742-47-8	10 - 30	Flam. Liq. 3 Asp. Tox. 1
Isopropylalcohol	(CAS No) 67-63-0	5 - 10	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Carbon dioxide	(CAS No) 124-38-9	1 - 5	Compressed gas
Polypropylene glycol monobutyl ether	(CAS No) 9003-13-8	1 - 5	Skin Irrit. 2 Eye Irrit. 2A
N-Phenyl-1-naphthylamine	(CAS No) 90-30-2	0.1 - 1	Acute Tox. 4 (Oral) Skin Sens. 1 STOT RE 2

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feelunwell.

First-aid measures after skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion : Do NOT

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: Harmful if inhaled. May cause respiratory tractirritation.

Symptoms/injuries after skin contact

: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skincontact.

Symptoms/injuries after eye contact

: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries afteringestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where poss ble).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Carbon dioxide, dry chemical, foam.

Unsuitable extinguishing media

: Water may beineffective.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon, hydrocarbons.

Explosion hazard

: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions

: Cool closed containers exposed to fire with water.

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.2. Methods and material for containment and cleaning up

For containment

: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up

: Scoop up material and place in a disposal container. Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safehandling

Precautions for safe handling

: Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 $^{\circ}\text{C/}$

Not applicable

122 °F. Store away from direct sunlight or other heat sources. Keep dry.Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

USA OSHA

Storage area

SECTION 8: Exposure controls/personalprotection

OSHA PEL (TWA)

8.1. Control parameters

o.i. Control para			
Distillates, petroleum	n, solvent-dewaxed heavy paraffinic (64742-65-0)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
Petroleum distillates	Petroleum distillates, hydrotreated light(64742-47-8)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
Isopropyl alcohol(67	Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	400 ppm	
USA OSHA	OSHA PEL (TWA)(mg/m³)	980 mg/m³	
USA OSHA	OSHA PEL (TWA)(ppm)	400 ppm	
Carbon dioxide(124-38-9)			
USA ACGIH	ACGIH TWA (ppm)	5000 ppm	
USA ACGIH	ACGIH STEL (ppm)	30000 ppm	
USA OSHA	OSHA PEL (TWA)(mg/m³)	9000 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm	
Polypropylene glycol monobutyl ether(9003-13-8)			
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
N-Phenyl-1-naphthyla	N-Phenyl-1-naphthylamine (90-30-2)		
USA ACGIH	ACGIH TWA	Not applicable	

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits. Ensure that eyewash stations and safety showers are close to

the workstation location.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must

be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selectedrespirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash handscarefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas / PressurizedLiquid.

Appearance : Viscous / Oily.

Color : Red.

Odor : Moderate aliphatic.
Odor threshold : No dataavailable.
pH : No data available.

Relative evaporation rate (butylacetate=1) : >1

Melting point No dataavailable. Freezing point No dataavailable. Boiling point 177.8 °C (352°F) 23.9 °C (75 °F)TCC Flash point Auto-ignition temperature No dataavailable. Decomposition temperature No dataavailable. Flammability (solid, gas) Flammable. Vapor pressure No dataavailable. Relative vapor density at 20 °C > 1(Air=1)

Relative vapor density at 20 °C : > 1 (Air=1)

Relative density : 0.8

Solubility : Neglig ble.

Log Pow : No dataavailable.

Log Kow : No dataavailable.

Viscosity, kinematic : No dataavailable.

Viscosity, dynamic : No dataavailable.

Explosive properties : No dataavailable.

Oxidising properties : No data available. Explosive limits : No data available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normaluse.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Excessivewater.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents. Water.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled

SET Small EngineTune-up	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	>1.0 but ≤5.0 mg/l/4h

Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	2.18 mg/l/4h

Petroleum distillates, hydrotreated light(64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

Isopropyl alcohol(67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rat	12800 mg/kg
LD50 dermal rabbit	12870 mg/kg
LC50 inhalation rat	72.6 mg/l/4h

Polypropylene glycol monobuty	ether(9003-13-8)	
LD50 oral rat	5840 mg/kg	
LD50 dermal rabbit	13340 mg/kg	

N-Phenyl-1-naphthylamine (90-30-2)	
LD50 oral rat	1625 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation : Based on available data, the classification criteria are not met.

Serious eye damage/irritation : Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Based on available data, the classification criteria are not met. Specific target organ toxicity(single exposure) : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : Harmful if inhaled. May cause respiratory tractirritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skincontact.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness andswelling.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

SET Small EngineTune-up

Persistence and degradability Not established.

12.3. Bioaccumulative potential

SET Small EngineTune-up

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapors may accumulate in the container. Do not incinerate empty containers.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No.(DOT) : UN1950

14.2. UN proper shipping name

Proper Shipping Name (DOT) : AEROSOLS, flammable, limited quantities

: 2.1

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT)



Packing group (DOT) : Not applicable

14.3. Additionalinformation

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA)inventory.

Isopropyl alcohol (67-63-0)	
Listed on United States SARA Section313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - EmissionReporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

15.3. US State regulations

SET Small EngineTune-up

State or local regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Indication of changes : None.

Date of issue : 01/04/2016

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.