TRYORNANCE

TRYON is available in 3 versions : safety spectacles, OTG and prescription spectacles. Ultra-wrap-around, sporty design, co-injected FLEX 160° temples, adjustable and non-slip bridge, PLATINUM[®] coating... TRYON perfectly combines style, innovation and absolute protection.



TRYON **STYLE AND PERFORMANCE**

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
TRYON	Clear	TRYOPSI	2C-1,2 🗁 1 FT KN CE	🗁 EN166 FT CE	Anti-scratch/Anti-fog +
	CSP	TRYOCSP	5-1,4 🗁 1 FT KN C€	🗁 EN166 FT 🕻 €	Anti-scratch/Anti-fog
	Smoke	TRYOPSF	5-3,1 🖆 1 FT KN CE	🗁 EN166 FT 🕻 €	Anti-scratch/Anti-fog +
	Blue flash	TRYOFLASH	5-3,1 🖆 1 FT CE	🗁 EN166 FT CE	AS
		TRYOPOL	5-3,1 🖆 1 FT K C €	🗁 EN166 FT CE	AS
	Retainer strap (option)	RUSHKITS	-	-	-

LENS MARKING

🗁 = Manufacturer name

Z87+ = Impact rated for Plano product - tested and approved to ANSI Z87.1-2015

Lens type

<u> </u>	
o Clear	= none
o Welding	= W and Shade number from 1,3 to 14
o UV filter	= U and scale number from 2 to 6
o Visible light filter	= L and scale number from 1,3 to 10
o IR filter	= R and scale number from 1,3 to 10
o Variable tint	= V
o Special purpose	= S

TECHNOLOGIES

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

BSi

POLARIZED

afaq

A technology approved for permanent wearand certified with perfect optical quality, it offers unbeatable comfort by filteringglare and reflections. Ideal for the maritimeenvironment Filters 99.99% of UVA/UVB.

PLATINUM[®]

appearance of fogging.

The exclusive scratch and fog resistant

PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this

permanent coating applied on both sides of the lens makes it highly

scratch resistant and durably delays the

FRAME MARKING

= Manufacturer name

Z87+ = Impact rated for Plano product - tested and approved to ANSI Z87.1-2015

Country of origin

ANSI: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

ANSI: Standard

= Manufacturer name

Bollé Safety product approval certificates to ANSI standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND UPC/EAN13 CODE							CHARACTERISTICS	
	TRYOPSI	TRYOPSF	TRYOCSP	TRYOFLASH	TRYOPOL	RUSHKITS	LENSES	PC - 2,2 mm - Curve 8
Inner Pack	3660740008260	3660740008277	3660740008284	3660740008437	3660740009496	3660740007546	FRAME	PC
Master Pack	3660740108267	3660740108274	3660740108281	3660740108434	3660740109493	3660740107543	TEMPLES	PC + TPR
							STRAP (OPTION)	Nylon/15mm/Adjustable
UPC/EAN13 code	3660740208264	3660740208271	3660740208288	3660740208431	3660740209490	3660740207540	SPARE LENSES	No

Non-contractual pictures



