

# 1/4", 3/8", 1/2" Pistol drills

Chicago Pneumatic Composite Drills for Vehicle Service and MRO



**Excellent  
for drilling,  
honing,  
reaming and  
hole sawing**

- ✓ **High Comfort**
- ✓ **Lightweight**

**People.  
Passion.  
Performance.**

 **Chicago  
Pneumatic**

# Composite Drills for Vehicle Service and MRO

The new Chicago Pneumatic composite drills offer high level of ergonomics with composite housing and easy-to-reach Forward – Reverse lever. They provide users high comfort and grip during drilling thanks to the thermoplastic rubber handles.

## EASY OPERATION

Forward – Reverse lever on the top for easier access

## HIGH RESISTANCE TO STALLS

Due to low speed gear box

## HIGH DURABILITY

Supplied with high quality industrial Jacobs® chucks for longer use – both options: keyed metal or keyless

## GREAT HANDLING

Flat back part for better pushing action while drilling and tapping

## HIGH COMFORT

Composite housing with thermoplastic rubber handle grip

## ERGONOMICS

Wings on right & left sides to guide the forefinger

## LIGHTWEIGHT

5% lighter than existing models

## EXCELLENT SPEED CONTROL

Large teasing trigger and progressive valve allowing more control to start holes



	Model	Part #	Reversible	Chuck type	Chuck capacity		Power		Free Speed RPM	Stall Torque		Average air cons		Air cons @ free speed		Overall length		Net Weight		Noise Level dB(A)	Sound Power dB(A)
					in.	mm	hp	W		ft.lbs.	Nm	cfm	l/s	cfm	l/s	in.	mm	lbs.	kg		
1/4"	CP7300C	894 107 3013	-	Keyed Metal	1/4	6	0.3	230	3300	1.9	2.6	5.3	2.5	21.2	10	6.7	170	1.4	0.64	85	96
	CP7300RC	894 107 3011	Reversible	Keyed Metal	1/4	6	0.3	230	2800	1.9	2.6	5.3	2.5	21.2	10	6.7	170	1.5	0.67	82	93
	CP7300RQCC	894 107 3012	Reversible	Keyless	1/4	6	0.3	230	2800	1.9	2.6	5.3	2.5	21.2	10	6.7	170	1.5	0.69	82	93
3/8"	CP9285C	894 109 2850	-	Keyed Metal	3/8	10	0.6	460	3000	4.1	5.5	6.9	3.25	27.5	13	8.2	209	2.4	1.09	83.7	94.7
	CP9287C	894 109 2870	-	Keyless	3/8	10	0.6	460	3000	4.1	5.5	6.9	3.25	27.5	13	8.2	209	2.4	1.09	83.7	94.7
	CP9790C	894 109 7900	Reversible	Keyed Metal	3/8	10	0.5	360	2100	4.1	5.5	6.9	3.25	27.5	13	9.3	235	2.4	1.09	87.5	98.5
	CP9792C	894 109 7920	Reversible	Keyless	3/8	10	0.5	360	2100	4.1	5.5	6.9	3.25	27.5	13	9.3	235	2.4	1.09	87.5	98.5
1/2"	CP9286C	894 109 2860	-	Keyed Metal	1/2	13	0.5	360	600	16.2	22	6.9	3.25	27.5	13	9.8	250	3.3	1.49	84.2	95.2
	CP9288C	894 109 2880	-	Keyless	1/2	13	0.5	360	600	16.2	22	6.9	3.25	27.5	13	9.8	250	3.2	1.45	84.2	95.2
	CP9789C	894 109 7890	Reversible	Keyed Metal	1/2	13	0.5	350	840	10.3	14	6.9	3.25	27.5	13	10.4	265	3.1	1.4	88.3	99.3
	CP9791C	894 109 7910	Reversible	Keyless	1/2	13	0.5	350	840	10.3	14	6.9	3.25	27.5	13	10.4	265	3.1	1.4	88.3	99.3

Hose int. 3/8" (10 mm) with pressure @90 PSI (@6.3 Bar)  
Vibration < 2.5 m/s<sup>2</sup> – Runout: 0.003 in. / 0.1 mm

Listed specifications are for reference only. Please check tool documentation.

## ACCESSORIES & SPARES



Rely only on high-grade air drills and drivers offered on our virtual shelves.