

DeVilbiss
CLEAN™

CLEAN AIR



CLEAN TECHNICIAN



CLEAN FINISHES



CONTAMINANT FREE REFINISHING





CLEAN TECHNICIAN

Reusable Coverall

Keeps both painter and spray booth cleaner

- Lightweight durable nylon front
- Breathable cool cotton back
- Washable/Reusable



Order No.	
803596 (M)	6/cs
803597 (L)	6/cs
803598 (XL)	6/cs
803599 (3XL)	6/cs

Disposable Coverall

Reduces Contamination From Street Clothing

- Disposable
- Lightweight and Comfortable
- Meets OSHA requirement



Order No.	
803671 (M)	48/cs
803672 (L)	48/cs
803673 (XL)	48/cs
803674 (3XL)	48/cs

Champion™ Disposable Cartridge Respirator

OV/N95 Dual Cartridge Respirator

- Soft, comfortable face piece
- Low-profile cartridges enhance visibility
- Packaged in resealable storage bag



Approved, when used as specified.



Order No.	Model No.	
803611 (M)	DCR-502	1/bag-12/cs
803612 (L)	DCR-503	1/bag-12/cs

Reusable Lab Coat

Contributes to clean prep practices

- Lightweight durable nylon
- 3-pocket design
- Washable/Reusable



Order No.	
803664 (M)	6/cs
803665 (L)	6/cs
803666 (XL)	6/cs
803667 (3XL)	6/cs



Champion™ Disposable Cartridge Respirator

Disposable Coverall

Reusable Lab Coat

Paint Booth & Prep Stations

CamAir® CT Plus™ 5-Stage Filter System

Worry free air filtration for top-quality paint jobs

- First stage filter removes oil, water and dirt down to 40 microns
- Second stage coalescer removes oil vapors and dirt particles down to .01 microns
- Third stage filter media repeats dirt and oil filtering
- Fourth stage dessicant removes water vapor down to dewpoint of -40° F
- Fifth stage exits final filter media
- 30 CFM capacity



Order No.
130522

Patented quick-change
dessicant bag design

First Step at Compressor

Automatic Drain with Y-Strainer Valve

Electric timer automatically drains water from compressed air systems

- Mounts directly on compressor tank drain and air piping drain points
- Eliminates water build-up that can decrease shop air capacity
- Removable filter for easy cleaning



Order No.
130512

Air Tools

FinishLine® Clean Air Control

Clean air filtration for air tool reliability and longevity

- 5 micron filter removes particulates and moisture
- Large capacity in a compact design
- Regulator and gauge included
- 80 CFM and 120 CFM models



Order No.	Model No.	Description
130099	HAR-602	FinishLine® Air Control Unit (120CFM w/50CFM Regulator)
803643	HAR-680	FinishLine® Clean Air Control (80CFM w/50CFM Regulator)

Booth & Prep Stations

3/8" x 35' Air Hose with High Flow Fittings

Durable construction for efficient air delivery

- Synthetic rubber compound tube
- High tensile strength braid
- Superior resistance to heat, weathering, ozone and abrasion

Synthetic rubber compound tube
High tensile strength braid

Order No.	Model No.	Description
220052	HA-5867	Hose w/HF Fittings
240145	HC-4419	HF Stem Female
240147	HC-4719	HF Coupler Male



CamAir® CT Plus™ 5-Stage Filter System

FinishLine® Clean Air Control

3/8" x 35' Air Hose with High Flow Fittings

Automatic Drain with Y-Strainer Valve





CLEAN BOOTH SOLUTIONS

A clean spray booth is the first step to a clean paint job.

Dirt Control Floor Coat

Traps airborne particulates caused by increased air movement necessary for drying waterborne paints

- A must for waterborne shops!
- Shops observe a reduction of airborne particles in spray booth of up to 50%
- Neutralizes particles electrical charge so they stick to the floor, not the vehicle



Order No.	Description
803491	Dirt Control Floor Coat
803492	2-Gallon Pump Sprayer

Dirt Control Wall Coat

Maintains bright spray booth walls for better color-match visibility

- Bright white, water based formula
- Lasts 500 bake cycles
- Easily peels off and reapplies without surface prep



Order No.	Description
803668	4 gals/cs

DeVilbiss® Clear Glass Coat

Peelable glass surface coating

Order No.	Description
803669	6 quarts/cs



1. Bumper Cover Surfaces

Bumper Prep Pad

Clean, degrease and abrade in one easy step

- Removes mold release residues found in OEM bumper covers
- Removes both water-based and oil-based contaminants
- Prepares surface for paint adhesion
- Individually bar coded for job costing



Order No.	Description
803557	1/pkg-12/cs

4. Pre-Paint - Decontamination

DeWipe-Outs™

Pre-saturated wipes for contaminant-free primed surfaces

- OEM process for final decontamination
- Eliminates static that attracts dirt
- Ideal for paintable surfaces, plastic parts and bumper covers



Order No.	Description	Quantity
803045	85% IPA/15% DI Water – Normal Climates Formula	50 wipes/pouch
803046	50% IPA/50% DI Water – Dry Climates Formula	50 wipes/pouch
803418	Acetone Blend – Low VOC Formula	50 wipes/pouch

DeWipe-Outs™ Refill Case

Sealed container keeps DeWipe-Outs saturated and ready to use

Order No.	Description
803048	



CLEAN SURFACE PREP

Best practices for contaminant-free refinishing

2. Pre-Paint Surfaces - Cleaning

Paint Prep Wipe

Pre-clean prep wipe

- ▮ Strong, absorbent, virtually lint-free non-woven wipe
- ▮ For use with water-based and solvent-based surface pre-cleaners
- ▮ Production oriented ¼ fold format



Order No.	Model No.	
803657	DC-101	300 ct dispenser box

3. Pre-Paint Surfaces - Tacking

Tack Wipe

Removes lint and fine particulates from refinish surfaces

- ▮ Low tack and moderate tack formulas
- ▮ Solvent and waterborne compatible
- ▮ Individually bar coded for job costing



Order No.	Model No.	Description	
803816	TCK-101-K12	Moderate Tack: Cotton	Individually bagged 12/bx
803817	TCK-121-K12	Low Tack: Poly	Individually bagged 12/bx

5. Intercoat Surfaces

Anti-Static Wipe

Treated wipe eliminates static between refinish coats

- ▮ Removes contaminants between coats of sealer, basecoat and before clear
- ▮ Helps reduce orange peel and improve metallic orientation
- ▮ Non-marring, lint-free and reusable



Order No.	
803553	Individually bagged 12/cs

Defect Repair

Shim-Mask®

Stainless steel masking stencil minimizes repair area of runs, sags and nibs

- ▮ Helps prevent sanding and shaving rub-through
- ▮ Saves time and improves repair quality
- ▮ Minimizes repair area to prevent over processing



Order No.	
803654	3/pkg

Dirt Control & Prep Solutions

Protect Profits And Increase Throughput By Minimizing Buffing And Costly Rework

DeVilbiss Dirt Control Floor Coat



- Reduces airborne particles in a spray booth by trapping them to booth floor
- Significantly reduces buffing time caused by dirt in paint jobs
- Ideal for shops spraying waterborne

Part No. Description

803491	Dirt Control Floor Coat (5 Gallons)
803492	2-gallon Pump Sprayer

DeWipe-Outs™ Pre-Saturated Prep Wipe



- “Static Killer” formula reduces static charge and static related dirt
- Great for plastic parts and bumper covers
- Lint-Free wipe removes residue and fibers left by tacking

Part No. Description

803045	85% IPA/15% DI Water Wipe
803046	50% IPA/50% DI Water Wipe
803418	Acetone blend, California exempt. Must be used with 803048 storage case
803048	Storage case w/lid gasket & snap closure

DeVilbiss Bumper Prep Pad



- Clean, abrade, & degrease in one easy step
- Reduces steps in bumper prep process to increase efficiency
- Provides comprehensive abrasion for better paint adhesion

Part No. Description

803557	All-In-One Bumper Prep Pad
--------	----------------------------

DeVilbiss Anti-Static Wiper



- Dry wiper eliminates paint defects caused by static imbalance
- Neutral surface eliminates issues caused by dirt and airborne particles, allows for better metallic orientation and flow of clearcoats
- Use before primer, basecoats and clearcoats – no marring

Part No. Description

803553	Anti-Static Wiper
--------	-------------------



Standard Operating Procedures DeVilbiss CLEAN™

Description

DeVilbiss CLEAN™ delivers solutions based products to simplify the automotive refinishing process. Each of the products can be used alone or together as part of a system. DeVilbiss CLEAN works to minimize buffing and costly rework delivering results that are more effective, efficient, and profitable.

Directions for Use

A: DeVilbiss® Clean Dirt Control Floor Coat – (before spraying)

DeVilbiss® CLEAN Dirt Control Floor Coat is a water-based floor coating that traps dirt and overspray circulating in the paint booth. Applied with a standard pump sprayer, the floor coat captures and transforms airborne particles into heavy dirt that is easily swept with a broom. Regular use of this floor coating helps keep dirt and overspray out of the paint job, improving the shop's quality and profitability by reducing time spent polishing defects. Apply sparingly. Excessive amounts can cause floors to become slippery.

NOTE: Do not use on tiled, painted cement, or grated floors.

- 1) Sweep the booth at the start of each day using a stiff push broom on the main floor, use a smaller broom for edges
- 2) Collect dirt and overspray in a dustpan and dispose
- 3) Apply approximately one quart (use approximately 2 quarts the first application) of floor coating in a light, even mist using a two-gallon pump sprayer. The floor should be damp but not shiny.
- 4) After approx. 7-8 cars, sweep out booth and reapply.
- 5) As performance results diminish wash out booth with a hose & push broom. Allow to dry before applying a new 2 quart application.

Directions for Use

B. DeVilbiss CLEAN™ Bumper Prep Pad – (if you have a bumper or plastic part to be prepped)

DeVilbiss CLEAN™ Bumper Prep Pad is a single-use pre-saturated scuff pad for new unprimed bumpers or plastic parts. The Bumper Prep Pad provides a more consistent scratch pattern and greatly improves paint adhesion. Additional prep products may not be needed as the Bumper Prep Pad cleans, abrades, and degreases in one easy step.

NOTE: Designed as a single-use scuff pad. Do not use on more than one bumper or part. The bumper/part to be prepped does not need to be tempered or prebaked. Clean water supply is needed.

- 1) Wear protective gloves to prevent possible skin irritation.
- 2) Remove all loose contaminants from the surface to be prepped.
- 3) Submerge Bumper Prep Pad in clean water for approximately 3 seconds



- 4) Thoroughly abrade the part two times. Rewet the pad in clean water as needed. Do not intentionally rinse/wring cleaning agent from the Bumper Prep Pad.
- 5) Do not allow the surface and pad to dry before thoroughly rinsing the part with clean water.
- 6) Repeat the scuffing process as needed if the part does not appear uniformly clean and abraded. Water should not bead on the abraded surface once the abrasion has been properly completed.
- 7) Blow dry and wipe down with a DeWipe-Outs wiper
- 8) Discard the Bumper Prep Pad after a single usage.

Directions for Use

C. DeVilbiss DeWipe-Outs™ – (if you prefer a pre-saturated wipe before priming and before topcoat)

DeVilbiss DeWipe-Outs™ is an effective lint-free wiper that removes residue and fibers left by tacking. Pre-saturated and infused with a “static killer” formula, it significantly reduces static charge and static related dirt. DeWipe-Outs are the final wipe before priming and before painting. It is effective on plastic and fiberglass surfaces and is often used in OEM facilities.

NOTE: Not to be used on basecoats

- 1) Wear protective gloves to prevent possible skin irritations.
- 2) Ensure package is tightly resealed
- 3) Test in an inconspicuous area to ensure desired results
- 4) Using firm & even strokes wipe down the entire surface area prior to priming and prior to topcoat.

Directions for Use

D. DeVilbiss CLEAN™ Anti-Static Wiper – (before sealer, between basecoats, and before clearcoat application)

DeVilbiss CLEAN™ Anti-Static Wiper is a dry wiper designed to eliminate paint defects caused by dirt and static imbalance. It is non-marring, lint-free, and OEM approved. ***The Anti-Static Wiper can be used before sealer, between basecoats, and before clearcoat applications.*** The Anti-Static Wiper assures better metallic orientation reducing the static charge which can cause metallics to orientate incorrectly. Static charge impedes the flow of clearcoat and is a contributing factor to “orange peel”, creating a neutrally charged surface with the Anti-Static Wiper allows clearcoat to flow as it was intended for a better finish.

NOTE: For best results cloth must make contact with entire surface to be sprayed. USE DRY ONLY.

- 1) Carefully wipe the entire surface to be sprayed with the DeVilbiss CLEAN™ Anti-Static Wiper.
- 2) For best results use even, firm, overlapping strokes as if you were spraying the surface.