

WAYPUMP08

Battery Operated Transfer Pump with Nozzle



Thank you for purchasing the **DeWay™ Battery Operated Transfer Pump with Nozzle**. This

User Guide is intended to provide you with guidelines to ensure that operation of this product is safe and does not pose risk to the user. Any use that does not conform to the guidelines described in this User Guide may void the limited warranty.

Please read all directions before using the product and retain this guide for reference. This product is intended for household use only. It is not intended for commercial use.

This product is covered by a limited one-year warranty. Coverage is subject to limits and exclusions. See warranty for details.

Safety Precautions


- > Only use compatible liquids with this pump.
- > Do not allow children to operate the product.
- > Make sure to remove any liquid left in the hose after use.
- > Do not use the pump for transferring the following liquids: acetone, benzene, cresol, ethyl, phenol, methyl ethyl, concentrated caustic soda liquid, nitric acid, hydrochloric acid, or sulfuric acid.
- > Do not refuel directly while the vehicle or other fuel-powered equipment is turned on.
- > Do not alter or disassemble the pump.
- > Do not place the pump in a wet or damp area.
- > Do not turn the pump upside down after use.
- > Do not leave pump unattended when in use.
- > **CAUTION: Remove the batteries from pump when not in use.**
- > When using the pump on a fuel tank of a heater, turn the heater off and allow it to cool off first.
- > Do not use corrosive chemicals in this pump.

Operating Instructions


WAYPUMP08




- 1 > Unscrew the battery case counterclockwise.



- 2 > Install two (2) D size batteries (not included) into the battery case. Insert batteries with positive and negative sides facing the correct way, as shown in the image below.



- 3 > Screw the battery case back onto the pump.
- 4 > Make sure the drain hose (long, flexible tube) is installed securely.
- 5 > Place a supply tank of a compatible liquid and a receiving container on a flat, level surface.
- 6 > Insert the suction pipe (short, nonflexible tube) into the supply tank.
- 7 > Place the drain hose into the receiving container.
- 8 > Slide the ON/OFF switch on the top of the pump to the ON position.



- 9 > Squeeze the trigger of the nozzle to control the pump flow.

NOTE: Even with the pump turned on, the product will not operate until you squeeze the trigger.

To turn off the pump:

- 1 > Release the trigger to stop pump flow.
- 2 > Slide the switch to the OFF position when you are finished with your pump.

Compatible Liquids

- ▶ Gasoline
- ▶ Kerosene
- ▶ Diesel
- ▶ Non-potable water
- ▶ Antifreeze
- ▶ Windshield washer fluid

Specifications

- ▶ Flow Rating: 2.4 gpm (9 Lpm)
- ▶ Power Source: Two (2) D size batteries (not included)
- ▶ Pump Type: Manual
- ▶ Material: Polypropylene, polyethylene, and acetal plastic



Questions or Concerns? Contact Us!

telephone: 888-375-6700

email: info@supportcbp.com

DeWay is a trademark of C&A IP Holdings, LLC, in the U.S.

All other products, brand names, company names, and logos are trademarks of their respective owners, used merely to identify their respective products, and are not meant to connote any sponsorship, endorsement, or approval.

Distributed by C&A Marketing, Inc., 114 Tived Lane East, Edison, NJ 08837. Made in Korea.

© 2020. C&A IP Holdings, LLC. All Rights Reserved.