

Dynabrade Nitro Series™

4" Extension Cut-Off Grinder

Safety, Operation and Maintenance – Save This Document and Educate All Personnel

Model	Wheel Dia.	RPM	Hp	Exhaust
ECU4	4" (76 mm) Type 41	14,000	1	Rear

GRINDER



Wheel sold separately.



⚠ WARNING

Read and understand this tool manual before operating your air tool. Follow all safety rules for the protection of operating personnel as well as adjacent areas. Always operate, inspect and maintain this tool in accordance with the American National Standards Institute (ANSI). Safety Requirements for abrading materials with coated abrasive systems – ANSI B7.1, Compressed Air and Gas Institute (CAGI) Safety Code for Portable Air Tools – B186.1, Code of Federal Regulation – CFR 29 Part 1910, International Organization for Standardization (ISO) Hand Held Non-Electric Power Tools – Safety Requirements and applicable State and Local Regulations.



Read and understand tool manual before work starts to reduce risk of injury to operator, visitors, and tool.



Eye protection must be worn at all times, eye protection to conform to ANSI Z87.1.



Ear protection to be worn when exposure to sound, exceeds the limits of applicable Federal, State or local statutes, ordinances and/or regulations.



Practice safety requirements. Work alert, have proper attire, and do not operate tools under the influence of alcohol or drugs.



Respiratory protection to be used when exposed to contaminants that exceed the applicable threshold limit values required by law.



Air line hazard, pressurized supply lines and flexible hoses can cause serious injury. Do not use damaged, frayed or deteriorated air hoses and fittings.

Some dust created by sanding, grinding, drilling, and other construction activities contain chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- Lead from lead-based paints
- Crystalline silica from bricks and cement and other masonry products
- Arsenic and chromium from chemically treated lumber

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

SAFETY and OPERATING INSTRUCTIONS



Carefully Read and Understand the General and Grinder sections found in Tool Safety and Operating Guidelines (PN00001676) Before Handling or Using Tool.

Carefully Read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool. Products offered by Dynabrade are not to be modified, converted or otherwise altered from the original design.

Tool Intent: Extension Cut-Off tools are intended to be used by professional operators for cutting or trimming steel, composites, aluminum and other materials using 4" diameter by 0.035" thick Type 41 cut-off wheels with a 3/8" center hole.

DO NOT USE Tool for Anything Other Than Its Intended Applications.

Training: Proper care, maintenance, and storage of your air tool will maximize tools performance and reduce chance for accident.

Employer's Responsibility: Provide operators with safety instructions and training for safe use of tools and accessories.

Report to Your Supervisor any Condition of the Tool, Accessories or Operation you Consider Unsafe.

MAINTENANCE INSTRUCTIONS

Important: To keep tool safe, a Preventative Maintenance Program is recommended. The program should include inspection of the tool and all related accessories and consumables, including air lines, pressure regulators, filters, oilers, etc. (refer to CAGI B186.1 for additional maintenance information). If accessory or tool breakage occurs, investigate failure to determine the cause and correct before issuing tool for work. Use the following schedule as a starting point in developing a Preventative Maintenance Program. If tool does not operate properly (RPM, vibration, start/stop) after these scheduled checks or at any time, the tool must be repaired and corrected before returning tool to use.

INSTALLATION

- To ensure long life and dependable service, use a Closed Loop Air System and Filter-Regulator-Lubricator (FRL) as diagramed below.
- Each tool should have its own dedicated hose connected to an air supply FRL. Quick disconnects should be installed at the FRL in an effort to reduce contamination into the tool. Securely affix all fittings and hose assemblies.
- It is strongly recommended that all Dynabrade rotary vane air tools be used with a Filter-Regulator-Lubricator to minimize the possibility of misuse due to unclean air, wet air or insufficient lubrication. Dynabrade recommends the following: **10690** Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components.
- Dynabrade recommends 1 drop of air lube per minute for each 20 SCFM (example: if the tool specification states 40 SCFM, set the drip rate on the filter-lubricator to 2 drops per minute). **95842** Dynabrade Air Lube is recommended.

MAINTENANCE SCHEDULE

Maintenance schedules depend on the type and style of tool. Refer to page 3 to reference symbols associated with specific maintenance items/areas. Match maintenance schedules accordingly. See page 4 for any additional maintenance information.

Note: Turbine style air motors do not require oil.

Daily (every 8 hours):

- Inspect tool and accessories for damage or broken parts. Replace items as necessary to ensure proper operation and safety.
- **O** Lubricate motor as recommended. Use **95842** Dynabrade Air Lube (10W/NR). Apply 1 drop/minute of air lube per 20 SCFM.
- Check air line pressure with a gage. (MAX. 90 PSIG or 6.2 Bar operating pressure at the air inlet of the tool.)
- **W** Lubricate wick system and right angle gears through screw hole in right angle housing. Remove 55376 screw and apply 3 plunges of 95848 Gear Oil using 95541 Lubricant Applicator, replace screw after lubricating.
- Check tool for proper operation: If operating improperly or demonstrates unusual vibration, the tool must be serviced and problem corrected before further use.

Every 20 Hours/Once a Week (which ever comes first):

- **G** For tools without "wick system", lubricate right angle gears through lubricant fitting. Apply 1 plunger of **95544** Grease. Use **95541** Lubricant Gun. (Prime lubricant gun before use).

- Measure RPM (speed) by setting air pressure to 90 PSIG (6.2 Bar) at tool inlet, without accessory mounted, while the tool is running. Using tachometer, check spindle speed of the tool. A non-governed tool may exceed the RPM marked on the tool by 10% when operated at free speed with no accessories.
- If tool is running too fast: look for worn, damaged or missing governor, air control rings and silencer(s). Service as required.
- If tool is running too slow: look for malfunctioning governor, clogged inlet screen, silencer(s) or air stream. Service as required.

Note: Special care must be taken when servicing governors. Refer to specific tool manual for governor instructions and/or speed control devices. Governor assemblies made from molded plastic components are non-serviceable and must be replaced.

Every 50 Hours:

- **G** Lubricate planetary gears through gear case fitting with 3 plunges of **95544** Grease. Use **95541** Lubricant Gun. (Prime lubricant gun before use).

REPAIR

- Use only genuine Dynabrade replacement parts to ensure quality. To order replacement parts, specify Model#, Serial# and RPM of your air tool.
- Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters, ketones, chlorinated hydrocarbons or nitro carbons.
- Air tool markings must be kept legible at all times, if not, reorder housing and replace. User is responsible for maintaining specification information.

- **O** After maintenance is performed on tool, add a few drops of **95842** Dynabrade Air Lube to the tool inlet and start the tool a few times to lubricate air motor. Verify RPM (per 20 hr maintenance schedule), vibration and operation.

HANDLING & STORAGE

- Use of tool rests, hangers and/or balancers is recommended.
- Protect tool inlet from debris (see Notice below).
- **Do Not** carry tool by air hose or near the tool throttle lever.
- Store accessories in protective racks or compartments to prevent damage.
- Follow the handling instructions outlined in the operating instructions when carrying the tool and when changing accessories.
- Protect accessories from exposure to water, solvents, high humidity, freezing temperature and extreme temperature changes.

END OF USE/DISPOSAL

When tool has reached its end of useful service, disassemble tool into its primary components (i.e. steel, aluminum and plastic) and recycle or discard per local, state and/or federal regulations as to not harm the environment.


NOTICE

All Dynabrade air motors use the highest quality parts available and are manufactured to exacting tolerances. Air motor failures are often traced to lack of lubrication or unclean air supply. Compressed air can force dirt and other contaminants into motor bearings causing early failure. Contaminants can score cylinder wall and vanes resulting in reduced efficiency and power. Our warranty obligation is contingent upon proper use of our tools. Air motors which have been subjected to misuse, contaminated air or lack of lubrication will void warranty.

CLOSED LOOP AIR SYSTEM

Sloped in Direction of Air Flow


- Dynabrade Air Power Tools are designed to operate at 90 PSIG (6.2 Bar) maximum air pressure at the tool inlet, when the tool is running. Use recommended regulator to control air pressure.
- Ideally the air supply should be free from moisture. To facilitate removing moisture from air supply, the installation of a refrigerated air dryer after the compressor and the use of drain valves at each tool station is recommended.



Lubricator Setting

1 Drop/Minute per 20 SCFM

Dynabrade Nitro Series™ 4" Extension Cut-Off Grinder Complete Assembly



ITEM	P/N	DESCRIPTION	QTY
1	55355	SCREW	1
2	55356	OUTER FLANGE	1
3	55357	INNER FLANGE	1
4	55358	RETAINING RING	1
5	55359	WASHER	1
6	55360	GUARD	1
7	55362	WAVE WASHER	4
8	55363	R/A HOUSING LOCK RING	1
9	55364	SPINDLE LOCK NUT	1
10	55365	BEARING	1
11	55366	GEAR	1
12	55367	PIN	1
13	55368	BEARING	1
14	55369	WICK	1
15	55370	R/A HOUSING	1
16	55371	SCREW	1
17	55372	WASHER	1
18	55373	SPRING	1
19	55374	BUSHING	1
20	55375	LOCK BAR	1
21	55376	SCREW	1
22	55377	NUT	1
23	55378	SPRING	1
24	55379	SPINDLE LOCK SHAFT	1
25	55380	O-RING	1
26	55381	SPINDLE LOCK NUT	1
27	55382	PINION GEAR	1
28	55383	BEARING	2
29	55384	BUSHING	1
30	55385	LOCK NUT	1
31	55386	EXTENSION SHAFT	1
32	55387	EXTENSION HOUSING	1
33	55836	BEARING	1
34	55765	RETAINING RING	2
35	55766	COUPLER NUT	1
36	55767	COUPLER	1
37	55361	COUPLER NUT	1
38	55768	LOCK RING	1
39	55769	ADAPTER	1
40	55770	O-RING	1
41	55771	COLLAR	1
42	55772	BEARING	1
43	55773	FRONT END PLATE	1
44	55774	PIN	3
45	55775	VANE	4
46	55776	ROTOR	1
47	55777	CYLINDER	1
48	55778	REAR END PLATE	1
49	55779	BEARING	1
50	55780	O-RING	1
51	55781	MOTOR HOUSING	1
52	55782	VALVE STEM	1
53	55848	O-RING	1
54	55783	VALVE SPRING	1
55	55853	O-RING	1
56	55784	VALVE PLUG	1
57	55785	O-RING	1
58	55786	GRIP ASSEMBLY	1
58.1	55788	LABEL - BRANDING	1
58.2	55789	LABEL - PRODUCT SPECS.	1
59	55790	SCREW	1
60	55791	LEVER ASSEMBLY	1
61	55853	PIN	1
62	55793	MUFFLER	1
63	55794	EXHAUST COVER	1
64	55795	INLET BUSHING	1
65	55796	HEX KEY (NOT SHOWN)	1

KEY

O Oil: O₁ = Air Lube

A Adhesive: A₈ = Loctite #567

W Gear Oil: W₁ = 95848

T_x X = Torque Value (N•m)
(N•m x 8.85 = lb•in.)

Always follow adhesive manufacturers cleaning and priming recommendations.

ITEM	P/N	DESCRIPTION	QTY
59	55790	SCREW	1
60	55791	LEVER ASSEMBLY	1
61	55853	PIN	1
62	55793	MUFFLER	1
63	55794	EXHAUST COVER	1
64	55795	INLET BUSHING	1
65	55796	HEX KEY (NOT SHOWN)	1

MACHINE SPECIFICATIONS

Model	Speed	Power	Air Consumption	Weight	Length	Height
ECU4	14,000 RPM	1 hp (746 W)	40 SCFM (1,133 LPM)	4.1 lb. (1.9 kg)	14.75" (375 mm)	1.9" (49 mm)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. 1/4" (6 mm) • 90 PSIG

OPTIONAL ACCESSORIES



Dynabrade Air Lube

- Formulated for pneumatic equipment.
- Absorbs up to 10% of its weight in water.
- Prevents rust and formation of sludge.
- Keeps pneumatic tools operating longer with greater power and less down time.

Part No. 95842: 1 pt. (473 ml)

Part No. 95843: 1 gal. (3.8 L)



Air Line Assembly

- 40" Hose Assembly
- 3/8" I.D.
- Includes 1 male and 1 female fitting

Part No. 95771



Dynabrade Gear Oil

- Specifically formulated to saturate wick system to right angle gear head.
- Apply every 8 hours of operation into tool's lubrication fitting.


Part No. 95848: 2.5 oz. (74 ml) tube

Part No. 95541: Push-type grease gun

ADDITIONAL SAFETY AND OPERATING INSTRUCTIONS

Proper Accessory Mounting Procedure for 4", Type 41 Abrasive Wheel

With Power Source Disconnected from the Tool, Mount Compatible Accessory



Note: Ensure driving tabs of 55364 spindle lock nut are adjacent to and engage slot of 55357 inner flange.