



Installation and Operation Instructions EW2461 LED Magnet Mount Worklamp

IMPORTANT! Read all instructions before installing and using. Installer: This manual must be delivered to the end user. ECCO is not responsible for the misuse of our work light products by unauthorized personnel.

WARNING! Risk of fire and burns. Do not open, crush, expose to heat above 120°F(50°C), incinerate or short terminals. Do not store, use or charge in locations that may reach or exceed 120°F(50°C). Never charge while unattended. Do not expose battery to water or liquids. Follow manufacturer's instructions.



WARNING!

Failure to install or use this product according to manufacturer's recommendations may result in property damage, serious bodily/personal injury, and/or death to you and those you are seeking to protect!



Do not install and/or operate this safety product unless you have read and understand the safety information contained in this manual.

1. Proper installation combined with operator training in the installation, use, care and maintenance of vehicle equipment accessories is essential to ensure the safety of you and those you are trying to protect.
2. Exercise caution when working with live electrical connections.
3. Proper placement and installation are vital to the performance of this worklamp. Install this product so that output performance of the system is maximized and the controls are placed within convenient reach of the operator so that s/he can operate the system without losing eye contact with the work area.
4. It is the responsibility of the vehicle operator to ensure during use that all features of this product work correctly. In use, the vehicle operator should ensure the projection of the beam is not blocked by vehicle components (i.e., open trunks or compartment doors), people, vehicles, or other obstructions.
5. The manufacturer assumes no liability for any loss resulting from the use of this device.

NOTE: Black die cast Aluminum housing gets very hot to the touch after operating constantly for several hours.

Specifications:

Weight:	1.56 lbs. approx.
Output Power (Lumens):	431 raw/412 effective lm \pm 50 lm
Charging Voltage:	5 VDC (USB Connection)

Prior to use:

1. Fully charge the battery for 7.5 hours before first use.
2. The battery should be charged at least once every three months when not in regular use.
3. The red light indicates the unit is charging; the green light indicates that the unit is fully charged.
4. Only use the USB charger provided with this unit.
WARNING: INTENDED FOR USE ON STATIONARY VEHICLES ONLY. REMOVE AND STORE WHEN VEHICLE IS IN MOTION.

Installation Instructions:

1. Mount the unit on a flat, clean, dry surface.

Operating Modes - Single Color Models

1. 100% White
2. 30% White
3. SOS Flashing White
4. Off

Operating Modes - Dual Color Models

1. 100% White
2. 30% White
3. 100% Amber or Red
4. Quad Flash Amber or Red
5. Double Flash Amber or Red
6. Off

Press power button sequentially to select operating mode

