## Cordless rail drilling machine

## **RAIL.360**

Available in 6 different rail adapter versions: S49, S54, TRC68, UIC50, UIC54 and UIC60.

## Technical data

	Metric		Imperial
Annular cutting	Ø 12 - 36 mm		Ø 7/16" - 1 7/16"
Length	297 mm		11 11/16"
Width	125 mm		4 15/16"
Height	510 - 685 mm		20 1/16" - 27"
Stroke	230 mm		9 1/16"
Weight (incl. batt)	16 kg		35.3 lbs
Motor power	1300 W DC		35.1 A DC
Total power	1350 W E	C	36.5 A DC
Speed (no load)	506 rpm		
Speed (load 1300 W, 35	.1 A DC)	375 rpm	
Spindle (Weldon)	19,05 mn	n	3/4"
Battery capacity	37 V / 2,6 Ah Li-ion		

From 0% to 75% battery charge in 17 minutes! Battery charge 75% to 100% takes 58 minutes. Fully charged in 75 minutes.



## Voordelen:

- Suitable for processing rails;
- Powerful battery with charger;
- Powerful high torque DC motor;
- Multi-level electronic protection for optimal safety;
- Extremely short battery charging time;
- Detachable spindle and integrated tool cooling and lubrication;
- High precision height adjustment for:
  - Low maintenance;
  - Minimal wear correction.

