

7265CS

DuraTech® SRL with 60' Stainless Steel Cable and Side-payout Aluminum Housing

Features :

- 3/16" stainless steel cable lifeline with load-indicating swivel snap hook
- Side-payout design delivers smooth lifeline operation.
- Internal inertial braking system with dual disc brakes provides superior deceleration
- Lifeline assembly includes recoil spring to help reduce retraction lock-up
- Integrated lifeline hand-grip simplifies dorsal connection
- Stackable housing design and handle provide easy installation and storage
- Complies with ANSI Z359.14-2014

Material Specifications		Performance Specifications		Compliant With:	
Cable	3/16" stainless steel; 3,400 lb min. static strength	Static Strength	3,000 lb min.	ANSI	Z359.14-2014
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	ANSI SRL Class	Class B	OSHA	1926.502 and 1910.66
		Avg. Arrest Force	1,350 lb		
		Max. Arrest Force	1,800 lb		
		Max. Arrest Distance	54"		
		ANSI User Capacity	130 to 310 lb max.		
		OSHA User Capacity	130 to 310 lb max.		

Sizes & Part Numbers				
7227CS - 20'	7232CS - 30'	7268CS - 50'	7265CS - 60'	