

Specifications: Fluke 120B Series Industrial ScopeMeter handheld Oscilloscopes

Oscilloscope mode		
Vertical		
Frequency response - dc coupled	Without probes and test leads (with BB120)	123B: dc to 20 MHz (-3 dB) 124B and 125B: dc to 40 MHz (-3 dB)
	With STL120-IV 1:1 shielded test leads	DC to 12.5 MHz (-3 dB) / dc to 20 MHz (-6 dB)
	With VP41 10:1 Probe	123B: dc to 20MHz (-3 dB) 124B and 125B: dc to 40 MHz (-3 dB)
Frequency response - ac coupled (If roll off)	Without probes and test leads	<10 Hz (-3 dB)
	With STL120-IV 1:1 shielded test leads	<10 Hz (-3 dB)
	With VP41 10:1 Probe	<10 Hz (-3 dB)
Rise time, excluding probes, test leads	123B <17.5 ns 124B and 125B <8.75 ns	
Input impedance	Without probes and test leads	1 M Ω //20 pF
	With BB120	1 M Ω //24 pF
	With STL120-IV 1:1 shielded test leads	1 M Ω //230 pF
	With VP41 10:1 Probe	5 M Ω //15.5 pF
Sensitivity	5 mV to 200 V/div	
Analog bandwidth limiter	10 kHz	
Display modes	A, -A, B, -B	
Max. input voltage A and B	Direct, with test leads, or with VP41 Probe	600 Vrms Cat IV, 750 Vrms maximum voltage.
	With BB120	600 Vrms
Max. floating voltage, from any terminal to ground	600 Vrms Cat IV, 750 Vrms up to 400Hz	
Horizontal		
Scope modes	Normal, Single, Roll	
Ranges (normal)	Equivalent sampling	123B: 20 ns to 500 ns/div, 124B and 125B: 10 ns to 500 ns/div
	Real time sampling	1 μ s to 5 s/div
	Single (real time)	1 μ s to 5 s/div
	Roll (real time)	1s to 60 s/div
Sampling rate (for both channels simultaneously)	Equivalent sampling (repetitive signals)	Up to 4 GS/s
	Real time sampling 1 μ s to 60 s/div	40 MS/s
Trigger		
Screen update	Free run, on trigger	
Source	A, B	
Sensitivity A and B	@ DC to 5 MHz	0.5 divisions or 5 mV
	@ 40 MHz	123B: 4 divisions

		124B and 125B: 1.5 divisions
	@ 60 MHz	123B: N/A
		124B and 125B: 4 divisions
Slope	Positive, negative	
Advanced scope functions		
Display modes	Normal	Captures up to 25 ns glitches and displays analog-like persistence waveform
	Smooth	Suppresses noise from a waveform
	Glitch off	Does not capture glitches between samples
	Envelope	Records and displays the minimum and maximum of waveforms over time
Auto set (Connect-and-View™)	Continuous fully automatic adjustments of amplitude, time base, trigger levels, trigger gap, and hold-off. Manual override by user adjustment of amplitude, time base, or trigger level.	
Dual input meter		
The accuracy of all measurements is within \pm (% of reading + number of counts) from 18 °C to 28 °C. Add 0.1x (specific accuracy) for each °C below 18 °C or above 28 °C. For voltage measurements with 10:1 probe, add probe uncertainty +1%. More than one waveform period must be visible on the screen.		
Input A and input B		
DC voltage (VDC)		
Ranges	500 mV, 5 V, 50 V, 500 V, 750 V	
Accuracy	\pm (0.5% +5 counts)	
Common mode rejection (CMRR)	>100 dB @ dc, >60 dB @ 50, 60, or 400 Hz	
Full scale reading	5000 counts	
True-rms voltages (V ac and V ac+dc)		
Ranges	500 mV, 5 V, 50 V, 500 V, 750 V	
Accuracy for 5% to 100% of range (DC coupled)	DC to 60 Hz (V ac+dc)	\pm (1% +10 counts)
	1 Hz to 60 Hz (V ac)	\pm (1% +10 counts)
Accuracy for 5% to 100% of range (AC or dc coupled)	60 Hz to 20 kHz	\pm (2.5% +15 counts)
DC rejection (only VAC)	>50 dB	
Common mode rejection (CMRR)	>100 dB @ dc	
	>60 dB @ 50, 60, or 400 Hz	
Full scale reading	5000 counts, reading is independent of any signal crest factor.	
Peak		
Modes	Max peak, Min peak, or pk-to-pk	
Ranges	500 mV, 5 V, 50 V, 500 V, 2200 V	
Accuracy	Accuracy Max peak or Min peak	5% of full scale
	Accuracy Peak-to-Peak	10% of full scale
Full scale reading	500 counts	
Frequency (Hz)		
Ranges	123B: 1 Hz, 10 Hz, 100 Hz, 1 kHz, 10 kHz, 100 kHz, 1 MHz, 10 MHz, and 50 MHz	
	124B and 125B: 1 Hz, 10 Hz, 100 Hz, 1 kHz, 10 kHz, 100 kHz, 1 MHz, 10 MHz, and 70 MHz	
Frequency range	15 Hz (1 Hz) to 50 MHz in continuous autose	

Accuracy @1 Hz to 1 MHz	±(0.5% +2 counts)	
Full scale reading	10,000 counts	
RPM		
Max reading	50.00 kRPM	
Accuracy	±(0.5% +2 counts)	
Duty cycle (PULSE)		
Range	2% to 98%	
Frequency range	15 Hz (1 Hz) to 30 MHz in continuous autose	
Pulse width (PULSE)		
Frequency range	15 Hz (1 Hz) to 30 MHz in continuous autose	
Full scale reading	1000 counts	
Amperes (AMP)		
With current clamp	Ranges	Same as V dc, V ac, V ac+dc, or PEAK
	Scale factors	0.1 mV/A, 1 mV/A, 10 mV/A, 100 mV/A, 400 mV/A, 1 V/A, 10 mV/mA
	Accuracy	Same as V dc, V ac, V ac+dc, or PEAK (add current clamp uncertainty)
Temperature (TEMP) with optional temperature probe		
Range	200 °C/div (200 °F/div)	
Scale factor	1 mV/°C and 1 mV/°F	
Accuracy	As V dc (add temp. probe uncertainty)	
Decibel (dB)		
0 dBV	1 V	
0 dBm (600 Ω /50 Ω)	1 mW referenced to 600 Ω or 50 Ω	
dB on	V dc, V ac, or Vac+dc	
Full scale reading	1000 counts	
Crest factor (CREST)		
Range	1 to 10	
Full scale reading	90 Counts	
Phase		
Modes	A to B, B to A	
Range	0 to 359 degrees	
Resolution	1 degree	
Power (125B only)		
Configurations	1 phase / 3 phase 3 conductor balanced loads (3 phase: fundamental component only, AUTASET mode only)	
Power factor (PF)	Ratio between watts and VA range - 0.00 to 1.00	
Watt	RMS reading of multiplying corresponding samples of input A (volts) and input B (amperes)	
	Full scale reading	999 counts
VA	Vrms x Arms	
	Full scale reading	999 counts
VA reactive (var)	$\sqrt{((VA)^2 - W^2)}$	
	Full scale reading	999 counts
Vpwm		

Purpose	To measure on pulse width modulated signals, like motor drive inverter outputs	
Principle	Readings show the effective voltage based on the average value of samples over a whole number of periods of the fundamental frequency	
Accuracy	As Vrms for sinewave signals	
Input A to common		
Ohm (Ω)		
Ranges	123B and 124B	500 Ω , 5 k Ω , 50 k Ω , 500 k Ω , 5 M Ω , 30 M Ω
	125B	50 Ω , 500 Ω , 5 k Ω , 50 k Ω , 500 k Ω , 5 M Ω , 30 M Ω
Accuracy	$\pm(0.6\% + 5 \text{ counts})$ 50 Ω $\pm(2\% + 20 \text{ counts})$	
Full scale reading	50 Ω to 5 M Ω - 5000 counts, 30 M Ω - 3000 counts	
Measurement current	0.5 mA to 50 nA, decreases with increasing ranges	
Open circuit voltage	<4 V	
Continuity (Cont)		
Beep	<(30 Ω \pm 5 Ω) in 50 Ω range	
Measurement current	0.5 mA	
Detection of shorts of	$\geq 1 \text{ ms}$	
Diode		
Measurement voltage	@0.5 mA	>2.8 V
	@open circuit	<4 V
Measurement current	0.5 mA	
Polarity	+ on input A, - on COM	
Capacitance (CAP)		
Ranges	50 nF, 500 nF, 5 μ F, 50 μ F, 500 μ F	
Full scale reading	5000 counts	
Measurement current	500 nA to 0.5 mA, increases with increasing ranges	
Advanced meter functions		
Zero Set	Set actual value to reference	
AutoHold (on A)	Captures and freezes a stable measurement result. Beeps when stable. AutoHold works on the main meter reading, with thresholds of 1 Vpp for AC signals and 100 mV for DC signals.	
Fixed decimal point	Activated by using attenuation keys	
Cursor Readout (124B and 125B)		
Sources	A, B	
Single vertical line	Average, min and max readout	
	Average, min, max and time from start of readout (in ROLL mode; instrument in HOLD)	
	Min, max and time from start of readout (in RECORDER mode; instrument in HOLD)	
Dual vertical lines	Harmonics values in POWER QUALITY mode.	
	Peak-peak, time distance and reciprocal time distance readout	
Dual horizontal lines	Average, min, max and time distance readout (in ROLL mode; instrument in HOLD)	
	High, low and peak-peak readout	
Rise or fall time	Transition time, 0%-level and 100%-level readout (manual or auto leveling; auto leveling only)	

possible in single channel mode)

Accuracy As oscilloscope accuracy

Recorder

The recorder captures meter readings in Meter Recorder mode or continuously captures waveform samples in Scope Recorder mode. The information is stored on internal memory or on optional SD card (with the 125B or 124B).

The results are displayed as Chart recorder display that plots a graph of min and max values of Meter measurements over time or as a waveform recorder display that plots all the captured samples.

Meter readings

Measurement Speed Maximum 2 measurement/s

Record Size (min, max, average) 2 M readings for 1 channel

Recorded Time Span 2 weeks

Maximum number of events 1024

Waveform record

Maximum sample rate 400 K sample/s

Size Internal memory 400 M samples Recorded Time

Span internal memory 15 minutes at 500 μ s/div
11 hours at 20 ms/div

Record Size SD card 1.5 G samples

Recorded Time Span SD card 11 hours at 500 μ s/div
14 days at 20 ms/div

Maximum number of events 64

Power Quality (125B only)

Readings Watt, VA, var, PF, DPF, Hz

250 W to 250 MW, 625 MW, 1.56 GW

Watt, VA, var ranges (auto) When selected: total (% r) $\pm(2\% + 6 \text{ counts})$

When selected: fundamental (% f) $\pm(4\% + 4 \text{ counts})$

DPF 0.00 to 1.00

PF 0.00 to 1.00, ± 0.04

Frequency range 10.0 Hz to 15.0 kHz
40.0 Hz to 70.0 Hz

Number of Harmonics DC to 51

Readings / Cursor readings (fundamental 40 Hz to 70 Hz) Vrms / Arms /Watt Each harmonic from fundamental maybe selected for individual readings

Includes frequency of fundamental, phase Angle and K-factor (in Amp and Watt)

BusHealth tester (Fluke 125B only)

Type	Subtype	Protocol
AS-i	NEN-EN50295	
CAN	ISO-11898	
Interbus S	RS-422	EIA-422
Modbus	RS-232	RS-232/EIA-232
	RS-485	RS-485/EIA-485
Foundation Fieldbus	H1	61158 type 1, 31.25 kBit
Profibus	DP	EIA-485
	PA	61158 type 1

Miscellaneous

Display	Type	5.7-inch color active matrix TFT
	Resolution	640 x 480 pixels
Waveform Display	Vertical	10 div of 40 pixels
	Horizontal	12 div of 40 pixels
Power	External	Via Power Adapter BC430
	Input voltage	10 V DC to 21 V DC
	Power consumption	5 W typical
	Input connector	5 mm jack
	Internal	Via Battery Pack BP290
	Battery power	Rechargeable Li-Ion 10.8 V
	Operating time	7 hours with 50% backlight brightness
Power	Charging time	4 hours with test tool off, 7 hours with test tool on
	Allowable ambient temp	0 to 40 °C (32 to 104 °F) during charging
	Memory	Internal memory can store 20 data sets (screen waveform and setup) Micro SD card slot with optional SD card (max size of 32 GB)
Mechanical	Size	259 x 132 x 55 mm (10.2 x 5.2 x 2.15 in)
	Weight	1.4 kg (3.2 lb) including battery pack
Interface	Optically isolated	Transfer screen copies (bitmaps), settings and data
	USB to PC/laptop	OC4USB optically isolated USB adapter/cable, (optional), using FlukeView® software for Windows®.
	Optional WiFi adapter	Fast transfer of screen copies (bitmaps), settings and data to PC/laptop, tablet, smartphone, etc. A USB port is provided for attaching the WiFi dongle. Do not use the USB port with a cable for safety reasons.
Environmental	MIL-PRF-28800F, Class 2	
Temperature	Battery Operation	0 to 40 °C (32 to 104 °F)
	Power Adapter Operation	0 to 50 °C (32 to 122 °F)
	Storage	-20 to 60 °C (-4 to 140 °F)
Humidity (Operating)	@ 0 to 10 °C (32 to 50 °F)	Non-condensing
	@ 10 to 30 °C (50 to 86 °F)	95%
	@ 30 to 40 °C (86 to 104 °F)	75%
	@ 40 to 50 °C (104 to 122 °F)	45%
Storage	@ -20 to 60 °C (-4 to 140 °F)	Non-condensing
Altitude	Operating at 3 km (10,000 feet)	CAT III 600 V
	Operating at 2 km (6,600 feet)	CAT IV 600 V
	Storage	12 km (40,000 feet)
EMC electromagnetic compatibility	International	IEC 61326-1: Industrial, CISPR 11: Group 1, Class A

	Korea (KCC)	Class A Equipment (Industrial Broadcasting & Communication Equipment)
	USA (FCC)	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.
Wireless radio with adapter	Frequency range	2412 MHz to 2462 MHz
	Output power	<100 mW
Enclosure protection	IP51, ref: EN/IEC60529	
Safety	General	IEC 61010-1: Pollution Degree 2
	Measurement	IEC 61010-2-033: CAT IV 600 V/CAT III 750 V
Max. input voltage input A and B	Direct on input or with leads	600 Vrms CAT IV for derating
	With Banana-to-BNC Adapter BB120	600 Vrms for derating
	Max. floating voltage from any terminal to ground	600 Vrms Cat IV, 750 Vrms up to 400 Hz