

# Safety Data Sheet

MM-030

Complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

Preparation: September 23, 2008  
Review / Revision: May 2014

## 1. PRODUCT IDENTIFICATION

**Part No. and Description:** MM-STD, Metal Marker-Yellow

**Product Class:** Solvent based marker

**Formula:** A419M

**Manufacturer:** ITW Dykem

**Distributor:** Goodson Tools & Supplies

**HMS:** Health - 2      Flammability - 2      Reactivity - 0      Personal Protection - B

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components					Other Limits	
	<u>Chemical Identity, Common Name</u>	<u>CAS No.</u>	<u>OSHA PEL</u>	<u>ACGIH-TLV</u>	<u>Recommended</u>	<u>% (Opt)</u>
Aromatic Hydrocarbon	64742-95-6	TWA 100 ppm	TWA 100 ppm	No Data	20-30	
Titanium Dioxide	13463-67-7	TWA 10 mg/m3	TWA 10 mg/m3	Nuisance dust*	20-30	
Clay, Silica	1332-58-7	TWA 15 mg/m3	TWA 15 mg/m3	Nuisance dust*	15-25	
1,2,4 Trimethyl Benzene	95-63-6	TWA 100 ppm	TWA 100 ppm	No Data	1-10	
Organic Yellow(s)	6358-31-2	TWA 10 mg/m3	TWA 10 mg/m3	Nuisance dust*	1-10	
	6528-34-3					
Xylene	1330-20-7	TWA 100 ppm	TWA 100 ppm	No Data	1-5	

\*Nuisance dust as free dust only, not as bound in paint or ink.

## 3. HAZARDS IDENTIFICATION

**Emergency overview - Yellow opaque thick viscosity liquid with aromatic odor. Warning! Combustible liquid and vapor. Keep away from heat sparks and flames. May cause eye, skin and respiratory tract irritation. If swallowed do not induce vomiting. Get immediate medical attention.**

### Potential Health Effects

**Eyes:** Liquid is moderately irritating to the eyes.

**Skin:** Liquid is mildly irritating to the skin.

**Ingestion:** Ingestion of liquid may cause vomiting.

**Inhalation:** High concentration of vapors may produce irritation of the respiratory tract, headache, dizziness, and nausea.

### Chronic Health Effects

Prolonged or repeated contact may cause skin sensitization or dermatitis. Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage. Intentional misuse by deliberately concentrating or inhaling this product may be harmful or fatal.

## 4. FIRST AID MEASURES

**Eyes :** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Skin:** Flush skin with plenty of water. Remove contaminated clothing and shoes.

**Ingestion:** If large quantities of this material are swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

## 5. FIRE FIGHTING MEASURES

**Flash Point (Method Used):** 108°F    **Flammable Limits:**    **LEL:** 1.9    **UEL:** 12.6

**Extinguishing Media:** Use water fog, foam, dry chemical or CO<sub>2</sub>. Use water spray to cool fire-exposed containers and to protect personnel.

**Special Fire Fighting Procedures:** Keep containers cool and vapors down with water spray. Prevent spill from entering drains, sewers, streams or other bodies of water. If run-off occurs, notify proper authorities. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Vapors are heavier than air and may travel along ground, or be moved by ventilation and be ignited by ignition source.

## 6. ACCIDENTAL RELEASE MEASURES

**Small Spill:** Absorb liquid with non-combustible floor absorbent and place in non-leaking container; seal properly and dispose of properly in compliance with federal, state, and local regulations.

**Large Spill:** Evacuate area of unprotected personnel. Eliminate all ignition sources. Stop spill at source if safe to do so. Handling equipment must be grounded to prevent sparking. Prevent spill from entering drains, sewers, streams or other bodies of water. If run-off occurs, notify proper authorities. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Dispose of properly in compliance with federal, state, and local regulations.

## 7. HANDLING AND STORAGE

**Handling:** Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flames, static electricity, or other sources of ignition. Many hot organic chemical vapors or mists are susceptible to sudden spontaneous combustion when mixed with air. Ignition may occur at temperatures below those published in the literature as "autoignition" or ignition temperatures. Ignition temperatures decrease with increasing vapor volume and vapor volume and vapor/air contact time, and are influenced by pressure changes. Ignition of organic chemical vapors may occur at typical elevated-temperature process conditions, especially in processes operating under vacuum if subjected to sudden ingress of air, or outside process equipment operating under elevated pressure if sudden escape of vapors or mists to the atmosphere occurs. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

**Storage:** Keep away from heat, sparks and open flames. Keep out of reach of children. Keep container tightly sealed when not in use. Store in cool, well-ventilated place away from incompatible materials. Information on this Safety Data Sheet refers to ink used in pens and markers, however, it applies to these inks in bulk. The inks are contained in capillary or valve reservoirs and will not spill or leak under normal conditions.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Respiratory Protection (Specify Type)-**

Not usually necessary. Use with adequate ventilation. Use NIOSH/MSHA approved respirator if PELs or TLVs are exceeded.

### **Engineering Controls:**

**Local Exhaust:** Not Usually needed    **Special:** None

**Mechanical (General):** Yes    **Other:** None

**Protective Gloves:** Chemical resistant gloves if skin contact is possible (consult your safety equipment supplier).

**Eye Protection:** Not normally required if used as intended. Wear chemical splash goggles in compliance with OSHA regulation if splashing is possible.

**Other Protective Clothing or Equipment:** Not usually necessary. For bulk material, if direct contact is possible, wear apron, boots, face shield, etc. as needed.

**Work/Hygienic Practices:** Follow label instructions. Wash hands after use and before eating, drinking, smoking, using restrooms, etc.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** 318 to 338°F

**Vapor Pressure (mm-HG @ 70°F):** No Data

**Vapor Density (Air=1):** Greater than 1

**Solubility in Water:** Negligible

**Appearance and Odor:** Yellow opaque thick viscosity liquid with aromatic odor.

**VOC:** This product contains 351 grams per liter or 28.73% by weight VOC's.

**Specific Gravity (H<sub>2</sub>O=1) @70°F:** >1

**Melting Point:** No Data

**Evaporation Rate (Butyl Acetate = 1):** Less than 1

**pH:** No Data

## 10. STABILITY AND REACTIVITY

**Chemical Stability :** Stable

**Conditions to Avoid:** None known.

**Incompatibility (Materials to Avoid):** Strong oxidizing and reducing agents, strong alkalis and strong acids.

**Hazardous Decomposition or Byproducts:** Carbon dioxide, carbon monoxide, smoke, soot and various organic oxidation by-products.

**Hazardous Polymerization:** Will not occur.

**Conditions to Avoid:** No Data.

## 11. TOXICOLOGICAL INFORMATION

Please refer to Section 3 for available information on potential health effects.

## 12. ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION (Not meant to be all inclusive)

### Domestic Highway (Containers < 1 Quart are ORM-D) Domestic Air Shipments (Pens)

**Proper Shipping Name:** Paint/Ink

**Proper Shipping Name:** Consumer Commodity

**Hazard Class/Subsidiary Hazard:** 3

**Hazard Class/Subsidiary Hazard:** 9

**UN/NA No:** UN1263

**UN/NA No:** I.D. 8000

**Packing Group:** III

**Packing Group:** None

**Label Required:** Combustible Liquid (2)

**Label Required:** Class 9

## 15. REGULATORY INFORMATION (Not meant to be all inclusive - selected regulations represented)

### U.S. Federal Regulations:

**Carcinogenicity:** NTP = No

**IARC Monographs = No**

**OSHA Regulated = No**

**OSHA:** Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

**Section 313:** This product contains Xylene (1330-20-7) and 1,2,4 Tri Methyl Benzene (95-63-6) which are listed and may require reporting under SARA Title III Sec. 313 if used over the threshold reporting quantity. This information must be included in all SDS's that are copied and distributed for this material.

### INTERNATIONAL REGULATIONS:

**CANADIAN WHMIS:** Not WHMIS controlled (pens) Bulk: Class B2, D2A

### STATE REGULATIONS:

#### CALIFORNIA PROPOSITION 65:

This product contains a chemical known to the State of California to cause cancer. Benzene, Ethyl benzene. This product contains chemicals known to the State of California to cause birth defects or other reproductive harm. Toluene, Benzene.

## 16. OTHER INFORMATION

**Warning!** The use of this product is beyond the control of the manufacturer and distributor; therefore, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The user must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials. The manufacturer and distributor warrant only that this product meets the specifications for such product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER OF THIS PRODUCT. THE MANUFAC-

TURER AND DISTRIBUTOR SHALL BE IN NO WAY RESPONSIBLE FOR THE IMPROPER USE OF THIS PRODUCT. The sole and exclusive remedy against the manufacturer and distributor for breach of warranty shall be reimbursement of the purchase price of the product in the event that a defective condition of the product shall be found to exist. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.