



## Impact wrench, extra short

· Maximum loosening torque: 461 Nm · Square, solid 10 mm (3/8 inch) · Single hammer striking mechanism

Article no.: 9011M

EAN: 4000896201570

### Product information

- Maximum loosening torque: 461 Nm
- **Extremely compact construction enables working in areas with restricted access**
- One-hand operation for right and left handed operators
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- **Extra short – only 92 mm**
- Single hammer striking mechanism
- Air connection inlet: Inside thread 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 375 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 101.3 db(A) Lp W
- Vibration acceleration: 7.78 m/s<sup>2</sup>
- Loosening torque (max) determined with screw size M: 13
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: Square, solid 10 mm (3/8 inch)
- Net weight: 1.24 kg
- Tightening torque max.: 461 Nm
- Maximum loosening torque: 461 Nm
- Sound pressure level: 90.3 dB(A) Lp A
- Revolutions per minute: 6500
- Air requirement: 85.2 l/min (1.4 l/sec)

### TECHNICAL DATA

- **Air inlet thread** : Inside thread 12.91 mm (1/4")
- **Air requirement l/min** : 85.2 l/min
- **Coupler plug** : nominal size 7.2 (included)
- **Forward/reverse** : three-stage (forward), single-stage (reverse)
- **Handle** : Cold insulated handle
- **Hose diameter (recommended)** : 10 mm
- **Loosening torque max.** : 461 Nm
- **Net weight** : 1.24 kg
- **Output** : Square, solid 10 mm (3/8 inch)
- **Recommended torque** : 375 Nm
- **Revolutions per minute** : 6500
- **Screw size M** : 13 M
- **Sound power level** : 101.3 db(A) Lp W
- **Sound pressure level** : 90.3 dB(A) Lp A
- **Striking mechanism (type)** : Single hammer striking mechanism
  
- **Tightening torque max.** : 461 Nm
- **Vibration acceleration** : 7.78 m/s<sup>2</sup>
- **Working pressure (bar)** : 6.3 bar