



## Impact wrench

· Maximum loosening torque: 1890 Nm · Square, solid 20 mm (3/4 inch) · Powerful twin hammer mechanism

**Article no.:** 9013M

**EAN:** 4000896212347

## Product information

### Application:

Application on SUVs, transport vehicles, trucks, agricultural machinery as well as for industrial machine and naval construction

- Maximum loosening torque: 1890 Nm
- Only 2.1 kg
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- **20 mm (3/4") impact wrench in 12.5 mm (1/2") housing size**
- Powerful twin hammer mechanism
- Air connection inlet: Inside thread 16.41 mm (3/8")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 922 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 93 db(A) Lp W
- Vibration acceleration: 7.47 m/s<sup>2</sup>
- Loosening torque (max) determined with screw size M: 32
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: Square, solid 20 mm (3/4 inch)
- Net weight: 2.1 kg
- Tightening torque max.: 1085 Nm
- Maximum loosening torque: 1890 Nm
- Sound pressure level: 104 dB(A) Lp A
- Revolutions per minute: 7300
- Air requirement: 153 l/min (2.5 l/sec)

# TECHNICAL DATA

- **Air inlet thread** : Inside thread 16.41 mm (3/8")
- **Air requirement l/min** : 153 l/min
- **Coupler plug** : Nominal size 7.2 (included)
- **Forward/reverse** : three-stage (forward), single-stage (reverse)
- **Handle** : Cold insulated handle
- **Hose diameter (recommended)** : 10 mm
- **Loosening torque max.** : 1890 Nm
- **Net weight** : 2.1 kg
- **Output** : ■ 20 = 3/4"
- **Recommended torque** : 922 Nm
- **Revolutions per minute** : 7300
- **Screw size M** : 32 M
- **Sound power level** : 93 db(A) Lp W
- **Sound pressure level** : 104 dB(A) Lp A
- **Striking mechanism (type)** : Powerful twin hammer mechanism
- **Tightening torque max.** : 1085 Nm
- **Vibration acceleration** : 7.47 m/s<sup>2</sup>
- **Working pressure (bar)** : 6.3 bar