

# Why is Hutchins Better?

Unlike imported sanders, Hutchins is an innovator in sanding technology. This means we constantly improve and re-design our sanders to offer the latest advances for performance, productivity and value. When you purchase a Hutchins sander, you will own it for your entire career. Only Hutchins offers a no-hassle, no strings attached flat rate repair program allowing you to keep sanding with your Hutchins sander long after the imported ones are thrown in the trash! Hutchins sanders may cost a little more initially because American made quality doesn't come cheap but in the long run, your Hutchins sander is built to make you money! After all, isn't that what it's all about?

ProFinisher™-Orbital Sanders

Legacy-Random Orbital Sanders

Legacy-Straightline Sanders

**Legacy-Orbital Sanders** 

Legacy-Rotary Sanders

Speed Files

Accessories



When you see this symbol, the corresponding sanders are safe for use on all surfaces including Aluminum.

## **PROFINISHER™ SANDERS**

### ProFinisher<sup>M</sup>-Random Orbitals





"For Aluminum Only" (Part No. 1529A) Composite red trigger available for newly purchased ProFinishers<sup>™</sup> - Use it to alert your shop to use the sander only on Aluminum surfaces

ProFinisher<sup>™</sup> Sanders by Hutchins offer cutting edge technology at an affordable price. All ProFinisher<sup>™</sup> sanders are made in America and deliver performance you'd expect from Hutchins Manufacturing. All ProFinisher™ sanders can accommodate 5" or 6" sanding pads (except for 3" models).

### ProFinisher™ 500 Series - 3/32 Offset

- Random Orbital sanders with a 3/32" offset are generally used for pre and post paint procedures.
- The fine orbit allows precise cut control and minimal scratch pattern.
- Preferred by painters world-wide, these sanders are the choice when sanding primers, topcoats or clears.

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
500	6" PSA	10.7CFM	12,000 RPM	81 dBa	3lbs	No		No
500H	6" Hook	10.7CFM	12,000 RPM	81 dBa	3lbs	No		No
503	3" Hook	10.7CFM	12,000 RPM	81 dBa	3lbs	No		No
510*	6" Hook Multi-hole	10.7CFM	12,000 RPM	84 dBa	3lbs	Self-Gen		1"
520**	6" Hook Multi-hole	10.7CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"
523**	3" Hook 3-hole	10.7CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"















### ProFinisher™ 600 Series - 3/16 Offset

- Random Orbital sanders with a 3/16" offset are generally used for all-around sanding tasks.
- Whether you plan to shape fillers & putties, feather-edge panels, or prep for paint, these • sanders will perform a broad array of tasks.
- If your budget only allows for one sander, the 3/16" offset should be your choice. ٠

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
600	6" PSA	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
600H	6" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
603	3" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
610*	6" Hook Multi-hole	10.7 CFM	12,000 RPM	84 dBa	3lbs	Self-Gen		1"
620**	6" Hook Multi-hole	10.7 CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"
623**	3" Hook 3-hole	10.7 CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"

### ProFinisher<sup>™</sup> 700 Series - 5/16 Offset

- When time is money and you want the fastest sander available; • turn to 5/16" offset sanders.
- These sanders deliver the fastest cut (up to 30% faster) while • maintaining low vibration for exceptional operator comfort and safety.

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
700	6" PSA	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
700H	6" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
703	3" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
710*	6" Hook Multi-hole	10.7 CFM	12,000 RPM	84 dBa	3lbs	Self-Gen		1"
720**	6" Hook Multi-hole	10.7 CFM	12,000 RPM	84 dBa	3lbs	Vacuum		1"
723**	3" Hook 3-hole	10.7 CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"



### ProFinisher™ Random Orbital Accessories

#### **Replacement Pads**

Part	Description
No.	
750	Low Profile 5" PSA Pad (optional)
751	Low Profile 5" Hook Pad (optional)
752	Vacuum, Low Profile 5" Hook Pad (optional)
760	Low Profile 6" PSA Pad
761	Low Profile 6" Hook Pad
762	Vacuum, Low Profile 6" Hook Pad
5101	1" Hook Pad for Models: 503, 603 & 3501 (optional)
5103	3" Hook Pad for Models: 503, 603 & 3501
5143	3" 3-Hole Vacuum Hook Pad for Models: 523 & 623

#### Accessories

Part No.	Description
780	Coaxial Hose Assembly
800	Pad Wrench
810	Vacuum Conversion Kit **
850	3/32" Offset Replacement Motor
860	3/16" Offset Replacement Motor
870	5/16" Offset Replacement Motor
1350-4	Disposable Dust Bag Complete
1529A	"For Aluminum Only" Red ProFinisher Trigger
5301-2	Connector (1 <sup>1/2</sup> " OD Vac line)
5301-5	ProFinisher™ Connector (1" OD Vac line)





\*\* Models 520, 523, 620, 623, 720, 723 & 810 Kit require either 5301-2 or 5301-5 to complete vacuum connection

> MADE IN THE USA





700







\* These models require optional accessories in order to function completely. See ProFinisher™ Accessories for details.







ProFinisher™ Orbital Sanders

ProFinisher<sup>™</sup> Sanders by Hutchins offer cutting edge technology at an affordable price. All ProFinisher<sup>™</sup> sanders are made in America and deliver performance you'd expect from Hutchins Manufacturing.

Orbital Action Sanders are versatile and adapt to every surface preparation need. Developed in the early 50's, this style of sander still is preferred for marine, industrial, and automotive applications. Because the fixed pad orbits an offset counterweight, fast sanding and smooth finish results can be expected.

- 3/32" offset orbitals sanders are used mainly for pre & post paint operations and are generally used for wet • sanding applications.
- Smaller rectangular orbit allows better sanding access for bumpers, recessed areas, and new panel prep.
- Sanders used standard 2 3/4" Velcro sandpaper rolls.
- Velcro pads securely hold scuff pads for easy new panel prep. •

Part No.	Offset	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
504	3/32"	2 3/4" x 4" Hook	10.7 CFM	12,000 RPM	81 dBa	1lb 9oz	No		No
505	3/32"	2 3/4" x 5 1/2" Hook	10.7 CFM	12,000 RPM	81 dBa	1lb 9oz	No		No
508	3/32"	2 3/4" x 8" Hook	10.7 CFM	12,000 RPM	81 dBa	1lb 10oz	No		No
525**	3/32"	2 3/4" x 5 1/2" VA Hook	10.7 CFM	12,000 RPM	81 dBa	1lb 9oz	Vacuum		1"
528**	3/32"	2 3/4" x 8" VA Hook	10.7 CFM	12,000 RPM	81 dBa	1lb 10oz	Vacuum		1"

### ProFinisher™ Orbital Accessories

#### **Replacement Pads**

Part	Description
No.	
740	2 3/4" x 4" PSA Pad (Model 504)
741	2 3/4" x 4" Hook Pad (Model 504)
754	2 3/4" x 5 1/2" PSA Pad (Model 505)
755	2 3/4" x 5 1/2" Hook Pad (Model 505)
756	2 3/4" x 8" PSA Pad (Model 508)
757	2 3/4" x 5 1/2" VA Hook Pad (Model 525)
758	2 3/4" x 8" Hook Pad (Model 508)
759	2 3/4" x 8" VA Hook Pad (Model 528)

#### Accessories

Part No.	Description
780	Coaxial Hose Assembly
1344-2	Pad Removal Allen Wrench
1529A	"For Aluminum Only" Red ProFinisher Trigger
5301-2	Connector (1 <sup>1/2</sup> " OD Vac line)
5301-5	ProFinisher™ Connector (1" OD Vac line)

\*\* Models 525 & 528 require either 5301-2 or 5301-5 to complete the vacuum connection.



"For Aluminum Only"-1529A Composite red trigger available for newly purchased ProFinishers™ - Use it to alert your shop to use the sander only on Aluminum surfaces









## LEGACY SANDERS

## Random Orbital Sanders

Legacy Sanders by Hutchins are the product of 65 years of engineering know-how and a dedication to manufacturing the best sanders available. All Legacy Sanders are made in America and are designed to deliver exceptional performance for years of trouble-free service. All Legacy Random Orbital Sanders have built-in pad release buttons and can accommodate 5", 6", or 8" sanding pads.

### Finishing Sanders - 3/32 Offset

- Legacy Random Orbit Sanders with a 3/32" offset are generally used for pre and post paint procedures.
- The fine orbit allows precise cut control and minimal scratch pattern.
- Available in conventional, vacuum or wet-sanding; these sanders are the choice when sanding primers, topcoats or clears in automotive, commercial or industrial applications.

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
3500	6" PSA	11 CFM	10,000 RPM	80 dBa	2lb 5.4oz	No		No
3501	3" Hook	11 CFM	10,000 RPM	80 dBa	1lb 11.2oz	No	5101 (1" pad)	No
3950*	6" PSA 6-hole	11 CFM	10,000 RPM	80 dBa	3lb 6oz	Vacuum		1"
4500	6" PSA	9.8 CFM	10,000 RPM	79 dBa	3lb 5oz	No		No
4950	6" PSA 6-hole	9.8 CFM	10,000 RPM	86 dBa	3lb 11oz	Vacuum	5304-1	1 <sup>1/2</sup> "
8950	6" PSA 6-hole	8.5 CFM	10,000 RPM	83 dBa	4lb 2oz	Self-Gen	5859/1350-4	1 <sup>1/2</sup> "

80 dBa

2lb 7.5oz









### Water Sanders

7544 6" Hook

1301-1

No

### General Purpose - 3/16 Offset

11 CFM

 Legacy Random Orbit Sanders with a 3/16" offset are generally used for all-around sanding tasks.

10,000 RPM

 Available in conventional, vacuum or wet-sanding; these sanders are the choice when sanding or shaping fillers & putties, feather-edging panels, or prep for paint, these sanders will perform a broad array of tasks and will deliver years of worry-free operation.

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
3560	6" PSA	11 CFM	10,000 RPM	84 dBa	3lb 5.4oz	No		No
3960*	6" PSA 6-hole	11 CFM	10,000 RPM	82 dBa	3lb 6oz	Vacuum		1"
4560	6" PSA	9.8 CFM	10,000 RPM	79 dBa	3lb 5oz	No		No
4960	6" PSA 6-hole	9.8 CFM	10,000 RPM	84 dBa	3lb 10oz	Vacuum	5304-1	1 <sup>1/2</sup> "
8960	6" PSA 6-hole	8.5 CFM	10,000 RPM	83 dBa	4lb 2oz	Self-Gen	5859/1350-4	1 <sup>1/2</sup> "
Water Sanders								
7545	6" Hook	11 CFM	10,000 RPM	80 dBa	2lb 7.5oz	No	1301-1	No

\*For hook-type tools not listed, add "H" to the sander part number (i.e. 3560H comes with a hook-pad instead of PSA)



No















## **Random Orbital Sanders**



Legacy Sanders by Hutchins are the product of 65 years of engineering know-how and a dedication to manufacturing the best sanders available. All Legacy Sanders are made in America and are designed to deliver exceptional performance for years of trouble-free service. All Legacy Random Orbital Sanders have built-in pad release buttons and can accommodate 5", 6", or 8" sanding pads.

### Industrial Aggressive Sanders

- Legacy Industrial Random Orbit Sanders are designed to deliver the fastest, most comfortable sanders while still affording years of worry-free operation.
- Due to an advanced motor design, these sanders deliver the fastest cut (up to 35% faster than conventional 3/16" offset sanders) while maintaining low vibration for exceptional operator comfort and safety.
- · Available in conventional, vacuum or wet-sanding.
- Accepts 5", 6" and 8" pads

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
3570	6" PSA	8.5 CFM	13,000 RPM	84 dBa	3lb 6oz	No		No
3970*	6" Hook 6-hole	8.5 CFM	13,000 RPM	80 dBa	3lb 6oz	Vacuum		1"
8970	6" Hook 6-hole	8.5 CFM	13,000 RPM	83 dBa	4lb 2oz	Self-Gen	5859/1350-4	1 <sup>1/2</sup> "

7547

3570



### Water Sanders

7	547	6" Hook 6-hole	11 CFM	13,000 RPM	80 dBa	2lb 7.5oz	No	1301-1	No

### Legacy Sander Accessories

#### **Replacement Pads**

Part No.	Description
5028	Vacuum, 8" PSA Pad
5028H	Vacuum, 8" Hook Pad
5101	1" Hook Pad
5103	3" Hook Pad
5108	8" PSA Pad
5108H	8" Hook Pad
5135	5" PSA Pad
5136	6" PSA Pad
5145	Vacuum, 5" PSA, 6-hole Pad
5146	Vacuum, 6" PSA, 6-hole Pad
5235	5" Hook Pad
5236	6" Hook Pad
5245	Vacuum, 5" Hook, 6-hole Pad
5246	Vacuum, 6" Hook, 6-hole Pad

#### **Replacement Pads**

Part No.	Description
5246-19	Vacuum, 6" Hook, 19-hole Pad
5246W	Water, 6" Hook, 6-hole Pad

#### Accessories

Part No.	Description
780	Coaxial hose for 3950-70
12028	Tune-up Kit for 4500/4560
1301-1	Interface, 6" 6-hole Hook Pad
1350-4	Disposable Dust Bag Complete
1352	Muffler for 4500/4560
5859	Coaxial hose for 8970
5861	Coaxial hose for 4906, 4921, 4950-60
5862	Coaxial hose for 8620, 8623-25, 8650-60







Models 3950-70 require either 5301-2 or 5301-5 to complete the vacuum connection.

\*For hook-type tools not listed, add "H" to the sander part number (i.e. 3570H comes with a hook-pad instead of PSA)





## Straightline Sanders



All Hutchins Straightline sanders have dual cylinders with a common piston and vertically-engaged, twin-drive gears. This double rack and pinion gear assembly gives twice normal gear contact for maximum balance, thrust and longevity.

- Straightline sanders are used for shaping fillers and putties and for achieving a perfectly flat surface.
- The Linear motion replicates hand sanding with a block.

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
2000	2 3/4" x 16" Clip/PSA	6.2 CFM	3,000 SPM	90 dBa	6lb 4oz	No		No
2000-4H	4 1/2" x 16" Hook	6.2 CFM	3,000 SPM	90 dBa	6lb 4oz	No		No
2023	2 3/4" x 8" PSA	4.4 CFM	3,000 SPM	78 dBa	4lb 13oz	No		No
2025	4 1/2" x 9" Clip/PSA	4.4 CFM	3,000 SPM	78 dBa	4lb 14oz	No		No
4920*	2 3/4" x 16" PSA 18-hole	6.2 CFM	3,000 SPM	88 dBa	6lb 2oz	Vacuum		1"
4920-4H*	4 1/2" x 16" Hook 18-hole	6.2 CFM	3,000 SPM	88 dBa	6lb 2oz	Vacuum		1"
8620	2 3/4" x 16" PSA 18-hole	6.0 CFM	3,000 SPM	87 dBa	7lb 1oz	Self-Gen	5862/1350-4	1 <sup>1/2</sup> "
8623	2 3/4" x 8" PSA 8-hole	4.3 CFM	3,000 SPM	78 dBa	5lb 12oz	Self-Gen	5862/1350-4	1 <sup>1/2</sup> "
8625	4 1/2" x 9" Clip/PSA 8-hole	4.3 CFM	3,000 SPM	78 dBa	5lb 12oz	Self-Gen	5862/1350-4	1 <sup>1/2</sup> "

# CLEAN AR B623 13/16° Stroke

2000 15/16" Stroke

2025 13/16" Stroke 2023 13/16" Stroke

4920 15/16" Stroke

### Straightline Accessories

#### **Replacement Pads**

Part No.	Description
5002-H	2 3/4" x 16" Hook Pad
5003	2 3/4" x 16" PSA Pad
5005	4 1/2" x 16" PSA Pad
5005-H	4 1/2" x 16" Hook Pad
5005-HVA	Vacuum, 4 1/2" x 16" 18-hole Hook Pad
5006-H	Vacuum, 2 3/4" x 8" Hook Pad
5011	2 3/4" x 11" PSA Pad
5011-H	2 3/4" x 11" Hook Pad
5013	Vacuum, 2 3/4" x 16" 18-hole PSA Pad
5013-H	Vacuum, 2 3/4" x 16" 18-hole Hook Pad
5023	2 3/4" x 8" PSA Pad(PSA paper only)
5023-H	2 3/4" x 8" Hook Pad

### **Replacement Pads**

Part No.	Description
5025	4 1/2" x 9" Clip/PSA Pad
5025-H	4 1/2" x 9" Hook Pad

#### Accessories

Part No.	Description
12027	Tune-up Kit for 2000
1350-4	Disposable Dust Bag Complete
5301-1	VA Connector Hose Fitting
5301-2	Connector (1 $^{1/2n}$ OD Vac line)
5862	Coaxial hose for 8620, 8623-25, 8650-60
780	Coaxial hose for current 4920, 4920H, 4920-4H



\*For hook-type tools not listed, add "H" to the sander part number (i.e. 2000H comes with a hook-pad instead of PSA)





## Legacy Orbital Sanders





Orbital Action Sanders are versatile and adapt to every surface preparation need. Developed in the early 50's, this style of sander still is preferred for marine, industrial, and automotive applications. Because the fixed pad orbits an offset counterweight, fast sanding and smooth finish results can be expected.

- 3/32" offset orbitals sanders are used mainly for pre & post paint operations and are generally used for wet • sanding applications.
- 3/16" offset orbitals sanders are more aggressive and used for applications requiring fast material removal ٠ and super-flat surface finishes.

Part No.	Offset	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
3800	3/16"	2 3/4" x 16" PSA/Clip	11.4 CFM	8,500+ RPM	89 dBa	5lb 5oz	No		No
3800-4H	3/16"	4 1/2" x 16" Hook	11.4 CFM	8,500+ RPM	89 dBa	6lb 5 oz	No		No
3805	3/16"	8" x 18" PSA	11.4 CFM	8,500+ RPM	89 dBa	6lb	No		No
3806	3/16"	8" x 18" Padded PSA/Clip	11.4 CFM	8,500+ RPM	89 dBa	6lb	No		No
3900	3/16"	4 1/2" x 9" PSA/Clip	11.4 CFM	8,500+ RPM	90 dBa	5lb 2 oz	No		No
4564	3/16"	3 2/3" x 7" PSA/Clip	10.4 CFM	8,500+ RPM	80 dBa	3lb 7oz	No		No
4932*	3/16"	2 3/4" x 16" PSA -hole	11.5 CFM	8,500+ RPM	91 dBa	5lb 6oz	VA/Self-Gen		1"
4932-4H*	3/16"	4 1/2" x 16" Hook Multi-hole	11.5 CFM	8,500+ RPM	91 dBa	7lb 4 oz	VA/Self-Gen		1"
4933	3/16"	4 1/2" x 9" PSA 10-hole	10.8 CFM	8,500+ RPM	88 dBa	5lb 4 oz	VA/Self-Gen		1"
8664	3/16"	3 2/3" x 7" PSA 10-hole	11.5 CFM	8,500+ RPM	88 dBa	4lb 12 oz	Self-Gen	5862/1350-4	1 <sup>1/2</sup> "
Water Sa	anders								
7004	3/32"	3 2/3" x 7" PSA/Clip	10.2 CFM	8,500+ RPM	76 dBa	3lb 14oz	No		No
7044	3/32"	3 2/3" x 7" Hook/Clip	10.4 CFM	8,500+ RPM	81 dBa	4lb 1oz	No	1301	No
7044-6	3/32"	6" Hook	10.4 CFM	8,500+ RPM	81 dBa	4in 1oz	No	1301-1	No

### Orbital <u>Accessories</u>

#### **Replacement Pads**

Part No.	Description
1802	2 3/4" x 16" PSA Pad (Model 3800)
1802-5	Vacuum, 2 3/4" x 16" 18-hole PSA Pad (Model 4932)
1902	4 1/2" x 9" PSA/Clip Pad (Model 3900)
1902H	4 1/2" x 9" Hook Pad (Model 3900)
1902-3H	Vacuum, 4 1/2" x 9" 10-hole Hook Pad (Model 4933)
5005	4 1/2" x 16" PSA Pad (Model 3800. 3800-4)
5005H	4 1/2" x 16" Hook Pad (Model 3800, 3800-4H)
5005HVA	Vacuum, 4 1/2" x 16" 18-hole Hook Pad (Model 4932)
5802	2 3/4" x 16" Hook Pad (Model 3800)
5803	Vacuum, 2 3/4" x 16" 18-hole Hook Pad (Model 4932)
5864A	Water, 3 2/3" x 7" Hook Pad (Model 7044)
5864R	3 2/3" x 7" PSA/Clip Pad (Model 4564)
5864W	Water, 3 2/3" x 7" PSA/Clip Pad & Water Line (Model 7004)

#### **Replacement Pads**

Part No.	Description
5864A	Water, 3 2/3" x 7" Clip Pad (Model 7044)
5866A	Water, 6" Hook Pad (Model 7044-6)

#### Accessories

Part No.	Description
1301	Interface Pad, 3 2/3" x 7" 10-Hole Hook Pad (Model 7044)
1301-1	Interface Pad, 6" 6-Hole Hook Pad (Model 7044-6)
1350-4	Disposable Dust Bag Complete
5301-2	Connector (1 <sup>1/2</sup> " OD Vac line)
780	Coaxial Hose for current 4932, 4932H, 4932-4H







\*For hook-type tools not listed, add "H" to the sander part number (i.e. 3800H comes with a hook-pad instead of PSA)



4932



4564









## Legacy Rotary Sanders





Hutchins Rotary sanders offer reduced gear drive action to increase operator control and to control heat generation to lessen distortion.

- Rotary Sanders operate in a circular motion.
- Rotary sanders are generally used for shaping fillers and grinding metals and composites.
- Reduced gear rotary sanders are ideal for Aluminum Preparation.

Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/ Self-Gen.	Accessories Included	Vac Port OD
2001	8" PSA	16 CFM	1,750 RPM	86 dBa	5lb 14oz	No		No
2001-11H	11" Hook	16 CFM	1,750 RPM	86 dBa	7lb 3 oz	No		No
2006	6" Hook	11 CFM	1,750 RPM	82 dBa	4lb 3oz	No		No
4906	6" Hook 6-hole	11 CFM	1,750 RPM	85 dBa	6lb	Vacuum	1345-3	1 <sup>1/2</sup> "
4921	8" PSA 8-12-hole	16 CFM	1,750 RPM	86 dBa	6lb	Vacuum	1743	1 <sup>1/2</sup> "
4921-11H	11" Hook 8-12 hole	16 CFM	1,750 RPM	86 dBa	7lb 3 oz	Vacuum	1743	1 <sup>1/2</sup> "









### **Rotary Accessories**

#### **Replacement Pads**

Part No.	Description
5017	8" PSA Pad (Model 2001)
5017-11	11" PSA Pad (Model 2001-11)
5018	Vacuum, 8" PSA 8-12 hole Pad (4921 Series)
5018-11	Vacuum, 11" PSA 8-12 hole Pad (Model 4921-11)
5019	8" Hook Pad (Model 2001H)
5019-11	11" Hook Pad (Model 2001-11H)
5020	Vacuum, 8" Hook 8-12 hole Pad (Model 4921H)
5020-11	Vacuum, 11" Hook 8-12 hole Pad (Model 4921-11H)
5028H	Vacuum, 8" PSA 8 hole Pad (4906 only)
5108H	8" Hook Pad (2006 only)
5115	5" Hook Pad (2006 only)
5116	6" Hook Pad (2006 only)
5116V	Vacuum, 6" Hook 6- hole Pad (4906 only)

#### Accessories

Part No.	Description
1743	Exhaust Hose Assembly (4921 Series)
5021	8" Polishing Kit
5022	8" Polishing Pad
5861	Coaxial Hose for 4906, 4921, 4950, 4960





\*For hook-type tools not listed, add "H" to the sander part number (i.e. 2001H comes with a hook-pad instead of PSA)







### Speed Files



5541H

Long before pneumatic sanders made the scene; Autobody craftsmen were using Speed Files (hand boards) to guarantee a precisely shaped panel. Whether the desired effect is a gentle curve or a perfectly flat surface, Hutchins Speed Files offer the ultimate in comfort & control. Unlike cheap imitations, we use unfinished domestic hickory for our handles to eliminate hand blisters and splinters. Shaped for comfort; these Speed Files allow effortless sanding and outstanding results.

5542H



5501 Can be used with water



5502 Can be used with water



5504 Can be used with water

Part No.	Model	Pad Size/Type	Vacuum/ Self-Gen.
5501	PF-16	2 3/4" x 16" PSA/Clip Pad	No
5501H	PF-16	2 3/4" x 16" Hook Pad	No
5502	AF-16	2 3/4" x 16" PSA/Clip Pad	No
5502H	AF-16	2 3/4" x 16" Hook Pad	No
5504	AF-11	2 3/4" x 11" PSA/Clip Pad	No
5504H	AF-11	2 3/4" x 11" Hook Pad	No
5506	AF-8	2 3/4" x 8" PSA/Clip Pad	No
5506H	AF-8	2 3/4" x 8" Hook Pad	No
5507	F-16	2 3/4" x 16" PSA/Clip Pad	No
5507H	F-16	2 3/4" x 16" Hook Pad	No
5510	S-11	4" x 11" PSA/Clip Pad, Medium Radius	No
5511	C-11	4" x 11" PSA/Clip Pad, Broad Radius	No
5512	R-11	4" x 11" PSA/Clip Pad, Small Radius	No
5515	HF-16	Replacement Handle	No
5540	PF-16V	Vacuum, 2 3/4" x 16" PSA/Clip, 18-hole	Vacuum
5540H	PF-16V	Vacuum, 2 3/4" x 16" Hook Pad, 18-hole	Vacuum
5541H		4 1/2" x 9" Hook Pad, 1-Hand	No
5542H		4 1/2" x 9" Hook Pad, 2-Hand	No
5543		Faring Board, 4 $1/2$ " x 30" PSA Pad	No
5543H		Faring Board, 4 $1/2$ " x 30" Hook Pad	No
5548		Faring Board, 2 3/4" x 30" PSA Pad	No
5548H		Faring Board, 2 3/4" x 30" Hook Pad	No



5548





Can be used with water










### Anti-Static Airlines

Clear, crushproof, reinforced construction allows instant detection of airborne contamination. The anti-static design decreases electrical charge to improve metallic orientation for both solvent & water based paints. Reduces static charge and dust build-up on plastic parts and bumpers. The lightweight, durable design with a large inside diameter improves airflow for better spray gun and air tool operation.

Part No.	Description
1361-3A-35	Anti-Static 3/8 <sup>th</sup> Airline - 35 Feet
1361-3A-50	Anti-Static 3/8 <sup>th</sup> Airline - 50 Feet







Operating pressure to 225 PSI

**Operating temperature to 150F** 

urface Safe

Static Electricity, in the presence of Aluminum or Magnesium dust, can cause dangerous and possibly explosive results. The Hutchins Anti-Static Hose, when properly installed, can greatly reduce the risk of static electricity arcing. Please consult your local and State codes for recommended guidelines.

### Vacuum Accessories

#### Accessories

Part No.	Description
780	Coaxial Hose Assembly for Sanders with Swivel Vacuum Connection
1352-PVN	Swivel Upgrade for Models 4920, 4932 & 4933
1350-4	Disposable Dust Bag Complete
5859	1" Coaxial Hose Assembly for Models: 3950, 3960, 3970 & 8970
5860	1 $^{\scriptscriptstyle 1/2"}$ Coaxial Hose Assembly for Models: 4920, 4932 W/O SWIVELS (Prior to 2015)
5861	1 <sup>1/2</sup> " Coaxial Hose for Models: 4906, 4921, 4950 & 4960
5862	1 1/2" Coaxial Hose Assembly for Models: 8620, 8623-25, 8650 & 8660

#### **Common Vacuum Terms**

The term "VA" refers to Vacuum-Assist. Vacuum-Assist Sanders require an external vacuum source (i.e. portable vacuum system)

The term "Self-Gen" refers to Self-Generation. Self-Generation Sanders generate their own vacuum so they can be used alone or in conjunction with a vacuum system.



MUTCHINS 1350-4









Connectors

Part No.	Description	Top ID	Top OD	Bottom ID	Bottom OD
1345-2	Vacuum Assist Adapter Collar	1 <sup>1/8</sup> "	N/A	1 <sup>1/2</sup> "	N/A
1355-3	Exhaust Hose Coupling (for 1/4" ID airline)	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "
1355-3L	Exhaust Hose Coupling (for 3/8" ID airlines)	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "
1362	Exhaust Hose Coupling (no airline port)	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "
5301-1	Vacuum Connector Hose Fitting	5/8"	N/A	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "
5301-2	Connector (1 <sup>1/2</sup> " OD Vac line)	1 <sup>1/16</sup> "	1 <sup>1/2</sup> "	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "
5301-3	Vacuum Connector (1 " hoses)	5/8"	N/A	1" threaded	N/A
5301-4	Vacuum Reducer	1"	N/A	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "
5301-5	Connector (1" OD Vac line)	1 <sup>1/16</sup> "	1 <sup>1/2</sup> "	1" threaded	N/A
5304-1	Vacuum Connector	1 <sup>1/4</sup> "	1 <sup>1/2</sup> "	1 <sup>1/4</sup> " threaded	1 <sup>1/2</sup> "

