

PTW-2048, 20" X 48" 6,000 LB CAPACITY PALLET TRUCK

140172

JET® PTW Series Pallet Trucks are available in 5 different configurations. Each JET PTW Pallet Truck has a low profile of 2-7/8 inches, varying widths of 20 to 27 inches, and different lengths from 36 to 48 inches. High quality welded steel construction gives the PTW series a capacity of 6,000 pounds. The 200 degree turning radius increases maneuverability and the easy-to-use fingertip controls permit single handed operation. JET PTW Series Pallet Trucks are built to handle heavy lifting

FEATURES

- Capacity: 6,000 pounds
- Turning Radius: 200 degrees
- Overload Protection ball valve prevents lifting loads past maximum capacity
- Top-Stroke release valve prevents cylinder extension beyond maximum height
- Chrome-plated pump piston and ram provide corrosion resistance in any industrial environment
- One-piece cast iron pump has a built-in valve that lowers the material in a controlled decent
- Poly over aluminum 7 x 2 inch steer wheels ensure contact with uneven floors
- Steer wheels feature double sealed lubricated bearings

SPECIFICATIONS

Capacity (Lbs.)	6,000	
Turning Radius (Deg)	200	
Overall Fork Dimensions (L x W) (In.)	48 x 20-1/2	
Fork Width (In.)	6-1/4	
Lowered Height (In.)	2-7/8	
Maximum Height (In.)	7-3/4	
Number of Strokes to Reach Maximum Height	12	
Force Required to Pump @ Maximum Load (Lbs)	78	
Steer Wheel Size (In.)	7 x 2	
Load Wheel Size (OD x W) (In.)	2-7/8 x 3-11/16	
Force Required to Move Maximum Load (Lbs)	110	
Overall Dimensions (L x W x H) (In.)	63 x 20-1/2 x 47	
Weight (Lbs)	161	
W1 Fork Width (In)	6-1/4	
W2 Overall Width (In)	20-1/2	
L1 Fork Length (In)	48	
L2 Overall Length (In)	64-1/2	



PTW-2048, 20" X 48" 6,000 LB CAPACITY PALLET TRUCK

140172

FULL SERIES

STOCK NO	MODEL NO	CAPACITY (LBS.)	TURNING RADIUS (DEG)	OVERALL FORK DIMENSIONS (L X W) (IN.)	FORK WIDTH (IN.)	LOWERED HEIGHT (IN.)
140170	PTW-2036	6,000	200	36 x 20-1/2	6-1/4	2-7/8
140171	PTW-2042	6,000	200	42 x 20-1/2	6-1/4	2-7/8
140172	PTW-2048	6,000	200	48 x 20-1/2	6-1/4	2-7/8
140174	PTW-2742	6,000	200	42 x 27	6-1/4	2-7/8
140175	PTW-2748	6,000	200	48 x 27	6-1/4	2-7/8