



J-FK350-2K, 350MM FERROUS MANUAL COLD SAW

414214K

JET Coldsaws deliver clean, burr-free cuts and offer machine shop and fabrication professionals a list of features and standard design characteristics that you've come to expect from JET. All backed by the industry leading full service Two Year Warranty.

FEATURES

- 30" adjustable length material stop
- 350mm (14") Ferrous Cold Saw for steel, stainless and tough to cut alloys
- Double self-centering vise with adjustable gibs secures the material for burr free cuts
- Flood style coolant with flow control system extends blade life
- Heavy-duty cast iron frame base with easy access storage provides a stable cutting platform
- Quick tension and release mitering capabilities with stops at 45° right, 45° left, and 90° (center), capable of slotting
- Spring loaded whole hand trigger starts or stops the sawing process for easy smooth cutting and increased user safety
- Thermal overload protection with magnetic starter for increased electrical safety
- Two-piece cast iron blade guard system permits quick and easy blade changes without removing the guards





J-FK350-2K, 350MM FERROUS MANUAL COLD SAW

414214K

SPECIFICATIONS

Style (Type)	Ferrous
Tubing Round at 45 Degrees (In.)	3-1/2
Tubing Round at 90 Degrees (In.)	4-1/2
Tubing Rectangle at 45 Degrees (In.)	3-19/64 x 3
Solid Round at 45 Degrees (In.)	2-25/64
Solid Round at 90 Degrees (In.)	3
Weight (Lbs.)	794
Solid Square at 45 Degrees (In.)	2-25/64 x 2-25/64
Solid Square at 90 Degrees (In.)	3 x 3
Maximum Vise Opening (In.)	6
Motor (HP)	2HP, 220V, 3Ph 2/4P 7.22/4.92 Amps





J-FK350-2K, 350MM FERROUS MANUAL COLD SAW

414214K

FULL SERIES

STOCK NO	MODEL NO	BLADE SPEEDS (RPM)	STYLE (TYPE)	TUBING ROUND AT 45 DEGREES (IN.)	TUBING ROUND AT 90 DEGREES (IN.)	TUBING RECTANGLE AT 45 DEGREES (IN.)
414228	CS-275-1	54	Ferrous	3-19/64	3-19/64	2-3/16 x 2
414226	CS-275		Ferrous	3-19/64	3-19/64	2-3/16 x 2
414229	CS-315-1	54	Ferrous	3-1/2	3-1/2	
414227	CS-315		Ferrous	3-1/2	3-1/2	
414214K	J-FK350-2K		Ferrous	3-1/2	4-1/2	3-19/64 x 3
414217K	J-FK350-4K		Ferrous	3-1/2	4-1/2	3-19/64 x 3