



JTM-949EVS MILL WITH ACURITE 203 DRO WITH X AND Y-AXIS POWERFEEDS AND AIR POWERED DRAWBAR

690523

Constructed using the Meehanite® casting process, The JTM-949EVS, 9" x 49" Electronic Variable Speed Milling Machines provides consistent and reliable operation. The newly designed column and base incorporates a rigid, robust design. These new Mills have features you've come to expect and is backed by the industry-leading JET Two Year Warranty.



FEATURES

- New! JET designed Certified Meehanite® casting with enhanced ribbing ensures rigidity and tolerance retention
 - Swing away control box houses an e-stop and puts all controls at the operators fingertips
 - The innovative design of the machine base provides an easier solution to level the machine without raising it up off the floor
 - Automatic oiler releases 3 to 6 cc/cy of lubrication every 30 minutes
 - For added safety, the heavy-duty spindle break stops the spindle and interrupts the power, preventing accidental start-ups
 - The electrical box has been relocated to the back of the mill and houses two 115V outlets for powered accessories
 - CSA/CUS Certified
 - Class 7 spindle bearings support the spindle for maximum rigidity in heavy cutting applications
 - Spindle head is internally cooled extending bearing, belt and motor life
 - Table and ways are hardened up to 54 HRC and precision ground for greater accuracy
 - The X and Y-Axis are coated with Turcite-B for reduced vibration and smooth movements
 - Swing away safety shield
 - LED work lamp
 - Chip pan
 - Dual locks on all moveable surfaces
 - Way covers
- Drawbar
 - Tool box with tools



JTM-949EVS MILL WITH ACU-RITE 203 DRO WITH X AND Y-AXIS POWERFEEDS AND AIR POWERED DRAWBAR

690523

SPECIFICATIONS

Style (Type)	EVS
Digital Readout	ACU-RITE 203
Number of Axis	2
Powerfeed	X and Y-Axis
Power Draw Bar	Pneumatic
Spindle Taper (In. x TPI)	R-8
Table Size (L x W) (In.)	9 x 49
Quill Diameter (In.)	3-3/8
Number of Spindle Speeds	Variable
Range of Spindle Speeds (RPM)	60 - 4,500
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Spindle Travel (In.)	5
Head Movement (Deg.)	90° R & L, 45° F & B
Max Distance Spindle to Table (In.)	20-3/4
Distance Spindle to Column (Max.) (In.)	18-1/8
Distance Spindle to Column (Min.) (In.)	4-3/4
Collet Capacity	1/8 - 7/8





JTM-949EVS MILL WITH ACU-RITE 203 DRO WITH X AND Y-AXIS POWERFEEDS AND AIR POWERED DRAWBAR

690523

FULL SERIES

STOCK NO	MODEL NO	STYLE (TYPE)	DIGITAL READOUT	NUMBER OF AXIS	POWERFEED	POWER DRAW BAR
690501	JTM-949EVS/230	EVS			X-Axis	
690502	JTM-949EVS/230	EVS			X-Axis	Pneumatic
690503	JTM-949EVS/230	EVS			X and Y-Axis	
690504	JTM-949EVS/230	EVS			X, Y and Z-Axis	
691500	JTM-949EVS/230	EVS				
690520	JTM-949EVS/230	EVS	ACU-RITE 203	2	X-Axis	
690521	JTM-949EVS/230	EVS	ACU-RITE 203	2	X-Axis	Pneumatic
690522	JTM-949EVS/230	EVS	ACU-RITE 203	2	X and Y-Axis	
690523	JTM-949EVS/230	EVS	ACU-RITE 203	2	X and Y-Axis	Pneumatic
690524	JTM-949EVS/230	EVS	ACU-RITE 203	2	X, Y and Z-Axis	
690525	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Knee)	X-Axis	
690526	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Knee)	X-Axis	Pneumatic
690527	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Knee)	X and Y-Axis	
690528	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Knee)	X and Y-Axis	Pneumatic
690530	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Quill)	X-Axis	
690531	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Quill)	X-Axis	Pneumatic
690532	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Quill)	X and Y-Axis	
690533	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Quill)	X and Y-Axis	Pneumatic
690534	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Quill)	X, Y and Z-Axis	
690535	JTM-949EVS/230	EVS	Newall DP700	2	X-Axis	
690536	JTM-949EVS/230	EVS	Newall DP700	2	X-Axis	Pneumatic
690537	JTM-949EVS/230	EVS	Newall DP700	2	X and Y-Axis	

JTM-949EVS MILL WITH ACU-RITE 203 DRO WITH X AND Y-AXIS POWERFEEDS AND AIR POWERED DRAWBAR

690523

FULL SERIES

STOCK NO	MODEL NO	STYLE (TYPE)	DIGITAL READOUT	NUMBER OF AXIS	POWERFEED	POWER DRAW BAR
690539	JTM-949EVS/230	EVS	Newall DP700	2	X, Y and Z-Axis	
690540	JTM-949EVS/230	EVS	Newall DP700	3 (Knee)	X-Axis	
690541	JTM-949EVS/230	EVS	Newall DP700	3 (Knee)	X-Axis	Pneumatic
690542	JTM-949EVS/230	EVS	Newall DP700	3 (Knee)	X and Y-Axis	
690543	JTM-949EVS/230	EVS	Newall DP700	3 (Knee)	X and Y-Axis	Pneumatic
690544	JTM-949EVS/230	EVS	Newall DP700	3 (Knee)	X, Y and Z-Axis	
690545	JTM-949EVS/230	EVS	Newall DP700	3 (Quill)	X-Axis	
690546	JTM-949EVS/230	EVS	Newall DP700	3 (Quill)	X-Axis	Pneumatic
690547	JTM-949EVS/230	EVS	Newall DP700	3 (Quill)	X and Y-Axis	
690548	JTM-949EVS/230	EVS	Newall DP700	3 (Quill)	X and Y-Axis	Pneumatic
690549	JTM-949EVS/230	EVS	Newall DP700	3 (Quill)	X, Y and Z-Axis	
690529	JTM-949EVS/230	EVS	ACU-RITE 203	3 (Knee)	X, Y and Z-Axis	

Check out the collection of bench and stationary power tools we offer.