



JTM-1050 MILL WITH 3-AXIS ACU-RITE G-2 MILLPWR CNC

690940

JET offers complete, factory-installed CNC packages with your choice of 2 or 3-axis CNC controls. The Computer Numerical Control system brings the added precision of digital automation to the process, allowing the user greater control and efficiency. Meehanite® casted JET Vertical Mills with CNC packages deliver accurate results every time. All the features you've come to expect backed by the industry-leading JET Two Year Warranty



FEATURES

- CNC Vertical Milling Machine Package JTM-1050
- Features of the ACU-RITE MILLPWR G2 CNC Package
- Precision Ground Ball Screws eliminate backlash for precise lateral movements
- Closed loop feedback using Acu-Rite precision linear encoders with 0.00005" resolution
- Powerful DC Servo motor assemblies that include mounting castings and hardware
- Handwheels are included for manual operation
- Features of the ACU-RITE MILLPWR G2 CONTROLLER
- USB + Ethernet compatible
- Simplified navigation that eliminates multiple menu screens
- 12.1" High resolution display (1024 x 768) with 3D graphics
- 1 GHz Celeron® M processor
- Expanded tool library and Datum offsets
- Program preview provides a graphical representation prior to operation
- Program size limit increased by 90% to 9,999 steps
- Jog Control allows table movement, quickly from one location to another - using one axis at a time or any two axes simultaneously
- 3-D Contouring, ability to import and run G-code files from CAD/CAM programs
- Mirror/Repeat/Rotate/Explode/Merge, easily manipulate, explode and merge part programs to save time and reduce program steps
- Menu-prompted Conversational programming, easily create part programs, edit, reverse, change, delete and copy/move steps - follow the menu prompts and let MILLPWR G2 do the rest
- Built-in Calculator, perform standard, trig and geometry calculations and transfer them directly into part programs
- Custom Pockets and Islands utilize the new optimized path and ramp feed features
- Circles including the Pocket, Frame, Ring and Helix incorporate the new ramp feed feature
- May be used automatically or manually for ultimate shop versatility
- Available offline software
- Estimated runtime feature



JTM-1050 MILL WITH 3-AXIS ACU-RITE G-2 MILLPWR CNC

690940

SPECIFICATIONS

Style (Type)	CNC
CNC Package	ACU-RITE MILLPWR® G2
Number of Axis	3
Table Size (L x W) (In.)	10 x 50
Spindle Taper (In. x TPI)	R-8
Quill Diameter (In.)	3-3/8
Number of Spindle Speeds	Variable
Range of Spindle Speeds (RPM)	70 - 3,800
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Spindle Travel (In.)	5
Head Movement (Deg.)	90° R & L, 45° F & B
Max Distance Spindle to Table (In.)	19
Distance Spindle to Column (Max.) (In.)	26
Distance Spindle to Column (Min.) (In.)	5-1/2
Collet Capacity	1/8 - 7/8
Table Longitudinal Travel (In.)	35
Table Cross Travel (In.)	15-1/4



FULL SERIES

STOCK NO	MODEL NO	STYLE (TYPE)	CNC PACKAGE	NUMBER OF AXIS	TABLE SIZE (L X W) (IN.)	POWER DRAW BAR
690930	JTM-1050 CNC G2	CNC	ACU-RITE MILLPWR® G2	2	10 x 50	
690940	JTM-1050 CNC G2	CNC	ACU-RITE MILLPWR® G2	3	10 x 50	

Check out the collection of bench and stationary power tools we offer.