

ABOVE GROUND **USED OIL** STORAGE SYSTEMS



Used oil evacuation, storage and transfer is safer, cleaner and faster with a pump-assist system from JohnDow Industries. Ideal for new car dealers, tire and automotive service stores and dealers, heavy-duty fleet owners and operators and municipal garages.



STORAGE

SPECIFICATIONS:

MODEL NO.	STYLE	CAPACITY(GAL)	DIMENSIONS (LXWXH)	WEIGHT
AGS-180D	WORKBENCH	180	56" x 28" x 40"	725 LBS.
AGS-245D	VERTICAL	245	40" x 37-1/2" x 69"	1100 LBS.
AGS-285D	WORKBENCH	285	67" x 31" x 42"	1100 LBS.
AGS-500D	WORKBENCH	500	89" x 49" x 40"	1300 LBS.

Features include:

- UL Listed double-wall tank provides 110% secondary containment
- Meets UL 142 specifications as well as the requirements of Uniform Fire Code and NFPA 30
- Workbench style tanks in 180-, 285-, and 500-gallon capacities
- Vertical-style for space saving is available in a 245-gallon capacity
- UL Listed, 1" air-operated diaphragm pump has a 30 gpm capacity
- Automatic pump shut-off to prevent overfilling
- 3/4" x 10' suction hose with quick-connect coupler
- 2" drop tube with camlock fitting and dust cover
- Air filter/regulator
- Easy-to-read level gauge
- High gloss enamel finish
- Protective cover for pump and shut-off valve