

**For use with: Gasoline, Diesel, Kerosene,  
Bio-Diesel, Transmission Fluid**

FC-25GC



# 25 GALLON U.L. LISTED STEEL GAS CADDY

Designed for the professional automotive service facility. Tested and approved to UL requirements for leakage, rupture, stability, abuse and endurance. Meets OSHA approved standards - with safety the number one priority.

## Features include:

- 25-gallon capacity steel tank
- UL Listed and complies with OSHA guidelines
- UL Listed cast iron pump
- 10" steel wheels
- Fill level gauge
- Fire-screened vent and filler neck
- Wide footprint for stability
- 8' PVC suction/discharge hose with internal steel grounding wire
- Tank ground wire & clamp
- Decal set for contents identification
- Two-way filter kit available



HANDLING  
FUEL



### UL Listed Pump

This heavy-duty, UL Listed cast iron rotary pump with carbon vanes and Viton seals offers a two-way operation for siphoning or dispensing fuel. One gallon is delivered for every 12 revolutions on the pump handle.

### SPECIFICATIONS: JDI-FC-25GC

CAPACITY	25-GALLONS
MATERIAL	14-GAUGE STEEL
PUMP	TWO-WAY, UL LISTED CAST IRON ROTARY
WHEEL SIZE	10" HEAVY-DUTY STEEL
DIMENSIONS	21"W X 13"L X 46"H
WEIGHT	95 LBS.