



AIR OPERATED Oil & Grease DELIVERY SYSTEMS

OIL HANDLING

GREASE

Professional Quality. Complete Packages - includes all required equipment. Designed for 35 lb., 120 lb. and 400 lb. grease containers.

Includes - 50:1 high pressure pump, control handle, Z-swivel, drum cover, follower plate and 8' outlet hose.

| MODEL NO. | DELIVERY CONTAINER | WEIGHT |
|-----------|---|---------|
| JDL-5 | 35 LBS. | 22 LBS. |
| JDL-16 | 120 LBS. | 27 LBS. |
| JDL-16C | (SAME AS JDL-16 BUT INCLUDES CASTER BASE) | |
| JDL-55 | 400 LBS. | 35 LBS. |

SPECIFICATIONS:

| | |
|------------------------------|-------------------|
| PRESSURE RATIO | 50:1 |
| AIR INLET PRESSURE | 70 - 115 PSI |
| AIR INLET CONNECTION | 1/4" NPT (FEMALE) |
| AIR MOTOR EFFECTIVE DIAMETER | 2.4" (63MM) |
| MAX PRESSURE | 5600 PSI |
| OUTLET CONNECTION | 1/4" NPT (MALE) |



OIL

Complete Packages - includes all required equipment. For motor oil, synthetic oil, hydraulic oil and ATF. Designed for 16-gallon and 55-gallon drums.

Includes - 30:1 medium pressure pump, delivery gun, 10' delivery hose. 16-gallon package includes drum cover.

| MODEL NO. | DELIVERY CONTAINER | WEIGHT |
|-----------|--------------------|---------|
| JDL-16 | 16-GAL | 26 LBS. |
| JDL-55 | 55-GAL | 22 LBS. |

SPECIFICATIONS:

| | |
|------------------------------|-------------------|
| PRESSURE RATIO | 3:1 |
| AIR INLET PRESSURE | 70 - 115 PSI |
| AIR INLET CONNECTION | 1/4" NPT (FEMALE) |
| AIR MOTOR EFFECTIVE DIAMETER | 2.49" (63MM) |
| MAX PRESSURE | 348 PSI |
| OUTLET CONNECTION | 1/2" NPT (MALE) |

