71

Exceptional cutting performance

- > induction hardened edges cut soft, hard and piano wire
- > cuts material like bolts, nails, rivets, etc. up to 1/4" (6.0 mm) dia.
- > exceptional cutting performance with minimum effort because of new lever action design
- > cutting edge hardness (approx. 64 HRC)
- > chrome vanadium heavy-duty steel; forged, multi stage oil-hardened

Micro-structured cutting edges allow easy cutting of large cross-sections

Gripping surface below the joint for gripping and pulling wires with a diameter from 3/64" (1 mm)

71 12 200

Opening spring and locking device are integrated in the handles for comfortable work and protected transport

71 02 200 T BKA*

Pliers with tether attachment point for tool drop protection system



Micro-structured cutting edges allow easy cutting of large cross-sections



Opening spring and locking device are integrated in the handles for comfortable work and protected transport



With gripping surface below the joint for gripping and pulling wires with a diameter from 3/64"



71 01 160: High cutting force with a length of just 6 1/4" – ideal for small hands

60% less effort required

compared to conventional high leverage diagonal cutters. The lever-action mechanism ensures an extremely favorable lever ratio with very little friction. The cutting force is about 20 times higher than the handforce applied.

R









71 02 20



| Product Number | Packaging | ⊲ ⊸► Inch mm | | Pliers | Handles | Ø Inch Ø mm | Ø Inch Ø mm | Ø Inch Ø mm | Ø Inch Ø mm | ۵ ^۲ ۵ Ibs |
|-----------------|-----------|---------------------------|---|--------------------|---|----------------|----------------------------|--------------------------|--------------------------|-------------------------|
| 71 01 160 | x | <mark>6 1/4</mark> 160 | | black atramentized | plastic coated | 13/64 5.3 | 11/64 4.4 | <mark>1/8</mark> 3.2 | <mark>1/8</mark> 3.0 | 0.43 |
| 71 01 200 | x | <mark>8</mark> 200 | | black atramentized | plastic coated | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.74 |
| 71 02 200 | x | <mark>8</mark> 200 | | black atramentized | slim multi-component grips | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.81 |
| 71 02 200 T BKA | X | <mark>8</mark> 200 | M | black atramentized | slim multi-component grips, integrated tether attachment point | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | <mark>5/32</mark> 4.0 | <mark>9/64</mark> 3.6 | 0.83 |
| 71 12 200 | х | <mark>8</mark> 200 | | black atramentized | slim multi-component grips | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.84 |

*Learn more about our tethered tool system on pages 207-211

The recess in the blade allows easier cutting of thicker wires, e.g. for anchor bolts in false ceilings

Gripping surface below the joint for gripping and pulling wires with a diameter from 3/64" (1 mm)

71 32 200 / 71 32 200 T BKA*

Opening spring and locking device are integrated in the handles for comfortable work and protected transport

71 32 200 T BKA*

Pliers with tether attachment point for tool drop protection system











| | | | | | Cutting capacities | | | | |
|-----------------|-----------|--------------------------|--------------------|---|-------------------------|----------------------------|----------------------------------|--------------------------|-------------------------|
| Product Number | Packaging | ← ► Inch mm | Pliers | Handles | Ø Inch Ø mm | Ø Inch Ø mm | ● <mark>Ø Inch</mark> Ø mm | Ø Inch Ø mm | ۵ ^۲ ۵ Ibs |
| 71 31 200 | Х | <mark>8</mark> 200 | black atramentized | plastic coated | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.73 |
| 71 32 200 | | <mark>8</mark> 200 | black atramentized | slim multi-component grips | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.82 |
| 71 32 200 T BKA | x | <mark>8</mark> 200 | black atramentized | slim multi-component grips, integrated tether attachment point | <mark>1/4</mark> 6.0 | 13/64 5.2 | <mark>5/32</mark> 4.0 | <mark>9/64</mark> 3.6 | 0.84 |

20° angled head with singlesided joint bar and diagonal cutting edge for flush cutting; with space for gripping

71 22 200 / 71 22 200 T BKA*

Opening spring and locking device are integrated in the handles for comfortable work and protected transport

71 22 200 T BKA*

Pliers with tether attachment point for tool drop protection system

71 41 200

The recess in the blade allows easier cutting of thicker wires, e.g. for anchor bolts in false ceilings





<u>×20°</u>

| | | | | | | Cutting capacities | | | | |
|-----------------|-----------|---------------------------|--------------------------|--------------------|---|-------------------------|----------------------------|----------------------------------|--------------------------|-------------------|
| Product Number | Packaging | ⊲− ► Inch mm | | Pliers | Handles | Ø Inch Ø mm | Ø Inch Ø mm | ● <mark>Ø Inch</mark> Ø mm | Ø Inch Ø mm | ۲ <u>۵</u> Ibs |
| 71 21 200 | Х | <mark>8</mark> 200 | <u>∡2</u> 0° ▶٩ | black atramentized | plastic coated | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.73 |
| 71 22 200 | х | <mark>8</mark> 200 | <u>∡2</u> 0° ▶ MM | black atramentized | slim multi-component grips | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | 5/32 4.0 | <mark>9/64</mark> 3.6 | 0.82 |
| 71 22 200 T BKA | x | <mark>8</mark> 200 | <u>∡2</u> 0° ▶ ₩ | black atramentized | slim multi-component grips, integrated tether attachment point | 1/4 6.0 | 1 <mark>3/64</mark> 5.2 | <mark>5/32</mark> 4.0 | <mark>9/64</mark> 3.6 | 0.83 |
| 71 41 200 | x | <mark>8</mark> 200 | <u>⊀2</u> 0° ▶● | black atramentized | plastic coated | <mark>1/4</mark> 6.0 | <mark>13/64</mark> 5.2 | <mark>5/32</mark> 4.0 | <mark>9/64</mark> 3.6 | 0.73 |

View other cutters made by Knipex on our website.