

# LINCOLN

®

## **MODEL 1162 FULLY AUTOMATIC PNEUMATIC GREASE GUN**

The variable speed trigger provides excellent grease flow control while the advanced pump design eliminates traditional priming issues

- **Outstanding durability and dependability**
- **Fully automatic, continuous operation**
- **Variable-speed trigger**
- **Accessible check valve assembly**
- **Comfortable grip**
- **30" high-pressure hose with coupler and attachment clip**
- **Includes a combination filler nipple and bleeder valve**
- **Superior flow performance obtained through advanced design**



Pump Ratio:	40:1 at 150 psi
Max. Grease Pressure:	6,000 psi (414 bar)
Air Pressure Range:	40 - 150 psi (2.8 - 10.3 bar)
Weight:	5.375 lbs. (2.4 kg)

**LINCOLN**  
®

# LINCOLN

®

## **MODEL 3601 VALUE SERIES USED OIL RECEIVER**

**Designed to provide an affordable option to draining, transferring and evacuating used oil quickly and safely**

- **All-steel design includes reinforced caster supports for durability and dependability.**
- **18-gallon tank includes a preset air regulator that allows the use of standard shop air up to 150 psi.**
- **14-inch telescoping bowl with a height adjustment range of 45 to 72 inches.**
- **Reinforced dispensing hose doubles as a sight gauge to prevent overfilling.**
- **Includes safety valve**



### 3601 Used Fluid Receiver

Capacity:	18 gallons (68 L)
Fluid Types:	Motor oils, transmission fluids, power steering fluids
Weight:	66 lbs. (30 kg)

**LINCOLN**  
®

Discover other air cutting tools on our website.