7-1/4" Trackital CIRCULAR SAW

#1 CIRCULAR SAW PREFERRED BY PROFESSIONAL CONTRACTORS

- Powerful 15 AMP Motor Delivers 5,800 RPM for Proven Performance and Jobsite Durability
- Lower Guard Design Improves Performance when making Bevel and Narrow Cuts
- Large Cutting Capacity (2-3/8" at 90°, 1-3/4" at 45°)
- Two Built-in L.E.D. Lights Illuminate the Line of Cut for Increased Accuracy
- Well Balanced Design for Superior Handling and Performance
- Ideal for Framers, Builders, Masons and Siding Contractors



POWER

Powerful 15 AMP motor delivers 5,800 RPM for proven performance and jobsite durability

ACCURACY



Two built-in L.E.D. lights illuminate the line of cut for increased accuracy

DURABILITY



Heavy gauge aluminum wraparound base engineered for improved durability

CAPACITY



Large cutting capacity 2-3/8" at 90°, 1-3/4" at 45°

DURABILITY AND PERFORMANCE.

7-1/4" CIRCULAR SAW

Model 5007F

FEATURES & BENEFITS

- #1 Circular saw preferred by professional contractors
- Powerful 15 AMP motor delivers 5,800 RPM for proven performance and jobsite durability
- Lower guard design improves performance when making bevel and narrow cuts
- Large cutting capacity (2-3/8" at 90°, 1-3/4" at 45°)
- Two built-in L.E.D. lights illuminate the line of cut for increased accuracy
- Well balanced design for superior handling and performance
- AC/DC switch allows for use with alternative power sources
- Bevel cuts 0°- 45° for the most common angles
- Technologically advance centrifugal fan and baffle system for efficient cooling of the motor
- Large and easy-to-read markings on depth and bevel scales
- Flat motor housing design increases stability when changing blades
- Heavy gauge aluminum wraparound base for improved durability and straighter cuts
- Conveniently located shaft lock for easy blade replacement
- Built-in dust blower clears the line of cut for greater accuracy
- All-ball bearing construction for longer tool life
- Ideal for framers, builders, masons and siding contractors
- Double insulated

STANDARD EQUIPMENT

- 7-1/4" Carbide tipped blade (24T) (D-24826)
- Blade wrench (782016-4)

SPECIFICATIONS	
Blade diameter	7-1/4"
Arbor	5/8"
Max. cutting capacities: 90° 45°	2-3/8" 1-3/4"
No load speed	5,800 RPM
Watts out	2,000
AMPS (120V)	15.0
Overall length	12"
Net weight	11.1 lbs.
Shipping weight	14.0 lbs.
UPC code	088381-040181





Model 5007F

OPTIONAL ACCESSORIES

7 4 /411	CADDIDE	TIDDED	DIADEC
/-1/4"	CARBIDE	IIPPED	READES

		2 1, 1 421	
Part No.	Description	Part No.	Description
A-90009-B-10	16T General Contractor Blade	A-94839-10	24T Framing Blade
D-35352-10	24T General Contractor Blade	721261-A-10	16T Coated Framing Blade

Part No.	Description
A-94530-10	24T Ultra Coated Framing Blade
721251-A	40T Fine Crosscutting Blade

