
Trakita 4", 4-1/2" & 5" ANGLE GRINDER SERIES






Dual ball bearings for smooth power transfer to the gears are protected with a dust proof design



Labyrinth construction and protective zig-zag varnish seals the motor and bearings from contamination

PERFORMANCE



Compact, lightweight design is 1 lb. lighter and slim barrel grip is only 2.5" for continuous use (9557PB)

ACCURACY



Gear housing rotates 90° left and right for operator convenience in cutting applications

COMPACT POWER

4", 4-1/2" & 5" ANGLE GRINDER SERIES

Models 9553NB/K, 9554NB, 9557NB/PB & 9558NB/PB

Features & Benefits

- n Small circumference barrel grip (only 2.5") for added comfort
- n Protective zig-zag varnish seals motor from contaminants by forming a barrier under rotation
- n Labyrinth construction seals and protects the motor and bearings from dust and debris by creating a complex set of channels
- n 7.5 AMP motor design for high output power in a more compact tool (only 3.5 lbs.) (Models 9553NB & 9554NB have 6.0 AMP motor and are only 3.1 lbs.)
- n Large paddle switch for easy operation (Models 9557PB & 9558PB)
- Thicker coil wires are wound more closely to reduce heat and energy loss
- n All ball bearing design and metal gear housing for durability
- n Rotatable gear housing rotates 90° for cutting applications
- n AC/DC switch for use with alternative power sources (Models 9553NB & 9554NB have AC switch only)



Standard Equipment

9553NB/K

- n 4" Grinding Wheel (741405-2-1)
- n Wheel Guard (125272-7)
- n Lock Nut (224573-1)
- n Lock Nut Wrench (782420-7)
- n Side Handle (153489-2)
- n Inner Flange (224377-1)
- n Tool Case (824736-5) (Model 9553NBK)

9554NB

- n 4-1/2" Grinding Wheel (741424-8-1)
- n Wheel Guard (125273-5)
- n Lock Nut (224568-4)
- n Lock Nut Wrench (782422-3)
- n Side Handle (153489-2)
- n Inner Flange (224399-1)

9557NB/PB

- 4-1/2" Grinding Wheel (741424-8-1)
- n Wheel Guard (125273-5)
- n Lock Nut (193465-4)
- Lock Nut Wrench (782422-3)
- n Side Handle (153489-2)
- n Inner Flange (224399-1)

9558NB/PB

- 5" Grinding Wheel (741407-8-1)
- n Wheel Guard (125274-3)
- n Lock Nut (193465-4)
- n Lock Nut Wrench (782422-3)
- n Side Handle (153489-2)
- n Inner Flange (224399-1)

Specifications

Model	9553NB/K*	9554NB	9557NB	9557PB	9558NB	9558PB
Grinding Wheel	4"	4-1/2"	4-1/2"	4-1/2"	5"	5"
Wire Cup Brush	3"	3-1/2"	3-1/2"	3-1/2"	3-1/2"	3-1/2"
Sanding Disc	4"	4-1/2"	4-1/2"	4-1/2"	5"	5"
No Load Speed	11,000 RPM	10,000 RPM	11,000 RPM	10,000 RPM	11,000 RPM	10,000 RPM
AMPS (120V)	6.0	6.0	7.5	7.5	7.5	7.5
Spindle Thread	M10 x 1.25	5/8" - 11 UNC				
Overall Length	10-1/8"	10-1/8"	10-5/8"	10-5/8"	10-5/8"	10-5/8"
Net Weight	3.1 lbs.	3.1 lbs.	3.5 lbs.	3.5 lbs.	3.5 lbs.	3.5 lbs.
Shipping Weight	5.6 lbs./8.2 lbs.	6.0 lbs.	6.3 lbs.	6.5 lbs.	6.4 lbs.	6.6 lbs.
Master Carton Qty.	4/3	4	4	4	4	4
UPC Code	088381-06158-2	088381-06177-3	088381-06244-2	088381-06353-1	088381-06246-6	088381-06392-0

088381-06158-2 088381-06177-3 088381-06244-2 088381-06353-1 088381-06246-6 088381-06392-0 088381-06317-3



