



Recipro Saw - 11 AMP

Model JR3050T/ JR3050TZ

POWERFUL 11.0 AMP MOTOR FOR IMPROVED PERFORMANCE

- Variable speed trigger for precise cutting in a wide variety of applications
- "Tool-less" blade change and shoe adjustment for fast blade installation and removal
- Long 1-1/8" stroke for faster cutting
- Well-balanced design (only 7.3 lbs.) reducing operator fatigue and all-day use
- Built-in dust blower clears the line of cut for greater accuracy
- Large 2-finger trigger with lock-on button for added convenience (JR3050T only)



(Model JR3050TZ shown)

PRECISION



Variable speed trigger to match the speed to the application


EFFICIENCY



"Tool-less" blade change and shoe adjustment

POWER

2,800 SPM



Powerful 11 AMP motor for continuous operation

PERFORMANCE



Long 1-1/8" blade stroke length for faster cutting

POWERFUL 11.0 AMP MOTOR

Recipro Saw - 11 AMP

Model JR3050T/ JR3050TZ

FEATURES & BENEFITS

- Variable speed trigger for precise cutting in a wide variety of applications
- "Tool-less" blade change and shoe adjustment for fast blade installation and removal
- Long 1-1/8" stroke for faster cutting
- Well-balanced design (only 7.3 lbs.) for reduced operator fatigue and all-day use
- Built-in dust blower clears the line of cut for greater accuracy
- All-ball and needle bearing construction for longer tool life
- Large 2-finger trigger with lock-on button for added convenience (JR3050T only)
- Soft grip and handle for increased comfort
- Ideal for framers, carpenters, electricians, plumbers and general construction
- Double insulated

STANDARD EQUIPMENT

- 1 each 6" x 6 TPI all-purpose blade (723054-A)
- 1 each 6" x 18 TPI metal cutting blade (723066-A)
- Tool case

SPECIFICATIONS

	JR3050T	JR3050TZ
Length of stroke	1-1/8"	1-1/8"
Variable speed	0 - 2,800 SPM	0 - 2,800 SPM
AMPS	11	11
Overall length	17-3/4"	17-3/4"
Tool case	Yes	Yes
Net weight	7.3 lbs.	7.3 lbs.
Shipping weight	13.9 lbs.	13.9 lbs.
UPC code JR3050T	088381-061407	088381-687836



Model JR3050T



Model JR3050TZ



OPTIONAL ACCESSORIES

- Industrial reciprocating saw blades

Wood Cutting

Length	TPI	Thickness	Material	Part No.	Qty./Pkg.
8"	Progressive	.050"	HCS	723078-A-5	5
9"	3	.050"	HCS	723053-A-5	5
9"	6	.050"	HCS	723052-A-5	5
6"	6	.050"	BIM	23058-A-5	5
6"	6	.050"	BIM	723054-A-5	5
				23054-A-100	100
9"	6	.050"	BIM	723055-A-5	5
				723055-A-25	25
				723055-A-100	100
				723056-A-5	5
12"	6	.050"	BIM	723056-A-25	25
				723056-A-100	100
6"	6	.050"	HCS	723050-A-5	5
12"	6	.050"	HCS	723051-A-5	5

Metal Cutting

Length	TPI	Thickness	Material	Part No.	Qty./Pkg.
6"	Progressive	.035"	BIM	723079-A-5	5
3-1/2"	18	.035"	BIM	23061-A-5	5
4"	14	.035"	BIM	723062-A-5	5
				723065-A-5	5
6"	14	.035"	BIM	723065-A-25	25
				723065-A-100	100
4"	18	.035"	BIM	723063-A-5	5
				723066-A-5	5
6"	18	.035"	BIM	723066-A-25	25
				723066-A-100	100
9"	18	.035"	BIM	723069-A-5	5
6"	24	.035"	BIM	723067-A-5	5
				723067-A-25	25



Makita[®]

RECIPRO SAW


POWERFUL NEW 11.0 AMP MOTOR

- Variable Speed (0 – 2,800 SPM) Enables User to Match the Speed to the Application
- "Tool-Less" Blade Change and Shoe Adjustment for Fast Blade Installation and Removal
- Long 1-1/8" Stroke for Faster Cutting
- Well-Balanced Design (Only 7.3 lbs.) for Reduced Operator Fatigue and All-Day Use
- Built-in Dust Blower Clears the Line of Cut for Greater Accuracy



Model
JR3050T

POWER



Powerful 11.0 AMP motor for improved performance

PRECISION



Variable speed (0 – 2,800 SPM) enables user to match the speed to the application

PERFORMANCE



Long 1-1/8" stroke for faster cutting

EFFICIENCY



"Tool-less" blade change and shoe adjustment for fast blade installation and removal

NEW

POWERFUL 11.0 AMP MOTOR.

RECIPRO SAW

Model JR3050T

FEATURES & BENEFITS

- Powerful 11.0 AMP motor for improved performance
- "Tool-less" blade change and shoe adjustment for fast blade installation and removal
- Long 1-1/8" stroke for faster cutting
- All ball-and-needle bearing construction engineered for longer tool life
- Large 2-finger trigger for added convenience
- Soft grip and handle for increased operator comfort and control
- Ideal for framers, carpenters, electricians, plumbers and general construction
- Double insulated

STANDARD EQUIPMENT

- 1 ea. Blade (723054-A, 723066-A)
- Tool Case

SPECIFICATIONS

Length of Stroke	1-1/8"
Strokes per Minute	0 – 2,800 SPM
AMPS (120V)	11.0
Overall length	17-3/4"
Net weight	7.3 lbs.
Shipping weight	13.6 lbs.
UPC code	088381-061407

OPTIONAL ACCESSORIES

INDUSTRIAL RECIPRO SAW BLADES

Wood Cutting

Length	TPI	Thickness	Material	Part No.	Qty./Pkg.
8"	Progressive	.050"	HCS	723078-A-5	5
9"	3	.050"	HCS	723053-A-5	5
9"	6	.050"	HCS	723052-A-5	5
6"	6	.050"	BIM	23058-A-5	5
6"	6	.050"	BIM	723054-A-5	5
				23054-A-100	100
9"	6	.050"	BIM	723055-A-5	5
				723055-A-25	25
				723055-A-100	100
12"	6	.050"	BIM	723056-A-5	5
				723056-A-25	25
				723056-A-100	100
6"	6	.050"	HCS	723050-A-5	5
12"	6	.050"	HCS	723051-A-5	5

Metal Cutting

Length	TPI	Thickness	Material	Part No.	Qty./Pkg.
6"	Progressive	.035"	BIM	723079-A-5	5
3-1/2"	18	.035"	BIM	23061-A-5	5
4"	14	.035"	BIM	723062-A-5	5
				723065-A-5	5
6"	14	.035"	BIM	723065-A-25	25
				723065-A-100	100
4"	18	.035"	BIM	723063-A-5	5
				723066-A-5	5
6"	18	.035"	BIM	723066-A-25	25
				723066-A-100	100
9"	18	.035"	BIM	723069-A-5	5
				723067-A-5	5
6"	24	.035"	BIM	723067-A-25	25

