
Trakita TOP HANDLE JIG SAW

POWERFUL 6.5 AMP MOTOR ENGINEERED TO PROVIDE ACCURATE CUTS IN A VARIETY OF MATERIALS 6.5 AMP Motor and 3 Orbital Settings Plus Straight Cutting Deliver Faster and More Accurate Cuts in a Variety of Materials Variable Speed Control Dial (500 - 3,100 SPM) Enables User to Match the Speed to the Application • Through-the-Body Dust Port for Use with a Vacuum Provides Efficient **Dust Management Counterbalance System for Reduced Vibration** "Tool-less" Blade Change System for Fast Blade Installation and Removal Low Profile Design Engineered for Improved Handling in Compact Areas Tnakita. Model JV0600K



6.5 AMP motor engineered to deliver precise cuts in a variety of materials

LESS WEIGHT



Well-balanced design (only 5.2 lbs.) for reduced operator fatigue

BETTER FIT



Ergonomic rubber grip and 2-finger trigger provide comfort and control

PERFORMANCE



Through-the-body dust port provides optimal dust management

LESS VIBRATION.

TOP HANDLE JIG SAW

JV0600K

FEATURES & BENEFITS

- 6.5 AMP motor and 3 orbital setting plus straight cutting deliver faster and more accurate cuts in a variety of materials
- Variable speed control dial (500-3,100 SPM) enables user to match the speed to the application
- Through-the-body dust port for use with a vacuum provides efficient dust management
- Counterbalance system for reduced vibration
- "Tool-less" blade change system for fast blade installation and removal
- Low profile design engineered for improved handling in compact areas
- Well-balance design (only 5.2 lbs.) for reduced operator fatigue
- Die-cast aluminum housing base for added durability
- Built-in dust blower clears the line of cut for increased accuracy
- Ergonomic rubberized grip and 2-finger trigger for increased comfort
- Die-cast aluminum base adjusts from 0° 45° right or left
- Lock-on button for continuous operation
- Uses Tang shank blades

STANDARD EQUIPMENT

- Blade (792529-7)
- Wrench (783201-2)
- Tool case (824998-5)

SP	ECI	FI	CAT	rio	NS
21	_	ш	GA	ΙV	The same

Length of stroke	7/8"		
Capacities: Wood Steel	3-1/2" 3/8"		
Strokes per minute	500 – 3,100		
AMPS (120V)	6.5		
Overall length	9-1/4"		
Net weight	5.2 lbs.		
Shipping weight	9.2 lbs.		
UPC code	088381-620314		







OPTIONAL ACCESSORIES

- Guide rail: 55" (194368-5) 118" (194367-7)



- Guide rail adaptor set (193517-1)
- Cover plate (417852-6)
- Anti-splintering device (415524-7)
- Dust nozzle (417853-4)
- Hose complete 28-5 (A-34229)



