

10" Dual-Bevel Sliding Compound Miter Saw with Laser Model LS1019L

Largest Crown Molding Cutting Capacity in its Class



CAPACITY

6-5/8" Crown Molding (vertically nested) and 5-1/4" baseboard (vertical) cutting capacity



DESIGN

Unique 2-Steel Rail Sliding System offers a reduced footprint and operation flush against a wall



ACCURACY

See-through blade guard system for greater visibility of blade and



CONVENIENCE

In-front bevel lock for convenient operation









FEATURES

- 10" slide miter saw with the crown molding cutting capacity (6-5/8" nested) of a 12" miter saw
- Linear ball bearing system engineered to deliver "dead-on" accurate cuts
- Innovative direct drive gearbox and guard system is engineered for increased vertical cutting capacity (5-1/4")
- Positive miter stops at: 0°, 15°, 22.5°, 31.6°, 45°, and 60° left or right
- Electronic speed control maintains constant speed under load for smoother, higher quality cutting
- Integrated upper and lower 4-3/4" tall fence system offers added rigidity for more precise miter and bevel cuts
- Large-sized aluminum base improves stability of material for efficient cutting
- Soft start suppresses start-up reaction for smooth start-ups and longer gear
- Miters 0-60° left and right; bevels 0-48° left and right

SPECIFICATIONS

Power Type	Corded
AMPS	15
Max. no load speed	3,200 RPM
Blade Diameter	10"
Arbor	5/8"
Max. Cutting Capacity (miter 90°)	2-13/16" x 12"
Max. Cutting Capacity (miter 45°, L/R)	2-13/16" x 8-1/2"
Electric Brake	Yes
Laser Guide	Yes
Stand included	No
Net Weight	57.9 lbs.
UPC Code	088381-843980

STANDARD EQUIPMENT

- Vertical Vise (126617-2)
- Dust Bag (122852-0)
- Triangular Rule (762001-3)
- 10" x 5/8" 60T Micro-Polished Miter Saw Blade
- Wrench (781044-6)

OPTIONAL ACCESSORIES

- 10" 40T Miter Saw Blade (A-94758)
- 10" x 5/8" 60T Ultra-Coated Miter Saw Blade (A-94764)
- 10" x 5/8" 80T Ultra-Coated Miter Saw Blade (A-94770)
- Jobsite Miter Saw Stand (WST05)
- Crown Molding Stopper Set (192628-9)
- Dust Box (194175-6)
- Horizontal Vise (122930-6)