

12V MAX CXT™ LITHIUM-ION CORDLESS SELF-LEVELING CROSS-LINE RED BEAM LASER KIT (2.0AH)



2.0Ah
BATTERY

3
YEAR
WARRANTY
LITHIUM-ION
TOOL & BATTERY


ALSO AVAILABLE AS A BARE TOOL: SK105DZ

PRODUCT HIGHLIGHTS



VERSATILITY

Selectable horizontal/vertical cross lines required for level, align and plumb applications



VISIBILITY

Red line visibility range up to 82' and detectable up to 262' with Makita Laser Detector



COMPATIBILITY

12V max CXT™ battery delivers the convenience of a rechargeable tool battery



DURABILITY

Integrated pendulum lock enables slope incline applications and provides added protection

RELATED PRODUCTS

1. Wall/Ceiling Mount Bracket (LE00870137)
2. Green/Red Beam Laser Detector (LE00855702)
3. Compact Tripod (TKOLM1001F)
4. High Elevation Tripod (TKOLM5030F)
5. 18V LXT® Cordless Power Source (Power Source Only) (ADP05)



Learn more about measuring and layout tools we have.



NEW TOOL OVERVIEW SK105DNAX



FEATURES

- Bright 635 nm class II red laser with +/-1/8" at 33' for best-in-class accuracy
- Laser line fan angle spans past the 180° horizontal line and 160° vertical line positions for full reference line coverage
- Fast self-leveling line stability is achieved in up to 3 seconds for increased productivity
- Self-leveling is correctable up to 4° of slope allowing operation on uneven surfaces
- Dust and water resistance with IP 54 rating for increased durability
- Highly protected laser windows are recessed into the housing for increased durability
- Rubberized housing over-mold for increased protection
- Simplified one button user interface for ease of operation
- Low laser brightness mode conserve battery power for extended run-time performance

SPECIFICATIONS

| | |
|--|---------------------------------------|
| Battery | 12V max CXT™ Lithium-Ion |
| Line accuracy (at 33') | +/- 1/8" |
| Line beam direction | 2 line (horizontal, vertical) |
| Working range (line) | 82' |
| Working Range with Detector | 262' |
| Operating time (hours) | 40 |
| Laser diode | Class II, 635 nm |
| Leveling range | 4° |
| Debris resistance | IP54 rating (dust & water resistance) |
| Auto shut off | No |
| Net Weight | 1.9 lbs. |
| UPC Code (SK105DNAX) | .088381-878173 |
| UPC Code (SK105DZ) | .088381-851893 |

STANDARD EQUIPMENT

- 12V Max CXT™ Self-Leveling Cross-Line Red Beam Laser (SK105DZ)
- 12V Max CXT™ Lithium-Ion 2.0Ah Battery (BL1021B)
- 18V LXT® / 12V Max CXT™ Lithium-Ion Rapid Optimum Charger (DC18RE)
- Magnetic L-Adapter (LE00870131)
- Red Laser Target Plate (LE00785638)
- Kit Bag (832173-9)