




18v X2 LXT® Lithium-Ion (36v) Brushless Cordless Blower, Tool Only

Model XBU02Z

**BL™ BRUSHLESS MOTOR DELIVERS UP TO 120 MPH
AIR VELOCITY AND 473 CFM OF AIR VOLUME**

- Two 18V LXT® Lithium-Ion batteries deliver the power and run time for gas powered demands without leaving the 18V LXT® platform (batteries not included)
- Delivers up to 29 minutes of run time on dial setting 3 using two BL1850 18V LXT® 5.0Ah batteries
- 6-stage air velocity/volume selection dial with variable speed control trigger
- Zero emissions and reduced maintenance; no need for gas or oil

POWER



POWER - BL™ Brushless motor delivers up to 120 MPH air velocity and 473 CFM of air volume

INNOVATION



Two 18V LXT® Lithium-Ion batteries deliver the power and run time for gas powered demands

VERSATILITY



6-stage air velocity/volume selection dial with variable speed control trigger

CONVENIENCE



Zero emissions and reduced maintenance; no need for gas or oil



PORTABLE & VERSATILE

18v X2 LXT® Lithium-Ion (36v) Brushless Cordless Blower, Tool Only

Model XBU02Z

FEATURES & BENEFITS

- In-line fan design provides better tool balance and improved ergonomics
- Compact and ergonomic design at only 38-3/4" long
- Weighs only 9.9 lbs. with batteries (batteries not included) for reduced operator fatigue
- Rubberized soft grip provides increased comfort on the job
- Instant start-up; simply load two 18V LXT® batteries and the blower is ready to use
- Dual L.E.D. battery indicators show charge level for each 18V LXT® battery
- 3-stage telescoping long nozzle for user convenience
- Conveniently located hole on housing bottom for easy storage
- Lock-on button for continuous operation
- Features Extreme Protection Technology (XPT) which is engineered to provide increased dust and water resistance in harsh job site conditions
- Equipped with Star Protection Computer Controls™ to protect against overloading, over-discharging and over-heating
- Rapid Optimum Charger communicates with the battery's built-in chip throughout the charging process to optimize battery life by actively controlling current, voltage and temperature (battery and charger sold separately)
- Rapid Optimum Charger has a built-in fan to cool the battery for faster, more efficient charging (battery and charger sold separately)
- Makita technology delivers category-leading charge time so the battery spends more time working and less time sitting on the charger (battery and charger sold separately)
- Compatible with Makita 18V Lithium-Ion batteries with a Star symbol (batteries sold separately)
- 3-year warranty on the tool
- Only use genuine Makita batteries and chargers

STANDARD EQUIPMENT

- 3-Stage Telescoping Nozzle (455915-0)

SPECIFICATIONS

Max. Air Volume	473 CFM
Max. Air Velocity	120 MPH
No Load Speed (variable speed)	11,400 - 21,500 RPM
Battery	(2) 18V X2 LXT® Lithium-Ion
Overall Length	38-3/4"
Sound Pressure	96 dB(A)
Net Weight (with battery)	9.9 lbs.
Shipping Weight	7.5 lbs.
UPC Code	088381-693158



OPTIONAL ACCESSORIES

- 18V Lithium-Ion Rapid Optimum 4-Port Charger (DC18RD)



- 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830)



- 18V LXT® Lithium-Ion 4.0Ah Battery (BL1840)



- 18V LXT® Lithium-Ion 5.0Ah Battery (BL1850)



All specifications subject to change without prior notice. All models and accessories subject to stock on hand.
The Makita Teal Color is the trade dress of Makita Corporation and is protected under common law and registered with the U.S. Patent and Trademark Office.
NTF-0215 MA-5009-15



Learn more about leaf blowers and yard vacuums we have.