Date: 03/04/16

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:Glue Stick, General PurposePart Numbers: 35412 & 35454Product Type:HotMelt AdhesiveRestriction of use:None Identified

**Company Address:** Master Appliance Corp

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
WARNING:	MOLTEN ADHESIVE MAY CAUSE SI ADHESIVE VAPORS MAY CAUSE S OR RESPIRATORY SYSTEM.	EVERE BURNS SLIGHT IRRITATION OF THE EYES, SKIN	
	HAZARD CLASS	HAZARD CATEGORY	

SKIN IRRITATION

#### **Precautionary Statements**

Prevention: Response:	Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Not prescribed

2

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Paraffin waxes (petroleum), hydrotreated	64742-51-4	2 – 10

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Date: 03/04/16

4. FIRST AID MEASURES			
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. Get immediate medical attention.		
Skin contact:	Immediately wash skin thoroughly with soap and water. Remove contaminated clothing and footwear. Get immediate medical attention.		
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get immediate medical attention.		
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical attention.		
Symptoms:	See Section 11.		
5. FIRE FIGHTING MEASURES			
Extinguishing media:	Use NFPA Class B fire extinguishers (Carbon dioxide, all purpose dry chemical or alcohol foam) designed to extinguish flammable liquid fires. Polymer foam is preferred for large fires.		

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: Not a fire hazard.

Special firefighting procedures:

Hazardous combustion products:

Smoke. Oxides of carbon. Hydrocarbons.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.
Clean-up methods:	Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Dispose of contaminated material as waste according to Section 13.

## 7. HANDLING AND STORAGE

Handling:
-----------

Avoid skin contact with molten resins. Always be careful around molten material.

Store in cool dry place, optimum temperature below 90°F

Storage:

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

Date: 03/04/16

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER	
Paraffin waxes (petroleum), hydrotreated	2 mg/m3 TWA Fume.	None	None	None	
Engineering controls:		Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.			
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).				
Eye/face protection:	Safety g	Safety goggles or safety glasses with side shields.			
Skin protection:	•	Use impermeable gloves and protective clothing as necessary to prevent skin contact.			

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Specific gravity:
Vapor density:
Flash point:
Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Viscosity:
Decomposition temperature:

Hot Melt Yellow Slight Not available. Not determined Not determined 232 °C (449.6 °F) 85 °C (185 °F) (Mettler Softening Point) 0.98 g/cc Not determined Not applicable Not available. Not available. Not determined Not applicable Not determined Not determined Negligible Not available. Not available.

### **10. STABILITY AND REACTIVITY**

Stability:	Stable.			
Hazardous reactions:	Will not occur.			
Hazardous decomposition products:	Smoke. Oxides of carbon. Hydrocarbons.			
Incompatible materials:	None known			
Reactivity:	Not available.			
Conditions to avoid:	None known			

Date: 03/04/16

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation.
Skin contact:	When it is heated, this material may cause thermal burns. May cause transient skin irritation.
Eye contact:	May cause irritation.
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

No

No

Hazardous Component(s) LD50s and LC50s		Immediate and Delayed Health Effects		
Paraffin waxes (petroleum), hydrotreated	None		Irritant	
		400.0-		OSHA Carcinogen
Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen		(Specifically Regulated)

#### **12. ECOLOGICAL INFORMATION**

Ecological information:

Paraffin waxes (petroleum), hydrotreated

Not available.

No

#### **13. DISPOSAL CONSIDERATIONS**

 Information provided is for unused product only.

 Recommended method of disposal:
 Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product.

 Hazardous waste number:
 To the best of our knowledge, this product is not listed nor does it meet the criteria of a hazardous waste if discarded in its purchased form. However, under RCRA, it is the responsibility of the user to determine at the time of disposal whether a product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics under the new Toxicity Characteristics Leaching Procedure (TCLP) 40 Code of Federal Regulations 261.20-24.

### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Date: 03/04/16

### 14. TRANSPORT INFORMATION (continued)

#### International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

#### **15. REGULATORY INFORMATION**

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: Section 313:	None above reporting de minimis Immediate Health CERCLA/SARA None above reporting de minimis
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
anada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

#### Prepared by:

Ca

**Issue date:** 03/04/16

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, DHM Adhesives, Inc. ("DHM") does not assume responsibility for any results obtained by persons over whose methods DHM has no control. It is the user's responsibility to determine the suitability of DHM's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any DHM's products. In light of the foregoing, DHM specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of DHM's products. DHM further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Page 5 of 5