

Master SELECT ACCESS™ Lock®

#5401D Wall Mount Model



Use level to verify the lock is vertical



Mark the position of the screw holes on the surface

Instructions:

Opening the key storage compartment door

1. Open shutter door to reveal the dials and the release button
2. Rotate dials to the current combination (if the lock is new, the combination is set at the factory to 0-0-0-0)
3. Press down on the release button to open the door
4. Pull the door fully open
5. Add or remove keys
6. Close compartment door
7. Scramble the combination dials to lock the door and conceal your combination (A)
8. Close the shutter door (B)

To set a new combination:

The initial combination is set at the factory to 0-0-0-0.

1. Open the compartment door (see instructions above)
2. Push the reset lever left and down. The lever remains in this position
3. Rotate dials to your desired combination
4. Push the reset lever, up and right, back to the original position
5. Close the key storage compartment door
6. Scramble the combination dials to lock the door and conceal your combination (A)
7. Close the shutter door (B)

To hang wall mount model

You will need: pencil or marker, Phillips head screwdriver, level, drill, and drill bit. *For certain surfaces (masonry) anchors and a hammer are recommended.*

1. Open the compartment door (see instructions above)
2. Position the lock on the desired surface
3. Use level to verify the lock is vertical
4. Mark the position of the screw holes on the surface
5. Remove lock
6. Drill holes
7. If necessary, use hammer to place anchors
8. Position lock
9. Insert and tighten screws
10. Close compartment door
11. Scramble the combination dials to lock the door and conceal your combination (A)
12. Close the shutter door

Reminder:

- (A) The release button will open the lock until you scramble the dials
- (B) Keep the shutter door closed to increase weather resistance and to conceal the dials from view